

# The **tabularkv** package

Heiko Oberdiek  
<heiko.oberdiek at googlemail.com>

2006/02/20 v1.1

## Abstract

This package adds a key value interface for tabular by the new environment **tabularkv**. Thus the T<sub>E</sub>X source code looks better by named parameters, especially if package **tabularht** is used.

## Contents

<b>1</b>	<b>Usage</b>	<b>1</b>
1.1	Example . . . . .	2
<b>2</b>	<b>Implementation</b>	<b>2</b>
<b>3</b>	<b>Installation</b>	<b>3</b>
3.1	Download . . . . .	3
3.2	Bundle installation . . . . .	3
3.3	Package installation . . . . .	3
3.4	Refresh file name databases . . . . .	3
3.5	Some details for the interested . . . . .	4
<b>4</b>	<b>History</b>	<b>4</b>
[2005/09/22 v1.0]	. . . . .	4
[2006/02/20 v1.1]	. . . . .	4
<b>5</b>	<b>Index</b>	<b>4</b>

## 1 Usage

\usepackage{tabularkv}

The package provides the environment **tabularkv** that takes an optional argument with tabular parameters:

**width:** width specification, "tabular\*" is used.

**x:** width specification, **tabularx** is used, package **tabularx** must be loaded.

**height:** height specification, see package **tabularht**.

**valign:** vertical positioning, this option is optional;

values: top, bottom, center.

Parameter **valign** optional, the following are equivalent:

```
\begin{tabularkv}{... , valign=top}{1}... \end{tabularkv}  
\begin{tabularkv}{... }[t]{1}... \end{tabularkv}
```

## 1.1 Example

```
1 (*example)
2 \documentclass{article}
3 \usepackage{tabularkv}
4
5 \begin{document}
6 \fbox{%
7   \begin{tabularkv}[
8     width=4in,
9     height=1in,
10    valign=center
11   ]{@{}l@{\extracolsep{\fill}}r@{}}
12   upper left corner & upper right corner \\
13   \noalign{\vfill}\%
14   \multicolumn{2}{c}{\bounding box} \\
15   \noalign{\vfill}\%
16   lower left corner & lower right corner \\
17 \end{tabularkv}%
18 }
19 \end{document}
20 
```

## 2 Implementation

```
21 (*package)
22 Package identification.
23 \NeedsTeXFormat{LaTeX2e}
24 \ProvidesPackage{tabularkv}%
25 [2006/02/20 v1.1 Key value interface for tabular parameters (HO)]
26 \RequirePackage{keyval}
27 \RequirePackage{tabularht}
28 \let\tabKV@star@x\empty
29 \let\tabKV@width\empty
30 \let\tabKV@valign\empty
31
32 \define@key{tabKV}{height}{%
33   \setlength{\dimen@}{#1}%
34   \edef\@toarrayheight{to\the\dimen@}%
35 }
36 \define@key{tabKV}{width}{%
37   \def\tabKV@width{#1}%
38   \def\tabKV@star@x{*}%
39 }
40 \define@key{tabKV}{x}{%
41   \def\tabKV@width{#1}%
42   \def\tabKV@star@x{x}%
43 }
44 \define@key{tabKV}{valign}{%
45   \edef\tabKV@valign{[\@car #1\@nil]}%
46 }
47 \newenvironment{tabularkv}[1][]{%
48   \setkeys{tabKV}{#1}%
49   \nameuse{%
50     tabular\expandafter\expandafter\expandafter
51   }{%
52     \expandafter\expandafter\expandafter\expandafter\expandafter
53   }{%
54     \nameuse{endtabular\expandafter\expandafter\expandafter}%
55   }
56 
```

## 3 Installation

### 3.1 Download

**Package.** This package is available on CTAN<sup>1</sup>:

<CTAN:macros/latex/contrib/oberdiek/tabularkv.dtx> The source file.

<CTAN:macros/latex/contrib/oberdiek/tabularkv.pdf> Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

<CTAN:install/macros/latex/contrib/oberdiek.tds.zip>

TDS refers to the standard “A Directory Structure for TeX Files” (<CTAN:tds/tds.pdf>). Directories with `texmf` in their name are usually organized this way.

### 3.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDSScripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

### 3.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain TeX:

```
tex tabularkv.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>tabularkv.sty</code>	→ <code>tex/latex/oberdiek/tabularkv.sty</code>
<code>tabularkv.pdf</code>	→ <code>doc/latex/oberdiek/tabularkv.pdf</code>
<code>tabularkv-example.tex</code>	→ <code>doc/latex/oberdiek/tabularkv-example.tex</code>
<code>tabularkv.dtx</code>	→ <code>source/latex/oberdiek/tabularkv.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

### 3.4 Refresh file name databases

If your TeX distribution (teTeX, mikTeX, ...) relies on file name databases, you must refresh these. For example, teTeX users run `texhash` or `mktexlsr`.

---

<sup>1</sup><ftp://ftp.ctan.org/tex-archive/>

### 3.5 Some details for the interested

**Attached source.** The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk tabularkv.pdf unpack_files output .
```

**Unpacking with L<sup>A</sup>T<sub>E</sub>X.** The `.dtx` chooses its action depending on the format:

**plain T<sub>E</sub>X:** Run `docstrip` and extract the files.

**L<sup>A</sup>T<sub>E</sub>X:** Generate the documentation.

If you insist on using L<sup>A</sup>T<sub>E</sub>X for `docstrip` (really, `docstrip` does not need L<sup>A</sup>T<sub>E</sub>X), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{tabularkv.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL<sup>A</sup>T<sub>E</sub>X:

```
pdflatex tabularkv.dtx
makeindex -s gind.ist tabularkv.idx
pdflatex tabularkv.dtx
makeindex -s gind.ist tabularkv.idx
pdflatex tabularkv.dtx
```

## 4 History

[2005/09/22 v1.0]

- First public version.

[2006/02/20 v1.1]

- DTX framework.
- Code is not changed.

## 5 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	B
<code>\@car</code> .....	45
<code>\@empty</code> .....	28, 29, 30
<code>\@nameuse</code> .....	49, 54
<code>\@nil</code> .....	45
<code>\@toarrayheight</code> .....	34
<code>\`</code> .....	12, 14, 16
<code>\begin</code> .....	5, 7
<code>\define@key</code> .....	32, 36, 40, 44
<code>\dimen@</code> .....	33, 34
<code>\documentclass</code> .....	2

E	R		
\end . . . . .	17, 19	\RequirePackage . . . . .	25, 26
\extracolsep . . . . .	11		
		S	
		\setkeys . . . . .	48
		\setlength . . . . .	33
		T	
		\tabKV@star@x . . . . .	28, 38, 42, 50, 54
		\tabKV@valign . . . . .	30, 45, 52
		\tabKV@width . . . . .	29, 37, 41, 52
		\the . . . . .	34
		U	
		\usepackage . . . . .	3
		V	
		\vfill . . . . .	13, 15
		P	
		\ProvidesPackage . . . . .	23