

CTAN:macros/latex/contrib/oberdiek/

Heiko Oberdiek
<heiko.oberdiek at googlemail.com>

2011/04/23

1 Overview

accsupp (contents)	2010/01/16 v0.3 Accessibility support by marked content	[pdf] [dtx]
aliascnt (contents)	2009/09/08 v1.3 Alias counter	[pdf] [dtx]
alphalph (contents)	2010/04/18 v2.3 Converting numbers to letters	[pdf] [dtx]
askinlude (contents)	2008/08/11 v2.1 Interactive asking of included files	[pdf] [dtx]
atbegshi (contents)	2011/01/30 v1.15 At begin shipout hook	[pdf] [dtx]
atenddvi (contents)	2007/04/17 v1.1 At end DVI hook	[pdf] [dtx]
attachfile2 (contents)	2010/09/27 v2.6 attach files into PDF	[pdf] [dtx]
atveryend (contents)	2011/04/23 v1.7 Hooks at very end of document	[pdf] [dtx]
auxhook (contents)	2011/03/04 v1.3 Hooks for auxiliary files	[pdf] [dtx]
bigintcalc (contents)	2011/01/30 v1.2 Expandable big integer calculations	[pdf] [dtx]
bitset (contents)	2011/01/30 v1.1 Data type bit set	[pdf] [dtx]
bmpsize (contents)	2009/09/04 v1.6 Extract size and resolution data from bitmap files	[pdf] [dtx]

bookmark (contents)	2011/04/21 v1.21 PDF bookmarks	[pdf] [dtx]
catchfile (contents)	2011/03/01 v1.6 Catches the contents of a file	[pdf] [dtx]
centernot (contents)	2010/03/29 v1.2 Centers the not symbol horizontally	[pdf] [dtx]
chemarr (contents)	2006/02/20 v1.2 Chemical reaction arrows	[pdf] [dtx]
classlist (contents)	2008/08/11 v1.3 Record loaded classes	[pdf] [dtx]
colonequals (contents)	2006/08/01 v1.0 Colon equals symbols	[pdf] [dtx]
dvipscol (contents)	2008/08/11 v1.2 Fix for dvips.def	[pdf] [dtx]
embedfile (contents)	2011/04/13 v2.6 embed files into PDF	[pdf] [dtx]
engord (contents)	2010/03/01 v1.8 Provides English ordinal numbers	[pdf] [dtx]
eolgrab (contents)	2011/01/12 v1.0 Grab line end delimited argument	[pdf] [dtx]
epstopdf (contents)	2010/02/09 v2.5 Conversion with epstopdf on the fly	[pdf] [dtx]
etexcmds (contents)	2011/02/16 v1.5 Prefix for e-TeX command names	[pdf] [dtx]
flags (contents)	2007/09/30 v0.4 Flag setting in bit fields	[pdf] [dtx]
getttitlestring (contents)	2010/12/03 v1.4 Cleanup title references	[pdf] [dtx]
grfext (contents)	2010/08/19 v1.1 Managing graphics extensions	[pdf] [dtx]
grffile (contents)	2010/12/09 v1.13 Extended file name support for graphics	[pdf] [dtx]
hobsub (contents)	2011/04/23 v1.4 Subsetting bundle oberdiek	[pdf] [dtx]
hologo (contents)	2011/04/21 v1.5 Logo collection	[pdf] [dtx]

holtxdoc (contents)	2011/02/04 v0.21 Private additional ltxdoc support	[pdf] [dtx]
hopatch (contents)	2011/01/30 v1.0 Wrapper for package hooks	[pdf] [dtx]
hycolor (contents)	2011/01/30 v1.7 Color options of hyperref/bookmark	[pdf] [dtx]
hypbmsec (contents)	2007/04/11 v2.4 Bookmarks in sectioning commands	[pdf] [dtx]
hypcap (contents)	2011/02/16 v1.11 Adjusting anchors of captions	[pdf] [dtx]
hypdestopt (contents)	2008/08/08 v2.2 Hyperref destination optimizer	[pdf] [dtx]
hypdoc (contents)	2010/03/26 v1.9 Hyper extensions for doc.sty	[pdf] [dtx]
hypgtoe (contents)	2007/10/30 v0.1 Experimental links to embedded files	[pdf] [dtx]
hyphsubst (contents)	2008/06/09 v0.2 Substitute hyphenation patterns	[pdf] [dtx]
ifdraft (contents)	2008/08/11 v1.3 Switch for option draft	[pdf] [dtx]
iflang (contents)	2007/11/11 v1.5 Language checks	[pdf] [dtx]
ifluatex (contents)	2010/03/01 v1.3 Provides the ifluatex switch	[pdf] [dtx]
ifpdf (contents)	2011/01/30 v2.3 Provides the ifpdf switch	[pdf] [dtx]
ifvtex (contents)	2010/03/01 v1.5 Switches for detecting VTeX and its modes	[pdf] [dtx]
infwarerr (contents)	2010/04/08 v1.3 Providing info/warning/message	[pdf] [dtx]
inputenx (contents)	2011/04/10 v1.8 Enhanced input encoding handling	[pdf] [dtx]
intcalc (contents)	2007/09/27 v1.1 Expandable integer calculations	[pdf] [dtx]
kvdefinekeys (contents)	2011/04/07 v1.3 Defining keys	[pdf] [dtx]

kvoptions (contents)	2010/12/23 v3.10 Keyval support for L ^A T _E X options	[pdf] [dtx]
kvsetkeys (contents)	2011/04/07 v1.13 Key value parser	[pdf] [dtx]
letltxmacro (contents)	2010/09/02 v1.4 Let assignment for L ^A T _E X macros	[pdf] [dtx]
listingsutf8 (contents)	2007/11/11 v1.1 Adding support for UTF-8 to listings	[pdf] [dtx]
ltexcmds (contents)	2011/04/18 v1.20 L ^A T _E X kernel commands for general use	[pdf] [dtx]
luacolor (contents)	2011/04/23 v1.6 Coloring based on LuaTeX's node attributes	[pdf] [dtx]
luatex (contents)	2010/03/09 v0.4 LuaTeX basic definition package	[pdf] [dtx]
magicnum (contents)	2011/04/10 v1.4 Magic numbers	[pdf] [dtx]
makerobust (contents)	2006/03/18 v1.0 Making a macro robust	[pdf] [dtx]
mleftright (contents)	2010/09/25 v1.0 Usual delimiter spacing with left and right	[pdf] [dtx]
pagegrid (contents)	2009/12/04 v1.4 Print page grid in background	[pdf] [dtx]
pagesel (contents)	2008/08/11 v1.8 Selecting shipout output pages	[pdf] [dtx]
pdfcol (contents)	2007/12/12 v1.2 Maintaining additional color stacks for pdfTeX	[pdf] [dtx]
pdfcolfoot (contents)	2007/09/09 v1.1 pdfTeX's color stack for footnotes	[pdf] [dtx]
pdfcolmk (contents)	2008/08/11 v1.2 PDFtex COlor MarK	[pdf] [dtx]
pdfcolparallel (contents)	2010/01/11 v1.3 Fixed parallel with color stacks support	[pdf] [dtx]
pdfcolparcolumns (contents)	2010/01/11 v1.3 Color stacks support for parcolumns	[pdf] [dtx]
pdfcrypt (contents)	2007/04/26 v1.0 Setting pdf encryption	[pdf] [dtx]

pdfescape (contents)	2011/04/04 v1.12 Provides string conversions	[pdf] [dtx]
pdflscape (contents)	2008/08/11 v0.10 Landscape pages in PDF	[pdf] [dtx]
pdfrender (contents)	2010/01/28 v1.2 Access to some PDF graphics parameters	[pdf] [dtx]
pdftexcmds (contents)	2011/04/22 v0.16 Utilities of pdfTeX for LuaTeX	[pdf] [dtx]
picture (contents)	2009/10/11 v1.3 Dimens for picture macros	[pdf] [dtx]
pmboxdraw (contents)	2011/03/24 v1.1 Poor man's box drawing characters	[pdf] [dtx]
protecteddef (contents)	2011/01/31 v1.0 Definition of protected macros	[pdf] [dtx]
refcount (contents)	2010/12/01 v3.2 Data extraction from references	[pdf] [dtx]
rerunfilecheck (contents)	2011/04/15 v1.7 Rerun checks for auxiliary files	[pdf] [dtx]
resizegather (contents)	2010/03/01 v1.2 Automatically resizing of too large equations	[pdf] [dtx]
rotchiffre (contents)	2010/11/12 v1.0 Provides ROT13, ROT5, ROT18, ROT47	[pdf] [dtx]
scrindex (contents)	2008/08/11 v1.1 Package index with scr* classes	[pdf] [dtx]
selinput (contents)	2007/09/09 v1.2 Select input encoding	[pdf] [dtx]
setouterhbox (contents)	2007/09/09 v1.7 Set hbox in outer horizontal mode	[pdf] [dtx]
settobox (contents)	2008/08/11 v1.4 Getting box sizes	[pdf] [dtx]
soulutf8 (contents)	2007/09/09 v1.0 Adding support for UTF-8 to soul	[pdf] [dtx]
stackrel (contents)	2007/11/11 v1.2 Adding subscript option to stackrel	[pdf] [dtx]
stampinclude (contents)	2008/07/14 v1.0 Time stamp based including	[pdf] [dtx]

stringenc (contents)	2010/03/01 v1.8 Converts strings between encodings	[pdf] [dtx]
tabularht (contents)	2007/04/11 v2.5 Tabular with height specification	[pdf] [dtx]
tabularkv (contents)	2006/02/20 v1.1 Key value interface for tabular parameters	[pdf] [dtx]
telprint (contents)	2008/08/11 v1.10 Formatting of German phone numbers	[pdf] [dtx]
transparent (contents)	2007/01/08 v1.0 Using a pdfTeX's color stack for transparency	[pdf] [dtx]
twoopt (contents)	2008/08/11 v1.5 Definitions with two optional arguments	[pdf] [dtx]
uniquecounter (contents)	2011/01/30 v1.2 Provides unlimited unique counter	[pdf] [dtx]
zref (contents)	2011/03/18 v2.21 New reference scheme for LATEX 2 ε	[pdf] [dtx]

2 Packages

The `accsupp` package

Abstract

Since PDF 1.5 portions of a page can be marked for better accessibility support. For example, replacement texts or expansions of abbreviations can be provided. Package `accsupp` starts with providing a minimal low-level interface for programmers. Status is experimental.

1 Documentation	2
1.1 Macros	2
1.1.1 Feature options	2
1.1.2 Input methods	2
1.2 Workaround, option <code>space</code>	3
1.3 Driver options	3
1.3.1 Option <code>pdftex</code>	3
1.3.2 Option <code>dvipdfm</code>	3
1.3.3 Option <code>dvips</code>	4
1.3.4 Turning off page stream compression	4
2 Example	4
2.1 Example <code>\notparallel</code>	4
2.2 Example with <code>pdfstringdef</code>	4

3 Implementation	5
3.1 Package	5
3.2 Space setup	6
3.3 Driver detection and setup	6
3.4 Main macro	7
3.4.1 Input methods	9
3.5 Drivers	10
3.5.1 Driver <code>pdftex</code>	10
3.5.2 Driver <code>dvipdfm</code>	10
3.5.3 Driver <code>dvips</code>	10
4 Test	10
4.1 Catcode checks for loading	10
5 Installation	11
5.1 Download	11
5.2 Bundle installation	11
5.3 Package installation	12
5.4 Refresh file name databases	12
5.5 Some details for the interested	12
6 References	13
7 History	13
[2007/03/21 v0.1]	13
[2007/11/14 v0.2]	13
[2010/01/16 v0.3]	13
8 Index	13

The `aliascnt` package

Abstract

Package `aliascnt` introduces *alias counters* that share the same counter register and clear list.

1 User interface	1
1.1 Introduction	1
1.2 Syntax	2
2 Implementation	2
2.1 Identification	2
2.2 Create new alias counter	2
2.3 Counter clear list	3
3 Installation	3
3.1 Download	3
3.2 Bundle installation	4
3.3 Package installation	4
3.4 Refresh file name databases	4
3.5 Some details for the interested	4
4 Acknowledgement	5
5 References	5
6 History	5
[2006/02/20 v1.0]	5
[2006/08/16 v1.1]	5
[2006/09/25 v1.2]	5
[2009/09/08 v1.3]	5
7 Index	5

The `alphalph` package

Abstract

The package provides methods to represent numbers with a limited set of symbols. Both L^AT_EX and plain-T_EXare supported.

1 Documentation	2
1.1 Introduction	2
1.2 Use cases	2
1.2.1 Number system based on symbols	2
1.2.2 Wrap symbols around	3
1.2.3 Multiple symbols	3
1.3 Glossary	4
1.4 Package usage	4
1.5 User commands	4
1.6 Programmer commands	5
1.7 Design principles	5
1.7.1 Number presentation commands	5
1.7.2 General usability	6
2 Implementation	6
2.1 Begin of package	6
2.2 Catcodes	7
2.3 Package loading	8
2.4 ε -T _E X detection	8
2.5 Help macros	8
2.6 Symbol provider	9
2.6.1 Alphabet	9
2.7 Finding number of symbols	10
2.8 Methods	12
2.8.1 Common methods	12
2.8.2 Method ‘alph’	12
2.8.3 Method ‘wrap’	13
2.8.4 Method ‘mult’	14
2.9 User interface	14
3 Test	16
3.1 Catcode checks for loading	16
4 Macro tests	17
5 Installation	21
5.1 Download	21
5.2 Bundle installation	22
5.3 Package installation	22
5.4 Refresh file name databases	22
5.5 Some details for the interested	22

6 History	23
[1999/03/19 v0.1]	23
[1999/04/12 v1.0]	23
[1999/04/13 v1.1]	23
[1999/06/26 v1.2]	23
[2006/02/20 v1.3]	23
[2006/05/30 v1.4]	23
[2007/04/11 v1.5]	23
[2007/09/09 v2.0]	24
[2008/08/11 v2.1]	24
[2010/03/01 v2.2]	24
[2010/04/18 v2.3]	24
7 Index	24

The `askinclude` package

Abstract

This package replaces `\includeonly` by an interactive user interface.

1 Documentation	2
1.1 User interface	2
1.2 Single asking mode	4
1.3 Regular expressions	4
1.3.1 Method <code>makematch</code>	4
1.3.2 Method <code>pdfmatch</code>	5
1.4 History	6
1.5 New features of version 2	6
1.6 Compatibility to version 1	6
2 Implementation	6
2.1 Header and catcodes	6
2.2 Delay action after preamble	7
2.3 Write entry in <code>.aux</code> file	8
2.4 Remember <code>\include</code> files	8
2.5 Redefine <code>\include</code>	9
2.6 Store answer and match method in <code>.aux</code> file	9
2.7 Support for <code>\@includeonly</code>	10
2.8 Stop if <code>\includeonly</code> is active	10
2.9 <code>\includeonly</code>	10
2.10 Options	10
2.11 Strings	11
2.12 Set defaults	12
2.13 Questions	12
2.13.1 Generic question header	12
2.13.2 Display files	13
2.13.3 Previous answer	13
2.13.4 Current regular expression support	14
2.13.5 Main question text	14
2.13.6 Main question	14
2.14 Evaluate answer of main question	15
2.15 Ask for each file	18
3 Test	20
3.1 Included files	20
3.2 Special test setup	20
3.3 Common start	21
3.4 First run tests	24
3.5 Second run tests	28
3.6 Compatibility for changing from old to new	32
3.7 Regular expressions	34
3.8 Common end	34

4 Installation	35
4.1 Download	35
4.2 Bundle installation	35
4.3 Package installation	35
4.4 Refresh file name databases	36
4.5 Some details for the interested	36
5 Acknowledgement	37
6 References	37
7 History	37
[1991/11/05 v0.95]	37
[1991/11/05 v0.99]	37
[1991/11/07 v1.0]	37
[1991/12/13 v1.1]	38
[1994/11/02 v1.2e]	38
[2007/10/15 v1.0 (askinc)]	38
[2007/10/23 v2.0]	38
[2008/08/11 v2.1]	38
8 Index	38

The `atbegshi` package

Abstract

This package is a modern reimplementation of package `everyshi` without the burden of compatibility. It makes use of ε - \TeX 's if available. Both L^AT_EX and plain- \TeX are supported.

1 Documentation	2
1.1 Examples	4
1.1.1 Example: circle in background	4
1.1.2 Example: adding TrimBox for dvipdfmx	4
2 Method of \shipout overloading	5
2.1 \shipout	5
2.2 \afterassignment	5
2.3 Test for direct or indirect boxes	6
2.3.1 With ε - \TeX	6
2.3.2 Without ε - \TeX	6
2.3.3 \lastkern method	7
2.4 Output	8
2.5 Separate box register	8
2.6 Summary	8
2.6.1 With ε - \TeX	8
2.6.2 Without ε - \TeX , traditional way	9
2.6.3 \lastkern method	9
3 Implementation	10
3.1 Reload check and package identification	10
3.2 Catcodes	11
3.3 Preparations	12
3.4 Positioning	16
3.5 Patches	17
3.5.1 Package <code>crop</code>	17
3.5.2 Package <code>everyshi</code>	19
3.5.3 Class <code>memoir</code>	20
4 Test	22
4.1 Catcode checks for loading	22
5 Installation	26
5.1 Download	26
5.2 Bundle installation	26
5.3 Package installation	26
5.4 Refresh file name databases	27
5.5 Some details for the interested	27

6 History	27
[2007/04/17 v1.0]	27
[2007/04/18 v1.1]	27
[2007/04/19 v1.2]	27
[2007/04/26 v1.3]	28
[2007/04/27 v1.4]	28
[2007/06/06 v1.5]	28
[2007/09/09 v1.6]	28
[2008/07/18 v1.7]	28
[2008/07/19 v1.8]	28
[2008/07/31 v1.9]	28
[2009/12/02 v1.10]	28
[2010/03/01 v1.11]	28
[2010/03/25 v1.12]	28
[2010/08/18 v1.13]	28
[2010/12/02 v1.14]	28
[2011/01/30 v1.15]	28
7 Index	29

The `atenddvi` package

Abstract

L^AT_EX offers `\AtBeginDvi`. This package `atenddvi` provides the counterpart `\AtEndDvi`. The execution of its argument is delayed to the end of the document at the end of the last page. Thus `\special` and `\write` remain effective, because they are put into the last page. This is the main difference to `\AtEndDocument`.

1 Documentation	1
2 Implementation	2
3 Installation	3
3.1 Download	3
3.2 Bundle installation	4
3.3 Package installation	4
3.4 Refresh file name databases	4
3.5 Some details for the interested	4
4 History	5
[2007/03/20 v1.0]	5
[2007/04/17 v1.1]	5
5 Index	5

The `attachfile2` package

Abstract

This package can be used to attach files to a PDF document. It is a further development of Scott Pakin's package `attachfile` for pdfTEX. Apart from bug fixes, package `attachfile2` adds support for `dvips`, some new options, gets and writes meta information data about the attached files.

1 Documentation	2
1.1 Introduction	2
1.1.1 Future development	2
1.2 User interface	3
1.2.1 New options	3
1.2.2 Option color	3
1.2.3 Perl script <code>pdfatfi.pl</code>	4
1.3 Changes to <code>attachfile</code>	4
2 Implementation	5
2.1 Package	5
2.1.1 Loading of packages	5
2.1.2 Value checking	5
2.1.3 Option declarations	7
2.1.4 Option calling	10
2.1.5 Evaluate driver options	10
2.1.6 Evaluate options <code>draft/final</code>	11
2.1.7 Load driver file	12
2.1.8 Graphics	12
2.1.9 Reading the <code>.atfi</code> file	15
2.1.10 Writing the <code>.atfi</code> file	17
2.1.11 Annotation appearance	18
2.2 Drivers	20
2.2.1 pdfTEX	20
2.2.2 dvips	23
2.2.3 dvipdfmx	32
2.3 Perl script <code>pdfatfi.pl</code>	35
3 Installation	38
3.1 Download	38
3.2 Bundle installation	39
3.3 Package installation	39
3.4 Refresh file name databases	39
3.5 Script installation	39
3.6 Some details for the interested	40
4 References	40

5 History	40
[2005/02/23 v2.0]	40
[2005/10/07 v2.1]	41
[2006/08/17 v2.2]	41
[2007/04/11 v2.3]	41
[2008/07/29 v2.4]	41
[2009/09/25 v2.5]	41
[2010/09/27 v2.6]	41
6 Index	42

The `atveryend` package

Abstract

This L^AT_EX package provides two hooks for `\end{document}` that are executed after the hook of `\AtEndDocument`. `\AfterLastShipout` can be used for code that is to be executed right after the last `\clearpage` before the `.aux` file is closed. `\AtVeryEndDocument` is used for code after closing and final reading of the `.aux` file.

1 Documentation	2
1.1 Related work	3
2 Implementation	3
2.1 Tools	4
2.2 Hooks	4
2.3 Redefining <code>\enddocument</code>	6
2.3.1 L ^A T _E X kernel	6
2.3.2 Package <code>booklet</code> , file <code>2up.tex</code>	7
2.3.3 Class <code>dinbrief</code>	7
2.3.4 Class <code>combine</code>	8
2.3.5 Class <code>jpsj2</code>	10
2.3.6 Testing and redefining	11
2.4 Hack into <code>\enddocument</code>	12
2.5 Using hooks of other packages	12
2.5.1 Package <code>scrlfile</code>	12
2.5.2 Package <code>etoolbox</code>	12
2.6 Class <code>letter</code>	13
3 Test	14
3.1 Catcode checks for loading	14
4 Installation	16
4.1 Download	16
4.2 Bundle installation	16
4.3 Package installation	17
4.4 Refresh file name databases	17
4.5 Some details for the interested	17
5 Acknowledgement	17
6 References	18
7 History	18
[2009/12/06 v1.0]	18
[2009/12/07 v1.1]	18
[2009/12/09 v1.2]	18
[2009/12/11 v1.3]	18
[2010/01/25 v1.4]	18

[2010/03/24 v1.5]	18
[2011/04/15 v1.6]	18
[2011/04/23 v1.7]	19

8 Index **19**

The `auxhook` package

Abstract

Package `auxhook` provides hooks for adding stuff at the begin of `.aux` files.

1 User interface	1
2 Implementation	2
2.1 Identification	2
2.2 Hook setup	2
2.3 User macros	3
2.4 Patches	3
2.4.1 <code>\document</code>	3
2.4.2 <code>\@include</code>	4
3 Installation	4
3.1 Download	4
3.2 Bundle installation	5
3.3 Package installation	5
3.4 Refresh file name databases	5
3.5 Some details for the interested	5
4 References	6
5 History	6
[2006/05/31 v1.0]	6
[2007/04/06 v1.1]	6
[2009/12/14 v1.2]	6
[2011/03/04 v1.3]	6
6 Index	6

The `bignumcalc` package

Abstract

This package provides expandable arithmetic operations with big integers that can exceed TeX's number limits.

1 Documentation	2
1.1 Introduction	2
1.2 Conditions	2
1.2.1 Preconditions	2
1.2.2 Postconditions	3
1.3 Error handling	3
1.4 Operations	3
1.4.1 Num	3
1.4.2 Inv, Abs, Sgn	3
1.4.3 Min, Max, Cmp	4
1.4.4 Odd	5
1.4.5 Inc, Dec, Add, Sub	5
1.4.6 Shl, Shr	5
1.4.7 Mul, Sqr, Fac, Pow	6
1.4.8 Div, Mul	6
1.5 Interface for programmers	7
2 Implementation	8
2.1 Reload check and package identification	8
2.2 Catcodes	9
2.3 ε -TeX detection	10
2.4 Help macros	10
2.5 Expand number	10
2.6 Normalize expanded number	11
2.7 Num	12
2.8 Inv, Abs, Sgn	13
2.9 Cmp, Min, Max	13
2.10 Odd	15
2.11 Inc, Dec	16
2.12 Add, Sub	19
2.13 Shl, Shr	24
2.14 \BIC@Tim	27
2.15 Mul	29
2.16 Sqr	31
2.17 Fac	31
2.18 Pow	32
2.18.1 Help macros	35
2.18.2 Recursive calculation	35
2.19 Div	37
2.20 Mod	42

3 Test	45
3.1 Catcode checks for loading	45
3.2 Macro tests	46
3.2.1 Preamble with test macro definitions	46
3.2.2 Time	50
3.2.3 Test sets	51
4 Installation	59
4.1 Download	59
4.2 Bundle installation	60
4.3 Package installation	60
4.4 Refresh file name databases	60
4.5 Some details for the interested	60
5 History	61
[2007/09/27 v1.0]	61
[2007/11/11 v1.1]	61
[2011/01/30 v1.2]	61
6 Index	61

The `bitset` package

Abstract

This package defines and implements the data type bit set, a vector of bits. The size of the vector may grow dynamically. Individual bits can be manipulated.

1 Documentation	3
1.1 Introduction	3
1.2 Glossary	3
1.3 Design principles	4
1.4 Operator overview	5
1.5 Package loading	5
1.6 Operators	5
1.6.1 Miscellaneous	6
1.6.2 Import	6
1.6.3 Export	6
1.6.4 Logical operators	7
1.6.5 Shifting	7
1.6.6 Bit manipulation	7
1.6.7 Bit retrieval	8
1.6.8 Bit set properties	8
1.6.9 Queries	8
2 Implementation	9
2.1 Reload check and package identification	9
2.2 Catcodes	10
2.3 Package loading	11
2.4 Help macros	12
2.4.1 Number constant	12
2.4.2 General basic macros	12
2.4.3 Tail recursion	12
2.4.4 Check macros	13
2.5 Miscellaneous	13
2.6 Import	13
2.6.1 From binary number	13
2.6.2 From octal/hex number	14
2.6.3 From decimal number	16
2.7 Export	17
2.7.1 To binary number	17
2.7.2 To octal/hexadecimal number	19
2.7.3 To decimal number	21
2.8 Logical operators	23
2.8.1 <code>\bitsetAnd</code>	23
2.8.2 <code>\bitsetAndNot</code>	24
2.8.3 <code>\bitsetOr</code>	24
2.8.4 <code>\bitsetXor</code>	25

2.8.5	Shifting	26
2.8.6	\bitsetShiftLeft	26
2.8.7	\bitsetShiftRight	27
2.9	Bit manipulation	28
2.9.1	Clear operation	28
2.9.2	Set operation	29
2.9.3	Flip operation	30
2.9.4	Range operators	30
2.10	Bit retrieval	32
2.10.1	\bitsetGet	32
2.10.2	\bitsetNextClearBit, \bitsetNextSetBit	33
2.10.3	\bitsetGetSetBitList	35
2.11	Bit set properties	36
2.12	Queries	37
3	Test	38
3.1	Catcode checks for loading	38
3.2	Macro tests	40
3.2.1	Preamble	40
3.2.2	Time	40
3.2.3	Detection of unwanted space	41
3.2.4	Test macros	41
3.2.5	Test sets	42
4	Installation	57
4.1	Download	57
4.2	Bundle installation	58
4.3	Package installation	58
4.4	Refresh file name databases	58
4.5	Some details for the interested	58
5	History	59
[2007/09/28 v1.0]	59
[2011/01/30 v1.1]	59
6	Index	59

The **bmpsize** package

Abstract

Package **bmpsize** analyzes bitmap images to extract size and resolution data. It adds this feature to the graphics package that now do not need separate bounding box files for bitmap images. Additionally the implementation for the inclusion of bitmap images in some drivers of package **graphicx** are rewritten to support options **viewport**, **trim** and **clip**.

1 Documentation	2
1.1 Introduction	2
1.2 Bitmap image parsers	2
1.2.1 User interface	3
1.2.2 Hints	3
1.2.3 Test program	3
1.2.4 Interface for programmers	4
1.3 Improved bitmap inclusion	4
2 Implementation	4
2.1 Basic package bmpsize-base	4
2.2 Bitmap formats	11
2.2.1 png	11
2.2.2 jpg	12
2.2.3 bmp	20
2.2.4 gif	22
2.2.5 tiff	23
2.2.6 pnm	26
2.2.7 pam	30
2.2.8 xpm	36
2.2.9 tga	41
2.2.10 pcx	42
2.2.11 msp	44
2.2.12 sgi	45
2.3 Package bmpsize	45
2.4 Drivers	48
2.4.1 dvips	48
2.4.2 dvipdfm and dvipdfmx	50
2.5 Test program bmpsize-test.tex	53
3 Installation	55
3.1 Download	55
3.2 Bundle installation	55
3.3 Package installation	56
3.4 Refresh file name databases	56
3.5 Some details for the interested	56

4 References	57
4.1 URLs for bitmap format descriptions	57
4.1.1 JPEG	57
4.1.2 PNG	57
4.1.3 GIF	57
4.1.4 BMP	57
4.1.5 PCX	57
4.1.6 MSP	57
4.1.7 TIFF	57
4.1.8 TGA	57
4.1.9 SGI	58
4.1.10 WMF	58
4.1.11 XPM	58
5 History	58
[2006/08/24 v1.0]	58
[2007/02/18 v1.1]	58
[2007/04/11 v1.2]	58
[2007/05/01 v1.3]	58
[2007/11/11 v1.4]	58
[2008/08/11 v1.5]	58
[2009/09/04 v1.6]	58
6 Index	59

The **bookmark** package

Abstract

This package implements a new bookmark (outline) organization for package `hyperref`. Bookmark properties such as style and color can now be set. Other action types are available (URI, GoToR, Named). The bookmarks are generated in the first compile run. Package `hyperref` uses two runs.

1 Documentation	2
1.1 Introduction	2
1.2 Options	3
1.2.1 Options <code>draft</code> and <code>final</code>	3
1.2.2 Driver options	4
1.2.3 Layout options	4
1.2.4 Action options	4
1.2.5 Level options	5
1.2.6 Style definitions	6
1.2.7 Hook support	6
1.3 Compatibility with <code>hyperref</code>	7
1.4 Adding bookmarks at the end	7
1.5 Limitations/ToDos	8
2 Example	8
3 Implementation	9
3.1 Package	9
3.1.1 Requirements	9
3.1.2 Package options	11
3.1.3 Action options	15
3.1.4 Option <code>atend</code>	19
3.1.5 Option <code>style</code>	19
3.1.6 Options for source file location	20
3.1.7 Hook support	20
3.1.8 Driver setup and loading	21
3.1.9 Compatibility for <code>hyperref</code>	23
3.2 Driver for <code>dvipdfm</code>	24
3.3 Driver for <code>VTEX</code>	27
3.4 Driver for <code>pdfTEX</code>	31
3.5 Drivers with <code>pdfmark</code> specials	34
3.5.1 Driver <code>dvips</code>	34
3.5.2 Driver <code>dvipsone</code>	34
3.5.3 Driver <code>textures</code>	34
3.5.4 Common part	34
3.6 Common part for <code>pdftex</code> and <code>pdfmark</code>	37
3.6.1 Write auxiliary file	37
3.6.2 Read auxiliary data	39
3.7 Option <code>atend</code>	40

3.7.1	Hook	40
3.7.2	Drivers using hooks at end of document	40
3.7.3	Drivers using \AtEndDvi	40
4	Installation	41
4.1	Download	41
4.2	Bundle installation	41
4.3	Package installation	41
4.4	Refresh file name databases	42
4.5	Some details for the interested	42
5	References	42
6	History	43
[2007/02/19 v0.1]	43
[2007/02/20 v0.2]	43
[2007/02/21 v0.3]	43
[2007/02/22 v0.4]	43
[2007/03/02 v0.5]	43
[2007/03/03 v0.6]	43
[2007/03/07 v0.7]	43
[2007/04/09 v0.8]	43
[2007/04/25 v0.9]	43
[2007/05/29 v1.0]	43
[2007/07/13 v1.1]	44
[2007/09/25 v1.2]	44
[2008/08/08 v1.3]	44
[2008/09/13 v1.4]	44
[2009/08/13 v1.5]	44
[2009/12/06 v1.6]	44
[2009/12/07 v1.7]	44
[2009/12/17 v1.8]	44
[2010/03/30 v1.9]	44
[2010/04/03 v1.10]	44
[2010/04/04 v1.11]	44
[2010/04/08 v1.12]	44
[2010/07/23 v1.13]	44
[2010/09/02 v1.14]	45
[2010/09/25 v1.15]	45
[2010/10/19 v1.16]	45
[2010/10/25 v1.17]	45
[2010/11/05 v1.18]	45
[2011/03/20 v1.19]	45
[2011/04/13 v1.20]	45
[2011/04/21 v1.21]	45
7	Index	45

The `catchfile` package

Abstract

This package catches the contents of a file and puts it in a macro. It requires ε - \TeX . Both \LaTeX and plain- \TeX are supported.

1 Documentation	1
2 Implementation	2
2.1 Reload check and package identification	2
2.2 Catcodes	3
2.3 Preparations	4
2.4 Looking for primitive \input	4
2.5 Input file check	5
2.6 Catch file contents	5
3 Test	7
3.1 Catcode checks for loading	7
3.2 \LaTeX	8
3.3 plain \TeX	10
4 Installation	11
4.1 Download	11
4.2 Bundle installation	12
4.3 Package installation	12
4.4 Refresh file name databases	12
4.5 Some details for the interested	12
5 History	13
[2007/05/30 v1.0]	13
[2007/09/09 v1.1]	13
[2007/11/11 v1.2]	13
[2010/03/01 v1.3]	13
[2010/04/08 v1.4]	13
[2010/04/28 v1.5]	13
[2011/03/01 v1.6]	13
6 Index	14

The `centernot` package

Abstract

This package provides `\centernot` that prints the symbol `\not` on the following argument. Unlike `\not` the symbol is horizontally centered.

1 User interface	1
2 Implementation	2
3 Installation	2
3.1 Download	2
3.2 Bundle installation	3
3.3 Package installation	3
3.4 Refresh file name databases	3
3.5 Some details for the interested	3
4 History	4
[2006/12/02 v1.0]	4
[2007/05/31 v1.1]	4
[2010/03/29 v1.2]	4
5 Index	4

The `chemarr` package

Abstract

Very often chemists need a longer version of reaction arrows (`\rightleftharpoons`) with the possibility to put text above and below. Analogous to `amsmath`'s `\xrightarrow` and `\xleftarrow` this package provides the macro `\xrightleftharpoons`.

1 Usage	1
1.1 Example	1
2 Implementation	2
3 Installation	3
3.1 Download	3
3.2 Bundle installation	3
3.3 Package installation	3
3.4 Refresh file name databases	4
3.5 Some details for the interested	4
4 History	4
[2001/06/21 v1.0]	4
[2001/06/22 v1.1]	4
[2006/02/20 v1.2]	4
5 Index	5

The `classlist` package

Abstract

This package records the loaded classes and stores them in a list.

1 Documentation	1
1.1 Background	1
1.2 Usage	1
2 Implementation	2
3 Installation	4
3.1 Download	4
3.2 Bundle installation	4
3.3 Package installation	5
3.4 Refresh file name databases	5
3.5 Some details for the interested	5
4 History	5
[2005/06/19 v1.0]	5
[2005/06/19 v1.1]	6
[2006/02/20 v1.2]	6
[2008/08/11 v1.3]	6
5 Index	6

The `colonequals` package

Abstract

Package `colonequals` defines poor man's symbols for math relation symbols such as "colon equals". The colon is centered around the horizontal math axis.

1 User interface	1
1.1 Introduction	1
1.2 Symbols	2
1.3 Fine tuning	2
1.3.1 Example	3
2 Implementation	3
2.1 Identification	3
2.2 Distance control	3
2.3 Centered colons	3
2.4 Combined symbols	4
3 Installation	5
3.1 Download	5
3.2 Bundle installation	5
3.3 Package installation	5
3.4 Refresh file name databases	5
3.5 Some details for the interested	6
4 References	6
5 History	6
[2006/08/01 v1.0]	6
6 Index	6

The dvipscol package

Abstract

Color support for dvips in `dvips.def` involves the color stack of dvips. The package tries to remove unnecessary uses of the stack to avoid the error “out of coor stack space”.

1 Documentation	1
1.1 Introduction	1
1.2 Usage	2
1.2.1 With ε - \TeX	2
1.2.2 Without ε - \TeX	2
2 Implementation	2
3 Installation	3
3.1 Download	3
3.2 Bundle installation	3
3.3 Package installation	3
3.4 Refresh file name databases	4
3.5 Some details for the interested	4
4 History	4
[2000/08/31 v1.0]	4
[2006/02/20 v1.1]	4
[2008/08/11 v1.2]	4
5 Index	5

The `embedfile` package

Abstract

This package embeds files to a PDF document. Currently the only supported driver is pdfTeX ≥ 1.30 in PDF mode.

1 Documentation	2
1.1 Introduction	2
1.1.1 Future development	2
1.2 User interface	2
1.3 Collection support (PDF 1.7)	4
1.4 Export of object references	5
1.4.1 Example	5
1.5 Examples	6
1.5.1 plain TeX	6
1.5.2 Collection example	6
1.6 Package <code>dtx-attach</code>	7
2 Implementation	8
2.1 Reload check and package identification	8
2.2 Catcodes	9
2.3 Tools	10
2.4 Check for recent pdfTeX in PDF mode	10
2.5 Strings	10
2.6 Switches	11
2.7 Key value definitions	12
2.8 Embed the file	17
3 Test	22
3.1 Catcode checks for loading	22
3.2 Simple test	23
3.3 Test for ini-TeX	24
4 Installation	24
4.1 Download	24
4.2 Bundle installation	25
4.3 Package installation	25
4.4 Refresh file name databases	25
4.5 Some details for the interested	25
5 References	26
6 History	26
[2006/08/16 v1.0]	26
[2007/04/11 v1.1]	26
[2007/09/09 v1.2]	26
[2007/10/28 v2.0]	27
[2007/10/29 v2.1]	27

[2007/11/11 v2.2]	27
[2007/11/25 v2.3]	27
[2009/09/25 v2.4]	27
[2010/03/01 v2.5]	27
[2011/04/13 v2.6]	27

7 Index	27
----------------	-----------

The `engord` package

Abstract

The package generates the suffix of English ordinal numbers. It can be used with plain and L^AT_EX formats.

1 Usage	2
1.1 Package options	2
1.2 Examples	2
2 Implementation	3
2.1 Reload check and identification	3
2.2 Help commands for plain compatibility	4
2.3 User macros	5
2.4 Suffix generation	6
3 Test	8
3.1 Catcode checks for loading	8
4 Installation	9
4.1 Download	9
4.2 Bundle installation	10
4.3 Package installation	10
4.4 Refresh file name databases	10
4.5 Some details for the interested	10
5 History	11
[2000/05/23 v1.0]	11
[2003/04/28 v1.1]	11
[2006/02/20 v1.2]	11
[2007/04/11 v1.3]	11
[2007/04/26 v1.4]	11
[2007/09/09 v1.5]	11
[2007/09/20 v1.6]	11
[2008/08/11 v1.7]	11
[2010/03/01 v1.8]	12
6 Index	12

The `eolgrab` package

Abstract

This package implements a generic argument grabber to catch an argument that is delimited by the line end.

1 Documentation	1
1.1 Examples	2
1.1.1 Small L ^A T _E X document as example	3
1.1.2 L ^A T _E X document with environments	4
1.2 Limitations	4
2 Implementation	4
2.1 Reload check and package identification	4
2.2 Catcodes	6
2.3 Resources	6
2.4 Macro \eolgrab	7
3 Test	8
3.1 Catcode checks for loading	8
3.2 Tests for plain T _E X	9
4 Installation	10
4.1 Download	10
4.2 Bundle installation	10
4.3 Package installation	11
4.4 Refresh file name databases	11
4.5 Some details for the interested	11
5 References	12
6 History	12
[2011/01/12 v1.0]	12
7 Index	12

The `epstopdf` package

Abstract

This packages adds support of handling eps images to package `graphics` or `graphicx` with option `pdftex`. If an eps image is detected, `epstopdf` is automatically called to convert it to pdf format.

1 Documentation	2
1.1 Introduction	2
1.2 Requirements	2
1.3 Usage	3
1.4 Options	3
1.5 Configuration	5
1.5.1 System configuration file <code>epstopdf-sys.cfg</code>	5
1.5.2 User configuration file <code>epstopdf.cfg</code>	5
1.5.3 Conversion program	5
1.6 Other image formats	5
2 Implementation	6
2.1 Wrapper package	6
2.1.1 Option handling	8
2.2 Base package	8
2.3 Preparations	8
2.3.1 Relead check and identification	8
2.3.2 Catcodes	9
2.3.3 Load packages	10
2.4 Checks	10
2.5 Package loading	10
2.6 Options	11
2.6.1 Default setting	11
2.7 Make and verbose	11
2.8 Adding conversion support	12
2.9 Declare graphics rule	14
3 Test	15
3.1 Preface for standard catcode check	15
3.2 Catcode checks for loading	16
4 Installation	17
4.1 Download	17
4.2 Bundle installation	18
4.3 Package installation	18
4.4 Refresh file name databases	18
4.5 Some details for the interested	18

5 History	19
[2001/01/06 v1.0]	19
[2001/02/04 v1.1]	19
[2006/02/20 v1.2]	19
[2006/08/26 v1.3]	19
[2007/04/26 v1.4]	19
[2007/10/02 v1.5]	19
[2007/11/11 v1.6]	19
[2008/05/06 v1.7]	20
[2009/03/01 v1.8]	20
[2009/07/06 v1.9]	20
[2009/07/07 v1.10]	20
[2009/07/12 v2.0]	20
[2009/07/15 v2.1]	20
[2009/07/16 v2.2]	20
[2009/09/24 v2.3]	20
[2009/10/17 v2.4]	20
[2010/02/09 v2.5]	20
6 Index	21

The `etexcmds` package

Abstract

New primitive commands are introduced in ε -TEX. Sometimes the names collide with existing macros. This package solves this name clashes by adding a prefix to ε -TEX's commands. For example, ε -TEX's `\unexpanded` is provided as `\etex@unexpanded`.

1 Documentation	2
1.1 <code>\unexpanded</code>	2
1.2 <code>\expanded</code>	2
2 Implementation	2
2.1 Reload check and package identification	2
2.2 Catcodes	3
2.3 Provide <code>\newif</code>	4
2.4 Load package <code>infwarerr</code>	4
2.5 <code>\unexpanded</code>	5
2.6 <code>\expanded</code>	5
3 Test	6
3.1 Catcode checks for loading	6
3.2 Macro tests	8
4 Installation	9
4.1 Download	9
4.2 Bundle installation	9
4.3 Package installation	10
4.4 Refresh file name databases	10
4.5 Some details for the interested	10
5 History	11
[2007/05/06 v1.0]	11
[2007/09/09 v1.1]	11
[2007/12/12 v1.2]	11
[2010/01/28 v1.3]	11
[2011/01/30 v1.4]	11
[2011/02/16 v1.5]	11
6 Index	11

The `flags` package

Abstract

Package `flags` allows the setting and clearing of flags in bit fields and converts the bit field into a decimal number. Currently the bit field is limited to 31 bits.

1 Documentation	1
1.1 User interface	2
1.2 Requirements	2
1.3 ToDo	2
2 Implementation	2
3 Installation	5
3.1 Download	5
3.2 Bundle installation	6
3.3 Package installation	6
3.4 Refresh file name databases	6
3.5 Some details for the interested	6
4 History	7
[2007/02/18 v0.1]	7
[2007/03/07 v0.2]	7
[2007/03/31 v0.3]	7
[2007/09/30 v0.4]	7
5 Index	7

The `gettitledstring` package

Abstract

The L^AT_EX package addresses packages that are dealing with references to titles (`\section`, `\caption`, ...). The package tries to remove `\label` and other commands from title strings.

1 Documentation	2
1.1 Macros	2
1.2 Options	2
2 Implementation	2
2.1 Options	4
2.2 <code>\GetTitleString</code>	4
2.2.1 Expand method	5
2.2.2 Non-expand method	6
3 Test	7
3.1 Catcode checks for loading	7
3.2 Test of non-expand method	9
4 Installation	10
4.1 Download	10
4.2 Bundle installation	10
4.3 Package installation	10
4.4 Refresh file name databases	10
4.5 Some details for the interested	11
5 References	11
6 History	11
[2009/12/08 v1.0]	11
[2009/12/12 v1.1]	11
[2009/12/13 v1.2]	11
[2009/12/18 v1.3]	12
[2010/12/03 v1.4]	12
7 Index	12

The `grfext` package

Abstract

This package provides macros for adding and reordering graphics extensions of package `graphics`.

1 Documentation	2
1.1 Introduction	2
1.2 User interface	2
1.3 Package loading	2
1.4 Option support for package <code>graphicx</code>	2
1.5 plain T _E X	3
2 Implementation	3
2.1 Relead check and identification	3
2.2 Catcodes	4
2.3 plain T _E X	5
2.4 Add	5
2.5 Check	6
2.6 Remove	6
2.7 Print	7
2.8 Defining options for package <code>graphicx</code>	7
3 Test	8
3.1 Catcode checks for loading	8
3.2 Macro tests	9
3.2.1 Preamble	9
3.2.2 Detection of unwanted space	10
3.2.3 Generic test macros	10
3.2.4 Test for <code>\AppendGraphicsExtensions</code>	10
3.2.5 Test for <code>\PrependGraphicsExtensions</code>	11
3.2.6 Test for <code>\RemoveGraphicsExtensions</code>	12
4 Installation	12
4.1 Download	12
4.2 Bundle installation	12
4.3 Package installation	12
4.4 Refresh file name databases	13
4.5 Some details for the interested	13
5 References	13
6 History	14
[2007/09/30 v1.0]	14
[2010/08/19 v1.1]	14
7 Index	14

The grffile package

Abstract

The package extends the file name processing of package `graphics` to support a larger range of file names. For example, the file name may contain several dots. Or in case of pdfTEX in PDF mode the file name may contain spaces.

1 Usage	2
1.1 Option <code>multidot</code>	2
1.2 Option <code>babel</code>	2
1.3 Option <code>extendedchars</code>	2
1.4 Option <code>encoding</code>	3
1.4.1 Option <code>inputencoding</code>	3
1.4.2 Option <code>filenameencoding</code>	3
1.4.3 Example	3
1.5 Option <code>space</code>	3
1.6 General use	4
1.7 Default settings	4
2 Implementation	4
2.1 Identification	4
2.2 Catcode stuff	4
2.3 Options	5
2.4 Fix <code>\Gin@ii</code> of package <code>graphicx</code>	11
3 Test	12
3.1 Multidot with default rule	12
4 Installation	13
4.1 Download	13
4.2 Bundle installation	13
4.3 Package installation	14
4.4 Refresh file name databases	14
4.5 Some details for the interested	14
5 References	15
6 History	15
[2004/07/18 v0.5]	15
[2006/08/15 v1.0]	15
[2006/08/17 v1.1]	15
[2006/11/30 v1.2]	15
[2007/04/11 v1.3]	15
[2007/06/13 v1.4]	15
[2007/08/16 v1.5]	15
[2007/11/11 v1.6]	15
[2007/11/24 v1.7]	15
[2008/08/11 v1.8]	15

[2008/10/13 v1.9]	16
[2009/09/25 v1.10]	16
[2010/01/28 v1.11]	16
[2010/08/26 v1.12]	16
[2010/12/09 v1.13]	16

7 Index **16**

The **hobsub** package

Abstract

Package **hobsub** implements the idea of loading several packages in one big collection package.

1 Documentation	2
1.1 Usage	2
1.2 Supported features	2
1.3 Common limitations	3
1.4 Package hobsub-generic	3
1.5 Package hobsub-hyperref	4
1.6 Package hobsub	4
2 Implementation	5
2.1 Reload check and package identification	5
2.1.1 Package hobsub	5
2.1.2 Package hobsub-generic	6
2.1.3 Package hobsub-hyperref	7
2.2 Catcodes	8
2.3 Package hobsub-hyperref loads hobsub-generic	9
2.4 Preamble	9
2.5 End of preamble for subset packages	11
2.6 Package list	11
2.7 End of packages	12
3 Test	12
3.1 Catcode checks for loading	12
4 Installation	13
4.1 Download	13
4.2 Bundle installation	14
4.3 Package installation	14
4.4 Refresh file name databases	14
4.5 Some details for the interested	14
5 References	15
6 History	15
[2011/01/30 v1.0]	15
[2011/04/16 v1.1]	15
[2011/04/17 v1.2]	15
[2011/04/18 v1.3]	15
[2011/04/23 v1.4]	15
7 Index	15

The `hologo` package

Abstract

This package starts a collection of logos with support for bookmarks strings.

1 Documentation	2
1.1 Logo macros	2
1.2 Setup macros	2
1.3 Options	3
2 Implementation	3
2.1 Load resources	5
2.2 Setup macros	6
2.3 Options	6
2.4 Break/no-break support	8
2.5 <code>\hologo</code>	9
2.6 Helpers	11
2.7 T _E X and friends	12
2.7.1 T _E X	12
2.7.2 plain T _E X	12
2.7.3 L ^A T _E X	13
2.7.4 L ^A T _E X 2 _ε	13
2.7.5 L ^A T _E X3	13
2.7.6 ε-T _E X	14
2.7.7 iniT _E X	14
2.7.8 iniT _E X	14
2.7.9 LuaT _E X	14
2.7.10 LuaL ^A T _E X	15
2.7.11 X _E T _E X, X _H L ^A T _E X	15
2.7.12 pdfT _E X, pdfL ^A T _E X	15
2.7.13 V _T E _X	15
2.7.14 A _M S,	16
2.7.15 ConT _E Xt	16
2.8 Driver detection	17
3 Test	20
3.1 Catcode checks for loading	20
3.2 Spacefactor	22
4 Installation	23
4.1 Download	23
4.2 Bundle installation	23
4.3 Package installation	23
4.4 Refresh file name databases	24
4.5 Some details for the interested	24

5 History	24
[2010/04/08 v1.0]	24
[2010/04/16 v1.1]	25
[2010/04/24 v1.2]	25
[2010/11/21 v1.3]	25
[2011/03/25 v1.4]	25
[2011/04/21 v1.5]	25
6 Index	25

The `holtxdoc` package

Abstract

The package is used for the documentation of my packages in DTX format.
It contains some private macros and setup for my needs. Thus do not use it.
I have separated the part that may be useful for others in package `hypdoc`.

1 No usage	2
2 Implementation	2
2.1 Help macros	2
2.2 Date	2
2.3 History	3
2.4 Formatting macros	3
2.5 Names	5
2.6 Setup	5
2.6.1 Package doc	5
2.6.2 Page layout	6
3 Installation	6
3.1 Download	6
3.2 Bundle installation	6
3.3 Package installation	6
3.4 Refresh file name databases	7
3.5 Some details for the interested	7
4 History	7
[1999/06/26 v0.3]	7
[2000/08/14 v0.4]	7
[2001/08/27 v0.5]	8
[2001/09/02 v0.6]	8
[2006/06/02 v0.7]	8
[2007/10/21 v0.8]	8
[2007/11/11 v0.9]	8
[2007/12/12 v0.10]	8
[2008/08/11 v0.11]	8
[2009/08/07 v0.12]	8
[2009/12/02 v0.13]	8
[2010/02/03 v0.14]	8
[2010/03/10 v0.15]	8
[2010/04/03 v0.16]	8
[2010/04/08 v0.17]	8
[2010/04/18 v0.18]	8
[2010/04/24 v0.19]	9
[2010/12/03 v0.20]	9
[2011/02/04 v0.21]	9
5 Index	9

The `hopatch` package

Abstract

This packages provides a wrapper to various package hooks provided by other packages or classes, but does not define own hooks.

1 Documentation	1
2 Implementation	3
2.1 Catcodes and package identification	3
2.2 Resources	3
2.3 Package patching	4
3 Test	5
3.1 Catcode checks for loading	5
4 Installation	8
4.1 Download	8
4.2 Bundle installation	8
4.3 Package installation	8
4.4 Refresh file name databases	9
4.5 Some details for the interested	9
5 References	9
6 History	10
[2011/01/30 v1.0]	10
7 Index	10

The **hycolor** package

Abstract

Package **hycolor** implements the color option stuff that is used by packages **hyperref** and **bookmark**. It is not intended as package for the user.

1 Documentation	2
1.1 Summary	2
2 Implementation	3
2.1 Normalization	3
2.1.1 Sanitize value of color option	3
2.1.2 Normalize result	4
2.2 Main algorithm for color options	5
2.3 Package bookmark	5
2.4 Utils	7
2.5 Package hyperref	8
2.5.1 Options Hyp.*color	8
2.5.2 Generic algorithm	10
2.5.3 Field options	12
2.5.4 Detection for naked RGB values	12
2.5.5 Options *bordercolor	14
2.6 Package attachfile2	15
2.7 Patch for package xcolor	17
2.7.1 Fix fragile \framebox	20
3 Test	20
3.1 Test for package attachfile2	24
3.2 Test for package xcolor	26
3.2.1 Test for \framebox	27
4 Installation	28
4.1 Download	28
4.2 Bundle installation	28
4.3 Package installation	28
4.4 Refresh file name databases	29
4.5 Some details for the interested	29
5 History	29
[2007/04/09 v1.0]	29
[2007/04/11 v1.1]	29
[2008/07/29 v1.2]	29
[2008/08/01 v1.3]	29
[2008/09/08 v1.4]	30
[2009/10/02 v1.5]	30
[2009/12/12 v1.6]	30
[2011/01/30 v1.7]	30

The `hypbmsec` package

Abstract

This package expands the syntax of the sectioning commands. If the argument of the sectioning commands isn't usable as outline entry, a replacement for the bookmarks can be given.

1 Usage	2
1.1 Bookmarks restrictions	2
1.2 <code>\texorpdfstring</code>	2
1.3 Sectioning commands	2
1.4 Places for sectioning strings	2
1.5 Solution with optional arguments	2
1.6 Syntax	3
1.6.1 Star form	3
1.6.2 Without optional arguments	3
1.6.3 One optional argument	3
1.6.4 Two optional arguments	3
1.6.5 Optional argument in parentheses	3
1.7 Without <code>hyperref</code>	3
1.8 Protecting parentheses	4
2 Implementation	4
3 Installation	7
3.1 Download	7
3.2 Bundle installation	7
3.3 Package installation	7
3.4 Refresh file name databases	7
3.5 Some details for the interested	8
4 History	8
[1998/11/20 v1.0]	8
[1999/04/12 v2.0]	8
[2000/03/22 v2.1]	8
[2006/02/20 v2.2]	9
[2007/03/05 v2.3]	9
[2007/04/11 v2.4]	9
5 Index	9

The `hypcap` package

Abstract

This package tries a solution of the problem with hyperref, that links to floats points below the caption and not at the beginning of the float. Therefore this package divides the task into two part, the link setting with \capstart or automatically at the beginning of a float and the rest in the \caption command.

1 Usage	2
1.1 Package options	2
1.2 User commands	2
1.3 Limitations	3
2 Implementation	3
3 Installation	5
3.1 Download	5
3.2 Bundle installation	6
3.3 Package installation	6
3.4 Refresh file name databases	6
3.5 Some details for the interested	6
4 History	7
[1999/02/13 v1.0]	7
[2000/08/14 v1.1]	7
[2000/09/07 v1.2]	7
[2001/08/27 v1.3]	7
[2001/09/06 v1.4]	7
[2006/02/20 v1.5]	7
[2007/02/19 v1.6]	7
[2007/04/09 v1.7]	7
[2008/04/14 v1.8]	8
[2008/08/11 v1.9]	8
[2008/09/08 v1.10]	8
[2011/02/16 v1.11]	8
5 Index	8

The **hypdestopt** package

Abstract

Package `hypdestopt` supports `hyperref`'s pdftex driver. It removes unnecessary destinations and shortens the destination names or uses numbered destinations to get smaller PDF files.

1 User interface	2
1.1 Introduction	2
1.2 Requirements	2
1.3 Use	2
1.4 Limitations	2
1.5 Future	3
2 Implementation	3
2.1 Identification	3
2.2 Options	3
2.2.1 Option <i>verbose</i>	3
2.2.2 Options <i>num</i> and <i>name</i>	3
2.3 Check requirements	4
2.4 Preamble for auxiliary file	4
2.5 Generation of destination names	4
2.6 Assign destination names	6
2.7 Redefinition of <code>hyperref</code> 's hooks	6
2.7.1 Destination setting	7
2.7.2 Links	7
2.7.3 Outlines of package <code>hyperref</code>	8
2.7.4 Outlines of package <code>bookmark</code>	8
3 Installation	9
3.1 Download	9
3.2 Bundle installation	9
3.3 Package installation	9
3.4 Refresh file name databases	9
3.5 Some details for the interested	10
4 References	10
5 History	10
[2006/06/01 v1.0]	10
[2006/06/01 v2.0]	10
[2007/11/11 v2.1]	10
[2008/08/08 v2.2]	11
6 Index	11

The `hypdoc` package

Abstract

This package adds hyper features to the package `doc` that is used in the documentation system of L^AT_EX 2 _{ε} . Bookmarks are added and references are linked as far as possible.

1 Features	2
2 Usage	3
2.1 Options	3
2.2 Simple example	3
2.3 Example <code>source2e.tex</code>	4
3 Implementation	4
3.1 Options	4
3.2 Package loading	4
3.2.1 Patch for bug latex/4096	5
3.3 Bookmarks	5
3.4 <code>\tableofcontents</code>	6
3.5 <code>\listoffigures</code>	6
3.6 <code>\listoftables</code>	7
3.7 <code>\thebibliography</code>	7
3.8 <code>\theindex</code>	7
3.9 <code>\theglossary</code>	8
3.10 Index	9
3.11 <code>\PrintDescribeMacro</code>	11
3.12 <code>\PrintMacroName</code>	11
3.13 <code>\theCodelineNo</code>	12
3.14 <code>\SpecialUsageIndex</code>	12
3.15 <code>\autoindex</code>	12
3.16 <code>\SpecialEnvIndex</code>	13
3.17 <code>\SortIndex</code>	13
3.18 <code>\@wrglossary</code>	13
3.19 <code>\MacroIndent</code>	14
4 Installation	14
4.1 Download	14
4.2 Bundle installation	14
4.3 Package installation	15
4.4 Refresh file name databases	15
4.5 Some details for the interested	15
5 History	15
[2002/05/10 v1.0]	15
[2006/02/20 v1.1]	16
[2006/04/27 v1.2]	16

[2006/06/01 v1.3]	16
[2006/06/02 v1.4]	16
[2007/04/11 v1.5]	16
[2007/11/12 v1.6]	16
[2009/12/10 v1.7]	16
[2010/02/03 v1.8]	16
[2010/03/26 v1.9]	16

6 Index **16**

The **hypgtoe** package

Abstract

Experimental package for links to embedded files.

1 Documentation	1
1.1 Introduction	1
1.2 User interface	2
1.3 Example	2
2 Implementation	3
2.1 Identification	3
2.2 Load packages	3
2.3 Color support	3
2.4 Extend \href	3
2.5 Implement gotoe action	4
2.6 Keys for gotoe action	5
3 Installation	5
3.1 Download	5
3.2 Bundle installation	6
3.3 Package installation	6
3.4 Refresh file name databases	6
3.5 Some details for the interested	6
4 References	7
5 History	7
[2007/10/30 v0.1]	7
6 Index	7

The `hyphsubst` package

Abstract

A TeX format file may include alternative hyphenation patterns for a language with a different name. If the naming convention follows babel's rules, then the hyphenation patterns for a language can be replaced by the alternative hyphenation patterns, provided in the format file.

1 Documentation	1
1.1 In short	1
1.2 Longer version	2
1.3 L ^A T _E X	2
1.4 plain TeX	3
2 Implementation	3
2.1 Reload check and package identification	3
2.2 Package	5
3 Test	6
3.1 Catcode checks for loading	6
3.2 Main tests	8
4 Installation	9
4.1 Download	9
4.2 Bundle installation	9
4.3 Package installation	9
4.4 Refresh file name databases	9
4.5 Some details for the interested	10
5 History	10
[2008/06/07 v0.1]	10
[2008/06/09 v0.2]	10
6 Index	10

The **ifdraft** package

Abstract

The package provides an interface for selecting code depending on the options `draft` and `final`.

1 Usage	1
1.1 Package loading	1
1.2 User macros	1
2 Implementation	2
3 Installation	3
3.1 Download	3
3.2 Bundle installation	3
3.3 Package installation	3
3.4 Refresh file name databases	4
3.5 Some details for the interested	4
4 History	4
[1999/12/28 v1.0]	4
[2005/10/05 v1.1]	5
[2006/02/20 v1.2]	5
[2008/08/11 v1.3]	5
5 Index	5

The `iflang` package

Abstract

This package provides expandible checks for the current language based on macro `\languagename` or hyphenation patterns.

1 Documentation	2
2 Implementation	2
2.1 Reload check and package identification	3
2.2 Tools	4
2.2.1 Provide some basic macros of L ^A T _E X	4
2.2.2 Expandible existence check for macros	5
2.2.3 Macros for messages	5
2.2.4 Support for <code>etex.src</code>	5
2.3 <code>\IfLanguagePatterns</code>	6
2.4 <code>\IfLanguageName</code>	6
2.5 Check plausibility of <code>\languagename</code>	8
3 Test	8
3.1 Catcode checks for loading	8
3.2 Test with L ^A T _E X	10
3.3 Test with plain T _E X and ε -T _E X	11
3.4 Test with plain T _E X and without ε -T _E X/pdfT _E X	11
4 Installation	13
4.1 Download	13
4.2 Bundle installation	13
4.3 Package installation	13
4.4 Refresh file name databases	13
4.5 Some details for the interested	14
5 Acknowledgement	14
6 History	14
[2007/04/10 v1.0]	14
[2007/04/11 v1.1]	14
[2007/04/12 v1.2]	14
[2007/04/26 v1.3]	14
[2007/09/09 v1.4]	15
[2007/11/11 v1.5]	15
7 Index	15

The `ifluatex` package

Abstract

This package looks for LUATEX regardless of its mode and provides the switch `\ifluatex`. Also it makes `\luatexversion` available if it is not present. It works with plain-TEX or LATEX.

1 Documentation	1
2 Implementation	2
2.1 Reload check and package identification	2
2.2 Catcodes	3
2.3 Macro for error messages	4
2.4 Check for previously defined <code>\ifluatex</code>	4
2.5 <code>\ifluatex</code>	4
2.6 LuaTEX v0.39	5
2.7 Protocol entry	6
3 Test	6
3.1 Catcode checks for loading	6
4 Reload check for plain	8
5 Installation	8
5.1 Download	8
5.2 Bundle installation	8
5.3 Package installation	9
5.4 Refresh file name databases	9
5.5 Some details for the interested	9
6 History	10
[2007/12/12 v1.0]	10
[2009/04/10 v1.1]	10
[2009/04/17 v1.2]	10
[2010/03/01 v1.3]	10
7 Index	10

The `ifpdf` package

Abstract

This package looks for pdf \TeX in pdf mode and implements and sets the switch `\ifpdf`. The detection is based on `\pdfoutput` and the package will not change this value. It works with plain or L^AT_EX formats.

1 Documentation	2
1.1 Introduction	2
1.2 Usage	2
1.3 Specification	3
2 Implementation	3
2.1 Reload check and package identification	3
2.2 Catcodes	4
2.3 Check for previously defined <code>\ifpdf</code>	5
2.4 <code>\pdfoutput</code> and L ^A T _E X	6
2.5 <code>\ifpdf</code>	6
2.6 Test for fool attempts	7
2.7 Protocol entry	7
3 Test	8
3.1 Catcode checks for loading	8
4 Installation	9
4.1 Download	9
4.2 Bundle installation	10
4.3 Package installation	10
4.4 Refresh file name databases	10
4.5 Some details for the interested	10
5 History	11
[2001/06/14 v1.0]	11
[2001/07/14 v1.1]	11
[2001/09/26 v1.2]	11
[2005/07/22 v1.3]	11
[2006/02/20 v1.4]	11
[2007/09/09 v1.5]	11
[2007/12/12 v1.6]	11
[2008/12/12 v1.7]	12
[2009/04/10 v2.0]	12
[2010/01/28 v2.1]	12
[2010/09/13 v2.2]	12
[2011/01/30 v2.3]	12
6 Index	12

The `ifvtex` package

Abstract

This package looks for VTeX, implements and sets the switches `\ifvtex`, `\ifvtex<mode>`, `\ifvtexgex`. It works with plain or L^AT_EX formats.

1	Usage	1
2	Implementation	2
2.1	Reload check and package identification	2
2.2	Catcodes	3
2.3	Check for previously defined <code>\ifvtex</code>	4
2.4	Provide <code>\newif</code>	4
2.5	<code>\ifvtex</code>	5
2.6	Mode and GeX switches	5
2.7	Protocol entry	6
3	Test	6
3.1	Catcode checks for loading	6
4	Installation	8
4.1	Download	8
4.2	Bundle installation	8
4.3	Package installation	8
4.4	Refresh file name databases	9
4.5	Some details for the interested	9
5	History	9
[2001/09/26 v1.0]	9
[2006/02/20 v1.1]	9
[2007/01/10 v1.2]	10
[2007/09/09 v1.3]	10
[2008/11/04 v1.4]	10
[2010/03/01 v1.5]	10
6	Index	10

The `infwarerr` package

Abstract

This package provides a complete set of macros for informations, warnings and error messages with support for plain-T_EX.

1 Documentation	1
2 Implementation	2
2.1 Reload check and package identification	2
2.2 Catcodes	3
2.3 L ^A T _E X detection	4
2.4 Version for L ^A T _E X	4
2.5 Version for plain T _E X	5
3 Test	8
3.1 Catcode checks for loading	8
3.2 Macro tests	9
4 Installation	13
4.1 Download	13
4.2 Bundle installation	13
4.3 Package installation	13
4.4 Refresh file name databases	13
4.5 Some details for the interested	14
5 History	14
[2007/04/26 v1.0]	14
[2007/06/14 v1.1]	14
[2007/09/09 v1.2]	14
[2010/04/08 v1.3]	14
6 Index	14

The `inputenx` package

Abstract

This package provides input encodings using standard mappings and covers nearly all slots. Thus it serves as more up-to-date replacement for package `inputenc`.

1 Documentation	1
1.1 Definition files	2
1.2 Unicode	3
1.3 Verbatim	3
2 References	186
2.1 Mappings to Unicode	187
3 History	187
[2006/03/05 v1.0]	187
[2007/04/11 v1.1]	188
[2007/06/16 v1.2]	188
[2007/08/16 v1.3]	188
[2009/08/13 v1.4]	188
[2009/12/15 v1.5]	188
[2010/01/11 v1.6]	188
[2011/02/08 v1.7]	188
[2011/04/10 v1.8]	188

The `intcalc` package

Abstract

This package provides expandable arithmetic operations with integers.

1 Documentation	2
1.1 Introduction	2
1.2 Conditions	2
1.2.1 Preconditions	2
1.2.2 Postconditions	3
1.3 Error handling	3
1.4 Operations	3
1.4.1 Num	3
1.4.2 Inv, Abs, Sgn	4
1.4.3 Min, Max, Cmp	4
1.4.4 Inc, Dec, Add, Sub	5
1.4.5 Shl, Shr	5
1.4.6 Mul, Sqr, Fac, Pow	5
1.4.7 Div, Mod	6
1.5 Interface for programmer	6
2 Implementation	7
2.1 Reload check and package identification	7
2.2 Catcodes	8
2.3 Macros independent of ε - T<small>E</small>X	9
2.3.1 Abs, Sgn	9
2.3.2 Min, Max, Cmp	10
2.3.3 Fac	10
2.4 Implementation based on ε - T<small>E</small>X	11
2.4.1 Num	11
2.4.2 Inv, Abs, Sgn	11
2.4.3 Min, Max, Cmp	11
2.4.4 Inc, Dec	12
2.4.5 Add, Sub	12
2.4.6 Shl, Shr	12
2.4.7 Mul, Sqr, Fac	13
2.4.8 Pow	13
2.4.9 Div, Mod	14
2.5 Implementation without ε - T<small>E</small>X	17
2.5.1 Num	17
2.5.2 Inv, Abs, Sgn	17
2.5.3 Min, Max, Cmp	18
2.5.4 Inc, Dec	18
2.5.5 Add, Sub	20
2.5.6 Shl, Shr	27
2.5.7 \InCa@Tim	29
2.5.8 Mul	32

2.5.9	Sqr, Fac	34
2.5.10	Pow	34
2.5.11	Div	36
2.5.12	Mod	40
2.5.13	Help macros	41
3	Test	41
3.1	Catcode checks for loading	41
3.2	Macro tests	43
3.2.1	Preamble with test macro definitions	43
3.2.2	Time	46
3.2.3	Test 4: additional mod/div operations	47
3.2.4	Test sets	48
4	Installation	56
4.1	Download	56
4.2	Bundle installation	57
4.3	Package installation	57
4.4	Refresh file name databases	57
4.5	Some details for the interested	57
5	History	58
[2007/09/09 v1.0]	58
[2007/09/27 v1.1]	58
6	Index	58

The `kvdefinekeys` package

Abstract

Package `kvdefinekeys` provides `\kv@define@key` to define keys the same way as `keyval`'s `\define@key`. However, it works also using ini-`TeX`.

1 Documentation	1
1.1 Motivation	1
2 Implementation	2
2.1 Identification	2
2.2 Package loading	3
2.3 Provide key defining macro	4
3 Test	4
3.1 Catcode checks for loading	4
4 Installation	6
4.1 Download	6
4.2 Bundle installation	6
4.3 Package installation	7
4.4 Refresh file name databases	7
4.5 Some details for the interested	7
5 References	8
6 History	8
[2010/03/01 v1.0]	8
[2010/08/19 v1.1]	8
[2011/01/30 v1.2]	8
[2011/04/07 v1.3]	8
7 Index	8

The `kvoptions` package

Abstract

This package is intended for package authors who want to use options in key value format for their package options.

1	Introduction	3
1.1	The beginning	3
1.2	Overview	3
2	Usage	3
2.1	Process options	3
2.1.1	<code>\ProcessKeyvalOptions</code>	3
2.1.2	<code>\ProcessLocalKeyvalOptions</code>	4
2.1.3	<code>\SetupKeyvalOptions</code>	4
2.2	Option declarations	4
2.2.1	<code>\DeclareStringOption</code>	5
2.2.2	<code>\DeclareBoolOption</code>	5
2.2.3	<code>\DeclareComplementaryOption</code>	6
2.2.4	<code>\DeclareVoidOption</code>	6
2.2.5	<code>\DeclareDefaultOption</code>	6
2.2.6	Local options	7
2.2.7	Dynamic options	7
2.2.8	<code>\DisableKeyvalOption</code>	7
2.2.9	<code>\AddToKeyvalOption</code>	8
2.3	Global vs. local options	8
2.4	Summary of internal macros	9
2.5	plain TeX	9
3	Example	9
4	Package options	11
4.1	Package <code>kvoptions-patch</code>	11
4.2	Option <code>debugshow</code>	12
5	Limitations	13
5.1	Compatibility	13
5.1.1	Package <code>kvoptions-patch</code> vs. package <code>xkvltxp</code>	13
5.2	Limitations	13
5.2.1	Option comparisons	13
5.2.2	Option list parsing with package <code>kvoptions-patch</code>	13
6	Implementation	14
6.1	Preamble	14
6.2	Option declaration macros	16
6.2.1	<code>\SetupKeyvalOptions</code>	16
6.2.2	<code>\DeclareBoolOption</code>	17
6.2.3	<code>\DeclareStringOption</code>	20

6.2.4	\DeclareVoidOption	20
6.2.5	\DeclareDefaultOption	21
6.2.6	\DeclareLocalOptions	22
6.3	Dynamic options	22
6.3.1	\DisableKeyvalOption	22
6.4	Change option code	24
6.4.1	\AddToKeyvalOption	24
6.5	Process options	25
6.5.1	\ProcessKeyvalOptions	25
6.5.2	\ProcessLocalKeyvalOptions	27
6.5.3	Helper macros	28
6.6	plain TeX	29
6.7	Package <i>kvoptions-patch</i>	29
7	Test	37
7.1	Preface for standard catcode check	37
7.2	Catcode checks for loading	37
8	Installation	40
8.1	Download	40
8.2	Bundle installation	41
8.3	Package installation	41
8.4	Refresh file name databases	41
8.5	Some details for the interested	41
9	References	42
10	History	43
[0000/00/00 v0.0]		43
[2004/02/22 v1.0]		43
[2006/02/16 v2.0]		43
[2006/02/20 v2.1]		43
[2006/06/01 v2.2]		43
[2006/08/17 v2.3]		43
[2006/08/22 v2.4]		43
[2007/04/11 v2.5]		43
[2007/05/06 v2.6]		43
[2007/06/11 v2.7]		43
[2007/10/02 v2.8]		44
[2007/10/11 v2.9]		44
[2007/10/18 v3.0]		44
[2009/04/10 v3.1]		44
[2009/07/17 v3.2]		44
[2009/07/21 v3.3]		44
[2009/08/13 v3.4]		44
[2009/12/04 v3.5]		44
[2009/12/08 v3.6]		44

[2010/02/22 v3.7]	44
[2010/07/23 v3.8]	44
[2010/12/02 v3.9]	44
[2010/12/23 v3.10]	44

11 Index	45
-----------------	-----------

The `kvsetkeys` package

Abstract

Package `kvsetkeys` provides `\kvsetkeys`, a variant of package `keyval`'s `\setkeys`. It allows to specify a handler that deals with unknown options. Active commas and equal signs may be used (e.g. see `babel`'s shorthands) and only one level of curly braces is removed from the values.

1 Documentation	2
1.1 Motivation	2
1.2 Normalizing key value lists	3
1.3 Parsing key value lists	3
1.4 Processing key value pairs	4
1.5 Default family handler	4
1.6 Put it all together	4
1.7 Comma separated lists	5
2 Example	5
3 Implementation	6
3.1 Identification	6
3.2 Package loading	8
3.3 Check for ε - <code>TeX</code>	8
3.4 Generic help macros	9
3.5 Normalizing	9
3.6 Parsing key value lists	11
3.7 Parsing comma lists	13
3.8 Processing key value pairs	13
3.9 Error handling	14
3.10 Do it all	14
4 Test	15
4.1 Catcode checks for loading	15
4.2 Macro tests	16
4.2.1 Preamble	16
4.2.2 Time	17
4.2.3 Test sets	17
5 Installation	20
5.1 Download	20
5.2 Bundle installation	21
5.3 Package installation	21
5.4 Refresh file name databases	21
5.5 Some details for the interested	21
6 References	22

7 History	22
[2006/03/06 v1.0]	22
[2006/10/19 v1.1]	22
[2007/09/09 v1.2]	22
[2007/09/29 v1.3]	23
[2009/07/19 v1.4]	23
[2009/07/30 v1.5]	23
[2009/12/12 v1.6]	23
[2009/12/22 v1.7]	23
[2010/01/28 v1.8]	23
[2010/03/01 v1.9]	23
[2011/01/30 v1.10]	23
[2011/03/03 v1.11]	23
[2011/04/05 v1.12]	23
[2011/04/07 v1.13]	23
8 Index	24

The `letltxmacro` package

Abstract

TeX's `\let` assignment does not work for L^AT_EX macros with optional arguments or for macros that are defined as robust macros by `\DeclareRobustCommand`. This package defines `\LetLtxMacro` that also takes care of the involved internal macros.

1 Documentation	1
1.1 Supported macro definition commands	2
2 Implementation	2
2.1 Show cases	2
2.1.1 <code>letltxmacro-showcases.tex</code>	2
2.1.2 Result	4
2.2 Package	4
2.2.1 Catcodes and identification	4
2.2.2 Main macros	5
3 Test	7
3.1 Catcode checks for loading	7
3.2 Package tests	8
4 Installation	12
4.1 Download	12
4.2 Bundle installation	12
4.3 Package installation	13
4.4 Refresh file name databases	13
4.5 Some details for the interested	13
5 History	14
[2008/06/09 v1.0]	14
[2008/06/12 v1.1]	14
[2008/06/13 v1.2]	14
[2008/06/24 v1.3]	14
[2010/09/02 v1.4]	14
6 Index	14

The `listingsutf8` package

Abstract

Package `listings` does not support files with multi-byte encodings such as UTF-8. In case of `\lstinputlisting` a simple workaround is possible if an one-byte encoding exists that the file can be converted to. Also ε -`TEX` and `pdfTEX` regardless of its mode are required.

1 Documentation	1
1.1 User interface	1
1.2 Future	2
2 Implementation	2
2.1 Catcodes and identification	2
2.2 Package options	3
2.3 Check prerequisites	3
2.4 Add support for UTF-8	4
2.4.1 Conversion	4
2.4.2 Patch <code>\lst@InputListing</code>	4
3 Test	4
3.1 Catcode checks for loading	4
3.2 Test example for latin1	5
4 Installation	6
4.1 Download	6
4.2 Bundle installation	6
4.3 Package installation	6
4.4 Refresh file name databases	7
4.5 Some details for the interested	7
5 References	7
6 History	8
[2007/10/22 v1.0]	8
[2007/11/11 v1.1]	8
7 Index	8

The `ltxcmds` package

Abstract

The package `ltxcmds` exports some utility macros from the L^AT_EX kernel into a separate namespace and also provides them for other formats such as plain-T_EX.

1 Documentation	3
1.1 Introduction	3
1.2 Numbers	3
1.3 Scratch registers	3
1.4 Argument killers	3
1.5 Argument grabbers	4
1.6 List helpers	4
1.7 Tail recursion	5
1.8 Empty macro	5
1.9 Characters	5
1.10 Boolean switch	5
1.11 Command definitions	5
1.12 Stripping	6
1.13 File management	6
1.13.1 File extensions	6
1.13.2 Load check	6
1.13.3 Version date check	7
1.14 Macro additions	7
1.15 Next character detection	7
1.16 <code>\ltx@leavevmode</code> , <code>\ltx@mbox</code>	8
1.17 Expandable test for emptiness	8
1.18 Stripping spaces	8
1.19 Check for emptiness of boxes	8
2 Implementation	9
2.1 Identification	9
2.2 Numbers	11
2.3 Scratch registers	11
2.4 Argument killers	13
2.5 Argument grabbers	13
2.6 List helpers	14
2.7 Tail recursion	15
2.8 Empty macro	15
2.9 Characters	15
2.10 Boolean switch	16
2.11 Command definitions	17
2.12 Stripping	18
2.13 File management	18
2.13.1 File extensions	18
2.13.2 Load check	18

2.13.3 Version date check	19
2.14 Macro additions	20
2.15 Next character detection	20
2.16 \ltx@leavevemode, \ltx@obox	21
2.17 Help macros	22
2.18 Expandable test for emptiness	22
2.18.1 Vanilla TeX	22
2.18.2 With \detokenize	23
2.18.3 \ltx@ifblank	23
2.19 \ltx@zapspace	24
2.20 \ltx@IfBoxEmpty	24
3 Test	25
3.1 Catcode checks for loading	25
3.2 Test \ltx@GobbleNum	27
3.3 Test \ltx@ifempty	30
3.4 Test \ltx@zap@space	32
3.5 Test \ltx@IfBoxEmpty	33
3.6 Test for next character detection	34
4 Installation	37
4.1 Download	37
4.2 Bundle installation	37
4.3 Package installation	38
4.4 Refresh file name databases	38
4.5 Some details for the interested	38
5 References	39
6 History	39
[2009/08/05 v1.0]	39
[2009/12/12 v1.1]	39
[2010/01/28 v1.2]	39
[2010/03/01 v1.3]	40
[2010/03/09 v1.4]	40
[2010/04/08 v1.5]	40
[2010/04/16 v1.6]	40
[2010/04/26 v1.7]	40
[2010/09/11 v1.8]	40
[2010/10/25 v1.9]	40
[2010/10/31 v1.10]	40
[2010/11/12 v1.11]	40
[2010/12/02 v1.12]	40
[2010/12/04 v1.13]	40
[2010/12/07 v1.14]	41
[2010/12/12 v1.15]	41
[2011/02/04 v1.16]	41

[2011/02/05 v1.17]	41
[2011/03/16 v1.18]	41
[2011/04/14 v1.19]	41
[2011/04/18 v1.20]	41

7 Index **41**

The luacolor package

Abstract

Package luacolor implements color support based on LUATEX's node attributes.

1 Documentation	2
1.1 Introduction	2
1.2 Usage	2
1.3 Limitations	2
2 Implementation	2
2.1 Catcodes and identification	2
2.2 Check for LuaTeX	3
2.3 Check for disabled colors	4
2.4 Load module and check version	4
2.5 Find driver	4
2.6 Attribute setting	5
2.7 Whatsit insertion	5
2.8 \pdfxform support	6
2.9 Lua module	6
2.9.1 Driver detection	7
2.9.2 Color strings	7
2.9.3 Attribute register	8
2.9.4 Whatsit insertion	8
3 Test	10
3.1 Catcode checks for loading	10
3.2 Driver detection	12
4 Installation	12
4.1 Download	12
4.2 Bundle installation	12
4.3 Package installation	13
4.4 Refresh file name databases	13
4.5 Some details for the interested	13
5 History	14
[2007/12/12 v1.0]	14
[2009/04/10 v1.1]	14
[2010/03/09 v1.2]	14
[2010/12/13 v1.3]	14
[2011/03/29 v1.4]	14
[2011/04/22 v1.5]	14
[2011/04/23 v1.6]	14
6 Index	14

The luatex package

Abstract

This package manages the new and extended features and resources that LUATEX provides. Examples are attributes and catcode tables.

1 Documentation	2
1.1 Introduction	2
1.1.1 L ^A T _E X	2
1.1.2 plain T _E X	2
1.2 Register allocation	3
1.2.1 Register with 16 bit	3
1.2.2 Insertions	3
1.3 Attributes	3
1.4 Catcode tables	4
1.4.1 Interface proposal	4
1.5 Lua module loading	5
1.5.1 Package luatex-loader	6
2 Implementation	6
2.1 Reload check and package identification	6
2.2 Catcodes	7
2.3 Check for Luatex	8
2.4 Provide Luatex primitives	8
2.5 Inherit support for ε-T _E X	9
2.6 Adaption of ε-T _E X's register allocation	10
2.7 plain T _E X compatibility	10
2.8 Attributes	12
2.8.1 Allocation	12
2.8.2 Interface	12
2.9 Catcode tables	13
2.9.1 Allocation	13
2.9.2 \SetCatcodeRange	13
2.9.3 Predefined catcode tables	14
2.9.4 Number stack	14
2.9.5 Catcode regime macros	15
2.10 Lua module loader	15
2.11 Lua script	17
3 Test	18
3.1 Catcode checks for loading	18
3.2 Catcode tables	20
3.2.1 Predefined catcode tables	20
3.2.2 Catcode table number stack	20
3.2.3 Catcode table stack	21
3.2.4 Catcode regime macros	21
3.3 Attribute allocation	22
3.4 Short test for plain T _E X	22

4 Installation	22
4.1 Download	22
4.2 Bundle installation	23
4.3 Package installation	23
4.4 Refresh file name databases	23
4.5 Some details for the interested	24
5 History	24
[2007/12/12 v0.1]	24
[2009/04/10 v0.2]	24
[2009/12/02 v0.3]	24
[2010/03/09 v0.4]	24
6 Index	25

The `magicnum` package

Abstract

This packages allows to access magic numbers by a hierarchical name system.

1 Documentation	2
1.1 Introduction	2
1.2 User interface	2
1.2.1 <code>\magicnum</code>	2
1.2.2 Properties	3
1.3 Data	3
1.3.1 Category <code>tex.catcode</code>	3
1.3.2 Category <code>etex.grouptype</code>	3
1.3.3 Category <code>etex.iftype</code>	4
1.3.4 Category <code>etex.nodetype</code>	4
1.3.5 Category <code>etex.interactionmode</code>	4
1.3.6 Category <code>luatex.pdfliteral.mode</code>	4
2 Implementation	4
2.1 Reload check and package identification	5
2.2 Catcodes	6
2.3 Check for previous definition	7
2.4 Without LuaTeX	7
2.5 With LuaTeX	7
2.6 Data	8
2.6.1 Plain data	8
2.6.2 Data for T _E X	10
2.6.3 Lua module	12
3 Test	15
3.1 Catcode checks for loading	15
3.2 Test data	17
3.3 Small test for iniT _E X	18
4 Installation	18
4.1 Download	18
4.2 Bundle installation	18
4.3 Package installation	18
4.4 Refresh file name databases	19
4.5 Some details for the interested	19
5 History	19
[2007/12/12 v1.0]	19
[2009/04/10 v1.1]	20
[2010/03/09 v1.2]	20
[2011/03/24 v1.3]	20
[2011/04/10 v1.4]	20

The `makerobust` package

Abstract

Package `makerobust` provides `\MakeRobustCommand` that converts an existing macro to a robust one.

1 User interface	1
1.1 Example	2
2 Implementation	2
3 Installation	3
3.1 Download	3
3.2 Bundle installation	3
3.3 Package installation	3
3.4 Refresh file name databases	4
3.5 Some details for the interested	4
4 History	4
[2006/03/18 v1.0]	4
5 Index	5

The `mleftright` package

Abstract

TeX sets subformulas by `\left` and `\right` as inner formulas with additional surrounding spaces in some situations. This package provides `\mleft` and `\mright` that call `\left` and `\right`, but the delimiters will act as normal `\mathopen` and `\mathclose` delimiters without the additional space of an inner formula.

1 Documentation	1
1.1 Use	2
2 Implementation	2
3 Test	7
3.1 Catcode checks for loading	7
4 Installation	8
4.1 Download	8
4.2 Bundle installation	9
4.3 Package installation	9
4.4 Refresh file name databases	9
4.5 Some details for the interested	9
5 Acknowledgement	10
6 References	10
7 History	10
[2010/09/25 v1.0]	10
8 Index	10

The **pagegrid** package

Abstract

The L^AT_EX package prints a page grid in the background.

1 Documentation	1
1.1 Options	2
1.1.1 Options enable, disable	2
1.1.2 Grid origins	2
1.1.3 Grid unit	2
1.1.4 Color options	2
1.1.5 Arrow options	3
1.1.6 Miscellaneous options	3
2 Implementation	3
3 Test	9
3.1 Catcode checks for loading	9
4 Installation	11
4.1 Download	11
4.2 Bundle installation	11
4.3 Package installation	12
4.4 Refresh file name databases	12
4.5 Some details for the interested	12
5 Acknowledgement	12
6 History	13
[2009/11/06 v1.0]	13
[2009/11/06 v1.1]	13
[2009/12/02 v1.2]	13
[2009/12/03 v1.3]	13
[2009/12/04 v1.4]	13
7 Index	13

The **pagesel** package

Abstract

Single pages or page areas can be selected for output.

1 Usage	1
1.1 Page selecting	2
1.1.1 Options for selecting pages	2
1.1.2 Examples	2
1.2 Auxiliary files	2
1.2.1 Options for handling auxiliary files	2
1.2.2 Package <code>hyperref</code>	3
2 Implementation	3
2.1 Package	3
2.2 AtBeginDvi hook support	6
3 Installation	7
3.1 Download	7
3.2 Bundle installation	7
3.3 Package installation	8
3.4 Refresh file name databases	8
3.5 Some details for the interested	8
4 History	9
[1999/03/01 v0.9]	9
[1999/04/05 v1.0]	9
[1999/04/13 v1.1]	9
[2003/06/05 v1.2]	9
[2006/02/20 v1.3]	9
[2006/03/02 v1.4]	9
[2006/03/07 v1.5]	9
[2007/04/11 v1.6]	9
[2007/04/12 v1.7]	9
[2008/08/11 v1.8]	9
5 Index	10

The **pdfcol** package

Abstract

Since version 1.40 pdfTEX supports color stacks. The driver file `pdftex.def` for package `color` defines and uses a main color stack since version v0.04b. Package `pdfcol` is intended for package writers. It defines macros for setting and maintaining new color stacks.

1 Documentation	2
1.1 Requirements	2
1.2 Interface	2
2 Implementation	3
2.1 Reload check and package identification	3
2.2 Catcodes	4
2.3 Check requirements	5
2.3.1 Check package <code>luacolor</code>	5
2.3.2 Check PDF mode	5
2.3.3 Check version of pdfTEX	6
2.3.4 Check <code>pdftex.def</code>	6
2.4 Enabled interface macros	6
2.5 Disabled interface macros	8
3 Test	9
3.1 Catcode checks for loading	9
3.2 Very simple test	10
3.3 Detection of package <code>luacolor</code>	11
4 Installation	11
4.1 Download	11
4.2 Bundle installation	12
4.3 Package installation	12
4.4 Refresh file name databases	12
4.5 Some details for the interested	12
5 History	13
[2007/09/09 v1.0]	13
[2007/12/09 v1.1]	13
[2007/12/12 v1.2]	13
6 Index	13

The **pdfcolfoot** package

Abstract

Since version 1.40 pdfTeX supports several color stacks. This package uses a separate color stack for footnotes that can break across pages.

1 User interface	1
1.1 Other packages or classes	2
2 Interface for package or class writers	2
2.1 Macro \pdfcolfoot@switch	2
2.2 Macro \pdfcolfoot@current	2
3 Implementation	2
3.1 Identification	2
3.2 Load package pdfcol	3
3.3 Color stack for footnotes	3
3.4 Patch \makefntext	3
3.5 Patch \makecol	3
4 Test	5
5 Installation	6
5.1 Download	6
5.2 Bundle installation	6
5.3 Package installation	6
5.4 Refresh file name databases	7
5.5 Some details for the interested	7
6 References	7
7 History	7
[2007/01/08 v1.0]	7
[2007/09/09 v1.1]	8
8 Index	8

The `pdfcolmk` package

Abstract

This package tries a solution for the missing color stack of pdfTEX.

1 Documentation	2
1.1 Introduction	2
1.2 Background	2
1.3 Limitations	2
1.4 Recommendation	2
1.5 Usage	2
1.6 Compatibility	2
2 Implementation	3
2.1 \marginpar fix	4
2.1.1 latex/base/latex.ltx	4
2.1.2 memoir.cls	5
2.1.3 poemscol/marn.sty, poemscol/newmarn.sty	6
2.1.4 refman/refart.cls, refnam/refrep.cls	7
2.2 Color fix	9
3 Installation	10
3.1 Download	10
3.2 Bundle installation	10
3.3 Package installation	11
3.4 Refresh file name databases	11
3.5 Some details for the interested	11
4 History	12
[2000/08/27 v0.1]	12
[2000/09/02 v0.2]	12
[2000/09/02 v0.3]	12
[2000/09/06 v0.4]	12
[2000/09/06 v0.5]	12
[2005/06/15 v0.6]	12
[2005/07/09 v0.7]	12
[2006/02/20 v0.8]	12
[2007/01/01 v1.0]	12
[2007/04/11 v1.1]	12
[2008/08/11 v1.2]	12
5 Index	13

The **pdfcolparallel** package

Abstract

This packages fixes bugs in `parallel` and improves color support by using several color stacks that are provided by pdfTEX since version 1.40.

1 Usage	1
1.1 Option <code>rulebetweencolor</code>	2
1.2 Future	2
2 Implementation	2
2.1 Identification	2
2.2 Load and fix package <code>parallel</code>	2
2.3 Color stack support	7
2.4 Redefinitions	7
3 Test	10
4 Installation	12
4.1 Download	12
4.2 Bundle installation	12
4.3 Package installation	12
4.4 Refresh file name databases	12
4.5 Some details for the interested	13
5 References	13
6 History	13
[2007/09/09 v1.0]	13
[2007/12/12 v1.1]	13
[2008/08/11 v1.2]	14
[2010/01/11 v1.3]	14
7 Index	14

The `pdfcolparcolumns` package

Abstract

Since version 1.40 pdfTeX supports several color stacks. This package uses them to fix color problems in package `parcolumns`.

1 Usage	2
1.1 Option <code>rulebetweencolor</code>	2
1.2 Future	2
2 Implementation	2
2.1 Identification	2
2.2 Load packages	2
2.2.1 Package <code>parcolumns</code>	2
2.2.2 Package <code>pdfcol</code>	3
2.2.3 Package <code>infwarerr</code>	3
2.3 Color stack macros	3
2.4 Patches	3
2.4.1 Init stacks	3
2.4.2 Switch stack	4
2.4.3 Set current stack color	4
3 Test	6
4 Installation	7
4.1 Download	7
4.2 Bundle installation	7
4.3 Package installation	7
4.4 Refresh file name databases	7
4.5 Some details for the interested	8
5 References	8
6 History	8
[2007/07/26 v1.0]	8
[2007/09/09 v1.1]	8
[2008/08/11 v1.2]	9
[2010/01/11 v1.3]	9
7 Index	9

The **pdfcrypt** package

Abstract

This package supports the setting of pdf encryption options for VTeX and some older versions of pdfTeX.

1 Documentation	2
1.1 Alternatives	2
1.2 Usage	2
1.2.1 Special characters	3
1.2.2 \nopdfcrypt	3
1.2.3 Configuration file	3
1.2.4 Support for plain TeX	3
1.3 Hints for pdfTeX	3
2 Implementation	4
2.1 Help macros for plain TeX	4
2.2 Package Identification and checks	5
2.3 Driver detection	5
2.4 Load package keyval	6
2.5 Define options	7
2.6 support of configuration file	11
2.7 Package options	11
3 Installation	12
3.1 Download	12
3.2 Bundle installation	12
3.3 Package installation	12
3.4 Refresh file name databases	12
3.5 Some details for the interested	13
4 History	13
[2001/04/02 v0.1]	13
[2001/07/19 v0.2]	13
[2001/07/19 v0.3]	13
[2001/07/19 v0.4]	13
[2001/08/05 v0.5]	13
[2001/08/09 v0.6]	14
[2001/10/28 v0.7]	14
[2006/02/20 v0.8]	14
[2007/04/11 v0.9]	14
[2007/04/26 v1.0]	14
5 Index	14

The `pdfescape` package

Abstract

This package implements pdf \TeX 's escape features (`\pdfescapehex`, `\pdfunescapehex`, `\pdfescapename`, `\pdfescapestring`) using \TeX or $\varepsilon\text{-}\text{\TeX}$.

1 Documentation	2
1.1 Additional unescape macros	2
1.2 Sanitizing macro	3
2 Implementation	3
2.1 Reload check and package identification	3
2.2 Catcodes	4
2.3 Load package	5
2.4 Sanitizing	5
2.4.1 Space characters	6
2.4.2 Space normalization	6
2.5 <code>\EdefUnescapeName</code>	6
2.6 <code>\EdefUnescapeString</code>	8
2.7 User macros (pdf \TeX analogues)	11
2.8 Help macros	12
2.8.1 Characters	12
2.8.2 Switch for $\varepsilon\text{-}\text{\TeX}$	12
2.9 Conversions	12
2.9.1 Conversion to hex string	12
2.9.2 Character code to octal number	13
2.9.3 Unpack hex string	14
2.9.4 Conversion to PDF name	15
2.9.5 Conversion to PDF string	16
3 Test	17
3.1 Catcode checks for loading	17
3.2 Macro tests	18
3.3 Test with <code>\pdfescape...</code> commands	18
3.4 Test without <code>\pdfescape...</code> , with $\varepsilon\text{-}\text{\TeX}$	18
3.5 Test without <code>\pdfescape...</code> and $\varepsilon\text{-}\text{\TeX}$	19
3.6 Test with Lua \TeX	19
3.7 Check/ensure test preconditions	19
3.7.1 Check <code>\pdfescape...</code>	19
3.7.2 Check $\varepsilon\text{-}\text{\TeX}$	19
3.7.3 Check Lua \TeX	19
3.8 Common part	19
3.8.1 Test for ini \TeX	25

4 Installation	28
4.1 Download	28
4.2 Bundle installation	28
4.3 Package installation	28
4.4 Refresh file name databases	28
4.5 Some details for the interested	29
5 History	29
[2007/02/21 v1.0]	29
[2007/02/25 v1.1]	29
[2007/03/20 v1.2]	29
[2007/04/11 v1.3]	30
[2007/04/21 v1.4]	30
[2007/08/27 v1.5]	30
[2007/09/09 v1.6]	30
[2007/10/27 v1.7]	30
[2007/11/11 v1.8]	30
[2010/03/01 v1.9]	30
[2010/11/12 v1.10]	30
[2011/01/30 v1.11]	30
[2011/04/04 v1.12]	30
6 Index	30

The `pdflscape` package

Abstract

Package `pdflscape` adds PDF support to the environment `landscape` of package `lscape` by setting the PDF page attribute `/Rotate`.

1 Documentation	2
1.1 Supported drivers	2
1.2 Caveat	2
1.3 Requirements	2
1.4 Usage	2
2 Implementation	2
2.1 Package identification	2
2.2 Driver options	2
2.3 Autodetection of driver	3
2.3.1 Driver <code>pdftex</code>	3
2.3.2 Driver <code>xetex</code>	3
2.3.3 Detect driver based on <code>\Gin@driver</code>	4
2.3.4 Driver <code>dvips</code>	4
2.4 Driver implementation	4
2.4.1 <code>pdfTEX</code>	4
2.4.2 PostScript driver	5
2.4.3 Driver <code>dvipdfm</code>	5
2.5 Driver independent stuff	6
3 Test	7
3.1 Driver detection tests	7
3.2 Test for <code>\PLS@CheckAngle</code>	7
3.3 Test for rotate	8
4 Installation	10
4.1 Download	10
4.2 Bundle installation	10
4.3 Package installation	10
4.4 Refresh file name databases	11
4.5 Some details for the interested	11
5 History	11
[2001/01/15 v0.1]	11
[2001/02/04 v0.2]	11
[2004/05/11 v0.3]	11
[2004/05/12 v0.4]	12
[2006/02/20 v0.5]	12
[2006/04/24 v0.6]	12
[2007/04/11 v0.7]	12
[2007/04/17 v0.8]	12

[2007/10/21 v0.9]	12
[2008/08/11 v0.10]	12

6 Index **12**

The `pdfrender` package

Abstract

The PDF format has some graphics parameter like line width or text rendering mode. This package provides an interface for setting these parameters.

1 Documentation	2
1.1 Usage	2
1.2 Macros	2
1.3 Parameters	2
1.3.1 Details	3
1.4 Color stack	3
2 Implementation	4
2.1 Look for pdfT _E X, its mode and features	6
2.2 Enable color support of L ^A T _E X	7
2.3 Hook into <code>\normalcolor</code>	7
2.4 Declare and setup parameters	12
2.5 Fill and stroke color support	13
3 Test	17
3.1 Catcode checks for loading	17
3.2 Simple test file	19
3.3 Further tests	20
3.4 Compatibility with plain T _E X	21
4 Installation	22
4.1 Download	22
4.2 Bundle installation	22
4.3 Package installation	22
4.4 Refresh file name databases	23
4.5 Some details for the interested	23
5 Acknowledgement	23
6 References	23
7 History	24
[2010/01/26 v1.0]	24
[2010/01/27 v1.1]	24
[2010/01/28 v1.2]	24
8 Index	24

The `pdftexcmds` package

Abstract

LuaTeX provides most of the commands of pdfTeX 1.40. However a number of utility functions are removed. This package tries to fill the gap and implements some of the missing primitive using Lua.

1 Documentation	2
1.1 General principles	3
1.2 Macros	3
1.2.1 Additional macro: <code>\pdf@isprimitive</code>	5
1.2.2 Experimental	5
2 Implementation	5
2.1 Reload check and package identification	5
2.2 Catcodes	7
2.3 Load packages	8
2.4 Without LuaTeX	8
2.5 <code>\pdf@primitive</code> , <code>\pdf@ifprimitive</code>	9
2.5.1 Using LuaTeX's <code>tex.enableprimitives</code>	9
2.5.2 Trying various names to find the primitives	10
2.5.3 Result	11
2.6 XeTeX	11
2.7 <code>\pdf@isprimitive</code>	11
2.8 <code>\pdf@draftmode</code>	12
2.9 Load Lua module	13
2.10 Lua functions	14
2.11 Lua module	18
3 Test	23
3.1 Catcode checks for loading	23
3.2 Test for <code>\pdf@isprimitive</code>	25
3.3 Test for <code>\pdf@shellescape</code>	26
3.4 Test for escape functions	26
4 Installation	29
4.1 Download	29
4.2 Bundle installation	29
4.3 Package installation	29
4.4 Refresh file name databases	30
4.5 Some details for the interested	30
5 History	30
[2007/11/11 v0.1]	30
[2007/11/12 v0.2]	31
[2007/12/12 v0.3]	31
[2009/04/10 v0.4]	31

[2009/09/22 v0.5]	31
[2009/09/23 v0.6]	31
[2009/12/12 v0.7]	31
[2010/03/01 v0.8]	31
[2010/04/01 v0.9]	31
[2010/11/04 v0.10]	31
[2010/11/11 v0.11]	31
[2011/01/30 v0.12]	31
[2011/03/04 v0.13]	31
[2011/04/10 v0.14]	31
[2011/04/16 v0.15]	32
[2011/04/22 v0.16]	32
6 Index	32

The `picture` package

Abstract

There are macro and environment arguments that expect numbers that will internally be multiplicated with `\unitlength`. This package extends the syntax of these arguments that dimens with calculation support can be added for these arguments.

1 User interface	2
1.1 Introduction	2
1.2 Options	2
1.3 Example	2
1.4 Supported packages	2
2 Implementation	3
2.1 Identification	3
2.2 Options	3
2.3 Calculation method	3
2.3.1 Method <code>calc</code>	3
2.3.2 Method <code>etex</code>	4
2.3.3 Method <code>plain</code>	4
2.3.4 Help macros	4
2.4 Redefinitions	5
2.4.1 L ^A T _E X base macros	6
2.4.2 Package <code>pspicture</code>	6
2.5 Check package loading order	6
3 Installation	7
3.1 Download	7
3.2 Bundle installation	7
3.3 Package installation	7
3.4 Refresh file name databases	8
3.5 Some details for the interested	8
4 History	8
[2006/08/26 v1.0]	8
[2007/04/11 v1.1]	8
[2008/11/26 v1.2]	8
[2009/10/11 v1.3]	8
5 Index	9

The `pmbboxdraw` package

Abstract

Package `pmbboxdraw` declares box drawings characters of old code pages, e.g. cp437. It uses rules instead of using a font.

1 User interface	2
1.1 Introduction	2
1.2 Setup	2
1.3 Symbol list	2
2 Implementation	9
2.1 Initial stuff	9
2.2 Resources	11
2.3 Dummy font encoding	11
2.4 Setup	11
2.4.1 Options	11
2.4.2 Setup commands of version 1.0	13
2.5 Utils	14
2.6 Block elements	16
2.6.1 U+2580	16
2.6.2 U+2581	16
2.6.3 U+2582	16
2.6.4 U+2583	17
2.6.5 U+2584	17
2.6.6 U+2585	17
2.6.7 U+2586	17
2.6.8 U+2587	17
2.6.9 U+2588	17
2.6.10 U+2589	18
2.6.11 U+258A	18
2.6.12 U+258B	18
2.6.13 U+258C	18
2.6.14 U+258D	18
2.6.15 U+258E	18
2.6.16 U+258F	19
2.6.17 U+2590	19
2.6.18 U+2594	19
2.6.19 U+2595	19
2.7 Shade characters	19
2.7.1 U+2591	20
2.7.2 U+2592	20
2.7.3 U+2593	20
2.7.4 Color warning	20
2.8 Terminal graphics characters	20
2.8.1 U+2596	21
2.8.2 U+2597	21

2.8.3	U+2598	21
2.8.4	U+2599	21
2.8.5	U+259A	21
2.8.6	U+259B	22
2.8.7	U+259C	22
2.8.8	U+259D	22
2.8.9	U+259E	22
2.8.10	U+259F	22
2.9	Box drawing	23
2.9.1	U+2500	23
2.9.2	U+2501	23
2.9.3	U+2502	23
2.9.4	U+2503	24
2.9.5	U+250C	24
2.9.6	U+250D	24
2.9.7	U+250E	25
2.9.8	U+250F	25
2.9.9	U+2510	26
2.9.10	U+2511	26
2.9.11	U+2512	27
2.9.12	U+2513	27
2.9.13	U+2514	28
2.9.14	U+2515	28
2.9.15	U+2516	29
2.9.16	U+2517	29
2.9.17	U+2518	30
2.9.18	U+2519	30
2.9.19	U+251A	31
2.9.20	U+251B	31
2.9.21	U+251C	32
2.9.22	U+251D	32
2.9.23	U+251E	33
2.9.24	U+251F	33
2.9.25	U+2520	34
2.9.26	U+2521	34
2.9.27	U+2522	35
2.9.28	U+2523	36
2.9.29	U+2524	36
2.9.30	U+2525	37
2.9.31	U+2526	37
2.9.32	U+2527	38
2.9.33	U+2528	38
2.9.34	U+2529	39
2.9.35	U+252A	39
2.9.36	U+252B	40
2.9.37	U+252C	40

2.9.38 U+252D	41
2.9.39 U+252E	41
2.9.40 U+252F	42
2.9.41 U+2530	43
2.9.42 U+2531	43
2.9.43 U+2532	44
2.9.44 U+2533	44
2.9.45 U+2534	45
2.9.46 U+2535	45
2.9.47 U+2536	46
2.9.48 U+2537	47
2.9.49 U+2538	47
2.9.50 U+2539	48
2.9.51 U+253A	49
2.9.52 U+253B	49
2.9.53 U+253C	50
2.9.54 U+253D	50
2.9.55 U+253E	51
2.9.56 U+253F	51
2.9.57 U+2540	52
2.9.58 U+2541	52
2.9.59 U+2542	53
2.9.60 U+2543	53
2.9.61 U+2544	54
2.9.62 U+2545	55
2.9.63 U+2546	56
2.9.64 U+2547	57
2.9.65 U+2548	57
2.9.66 U+2549	58
2.9.67 U+254A	58
2.9.68 U+254B	59
2.10 Box drawing, double lines	59
2.10.1 U+2550	60
2.10.2 U+2551	60
2.10.3 U+2552	61
2.10.4 U+2553	61
2.10.5 U+2554	62
2.10.6 U+2555	62
2.10.7 U+2556	63
2.10.8 U+2557	63
2.10.9 U+2558	64
2.10.10 U+2559	64
2.10.11 U+255A	65
2.10.12 U+255B	66
2.10.13 U+255C	66
2.10.14 U+255D	67

2.10.15 U+255E	67
2.10.16 U+255F	68
2.10.17 U+2560	68
2.10.18 U+2561	69
2.10.19 U+2562	70
2.10.20 U+2563	70
2.10.21 U+2564	71
2.10.22 U+2565	71
2.10.23 U+2566	72
2.10.24 U+2567	73
2.10.25 U+2568	73
2.10.26 U+2569	73
2.10.27 U+256A	74
2.10.28 U+256B	75
2.10.29 U+256C	75
2.10.30 U+2574	76
2.10.31 U+2575	76
2.10.32 U+2576	76
2.10.33 U+2577	77
2.10.34 U+2578	77
2.10.35 U+2579	77
2.10.36 U+257A	78
2.10.37 U+257B	78
2.10.38 U+257C	78
2.10.39 U+257D	79
2.10.40 U+257E	79
2.10.41 U+257F	79
2.11 Box drawing, light single lines	80
2.12 Unicode support file	80
3 Test	82
3.1 Catcode checks for loading	82
4 Installation	84
4.1 Download	84
4.2 Bundle installation	84
4.3 Package installation	85
4.4 Refresh file name databases	85
4.5 Some details for the interested	85
5 References	86
6 History	86
[2006/05/03 v1.0]	86
[2011/03/24 v1.1]	86
7 Index	86

The `protecteddef` package

Abstract

This packages provides `\ProtectedDef` for defining robust macros for both plain `TeX` and `LATEX`. First ε -`TeX`'s `\protected` is tried, then `LATEX`'s `\DeclareRobustCommand` is used. Otherwise the macro is not made robust.

1 Documentation	1
1.1 The <code>L^AT_EX</code> 's way	2
1.2 The ε - <code>TeX</code> 's way	2
1.3 The way of this package	2
1.4 Usage	2
2 Implementation	2
2.1 Reload check and package identification	2
2.2 Catcodes	4
2.3 Resources	4
3 Test	6
3.1 Catcode checks for loading	6
3.2 Test without <code>L^AT_EX</code> and <code>\protected</code>	8
4 Installation	11
4.1 Download	11
4.2 Bundle installation	11
4.3 Package installation	11
4.4 Refresh file name databases	11
4.5 Some details for the interested	12
5 History	12
[2011/01/31 v1.0]	12
6 Index	12

The `refcount` package

Abstract

References are not numbers, however they often store numerical data such as section or page numbers. `\ref` or `\pageref` cannot be used for counter assignments or calculations because they are not expandable, generate warnings, or can even be links. The package provides expandable macros to extract the data from references. Packages `hyperref`, `nameref`, `titleref`, and `babel` are supported.

1 Usage	2
1.1 Setting counters	2
1.2 Expandable commands	2
1.3 Undefined references	3
1.3.1 Check for undefined references	3
1.4 Notes	3
2 Implementation	3
2.1 Loading packages	5
2.2 Defining commands	5
2.3 <code>\setrefcountdefault</code>	6
2.4 <code>\refused</code>	6
2.5 Setting counters by reference data	7
2.5.1 Generic setting	7
2.5.2 User commands	8
2.6 Extracting references	8
2.7 Macros for checking undefined references	10
3 Test	10
3.1 Catcode checks for loading	10
3.2 Macro tests	12
3.3 Test with package <code>titleref</code>	15
4 Installation	16
4.1 Download	16
4.2 Bundle installation	16
4.3 Package installation	16
4.4 Refresh file name databases	17
4.5 Some details for the interested	17
5 History	17
[1998/04/08 v1.0]	17
[2000/09/07 v2.0]	17
[2006/02/20 v3.0]	17
[2008/08/11 v3.1]	18
[2010/12/01 v3.2]	18
6 Index	18

The `rerunfilecheck` package

Abstract

The package provides additional rerun warnings if some auxiliary files have changed. It is based on MD5 checksum, provided by pdfTeX.

1 Documentation	1
1.1 Options	2
1.2 Interface for class/package authors	2
2 Implementation	3
2.1 Options	4
2.2 Check for checksum feature	4
2.3 Standard .aux files	4
2.4 Rerun check	7
3 Test	8
3.1 Catcode checks for loading	9
4 Installation	10
4.1 Download	10
4.2 Bundle installation	11
4.3 Package installation	11
4.4 Refresh file name databases	11
4.5 Some details for the interested	11
5 History	12
[2009/12/10 v1.0]	12
[2009/12/12 v1.1]	12
[2009/12/18 v1.2]	12
[2010/01/25 v1.3]	12
[2010/02/22 v1.4]	12
[2010/03/15 v1.5]	12
[2010/03/16 v1.6]	12
[2011/04/15 v1.7]	12
6 Index	13

The `resizegather` package

Abstract

Equations that are too large are resized to fit the available space. The environment `gather` of package `amsmath` is supported. Also the environments `equation` and `displaymath` are redefined using `gather` and its starred version.

1 Documentation	1
1.1 Options	2
1.2 Options for packages <code>amsmath</code> or <code>graphics</code>	2
2 Implementation	3
3 Test	8
3.1 Catcode checks for loading	8
4 Installation	9
4.1 Download	9
4.2 Bundle installation	10
4.3 Package installation	10
4.4 Refresh file name databases	10
4.5 Some details for the interested	10
5 Acknowledgement	11
6 History	11
[2009/12/04 v1.0]	11
[2009/12/05 v1.1]	11
[2010/03/01 v1.2]	11
7 Index	11

The `rotchiffre` package

Abstract

This package implements chiffres ROT13 with its variants ROT5, ROT18, and ROT47.

1 Documentation	2
1.1 Motivation	2
1.2 Usage	2
1.2.1 Examples	2
2 Implementation	3
2.1 Reload check and package identification	3
2.2 Catcodes	4
2.3 Loading resources	5
2.4 <code>\EdefRot</code> as robust macro	5
2.5 Set <code>\lccode</code> on a range of characters	5
2.6 Chiffres	6
2.6.1 ROT13	6
2.6.2 ROT5	6
2.6.3 ROT18	7
2.6.4 ROT47	7
2.7 <code>\RotCh@rot</code> with big char support	7
2.8 <code>\RotCh@rot</code> without big char support	8
3 Test	8
3.1 Catcode checks for loading	8
3.2 Macro tests	10
3.2.1 Preamble	10
3.2.2 ROT13	13
3.2.3 ROT5	13
3.2.4 ROT18	13
3.2.5 ROT47	13
3.2.6 Big chars	14
4 Installation	14
4.1 Download	14
4.2 Bundle installation	15
4.3 Package installation	15
4.4 Refresh file name databases	15
4.5 Some details for the interested	15
5 References	16
6 History	17
[2010/11/12 v1.0]	17
7 Index	17

The `scrindex` package

Abstract

This package redefines environment ‘theindex’ of package `index`, if a class from KOMA-Script is loaded. Also option `idxtotoc` is supported. Index preambles can be given either by means of package `index` or via the interface provided by KOMA-Script.

1 Documentation	1
1.1 Usage	2
1.2 Preambles	2
1.2.1 Class <code>scrartcl</code>	2
1.2.2 Classes <code>scrreprt</code> and <code>scrbook</code>	2
2 Implementation	3
3 Installation	6
3.1 Download	6
3.2 Bundle installation	6
3.3 Package installation	6
3.4 Refresh file name databases	7
3.5 Some details for the interested	7
4 History	7
[2008/07/07 v1.0]	7
[2008/08/11 v1.1]	8
5 Index	8

The **selinput** package

Abstract

This package selects the input encoding by specifying between input characters and their glyph names.

1 Documentation	1
1.1 Introduction	1
1.2 User interface	2
1.3 Options	3
1.4 Encodings	3
2 Implementation	3
3 Test	7
4 Installation	9
4.1 Download	9
4.2 Bundle installation	9
4.3 Package installation	10
4.4 Refresh file name databases	10
4.5 Some details for the interested	10
5 References	11
6 History	11
[2007/06/16 v1.0]	11
[2007/06/20 v1.1]	11
[2007/09/09 v1.2]	11
7 Index	11

The `setouterhbox` package

Abstract

If math stuff is set in an `\hbox`, then TeX performs some optimization and omits the implicit penalties `\binoppenalty` and `\relpenalty`. This package tries to put stuff into an `\hbox` without getting lost of those penalties.

1 Documentation	2
1.1 Introduction	2
1.2 Acknowledgement	2
1.3 Usage	2
1.4 Option <code>hyperref</code>	3
1.5 Example	3
2 Implementation	3
2.1 Package start stuff	3
2.2 Interface macros	5
2.3 Main part	6
2.4 Environment support	8
2.5 Option <code>hyperref</code>	9
3 Test	9
3.1 Catcode checks for loading	9
3.2 Test with package <code>url</code>	11
4 Installation	11
4.1 Download	11
4.2 Bundle installation	11
4.3 Package installation	12
4.4 Refresh file name databases	12
4.5 Some details for the interested	12
5 References	13
6 History	13
[2005/10/05 v1.0]	13
[2005/10/07 v1.1]	13
[2005/10/18 v1.2]	13
[2006/02/12 v1.3]	13
[2006/08/26 v1.4]	13
[2007/04/26 v1.5]	13
[2007/05/17 v1.6]	14
[2007/09/09 v1.7]	14
7 Index	14

The `settobox` package

Abstract

Commands are defined for getting box sizes similar to L^AT_EX's `\settowidth` commands.

1 Usage	1
1.1 Get box dimensions	1
1.2 Set box dimensions	2
1.3 Move box	2
1.4 Example	2
1.4.1 Short example	2
1.4.2 Test file that shows box manipulations	2
2 Implementation	4
3 Installation	6
3.1 Download	6
3.2 Bundle installation	6
3.3 Package installation	6
3.4 Refresh file name databases	7
3.5 Some details for the interested	7
4 History	7
[2000/02/11 v1.0]	7
[2000/09/07 v1.1]	7
[2006/02/20 v1.2]	7
[2007/04/11 v1.3]	8
[2008/08/11 v1.4]	8
5 Index	8

The `soulutf8` package

Abstract

This package extends package `soul` and adds some support for UTF-8. Namely the input encodings `utf8.def` from package `inputenc` and package `ucs`'s `utf8x.def` are supported.

1 Documentation	2
1.1 Patch	2
1.2 Future	2
2 Implementation	2
2.1 Reload check and package identification	2
2.2 Catcodes	3
2.3 Loading packages	4
2.3.1 plain \TeX	5
2.3.2 \LaTeX	5
2.3.3 $\varepsilon\text{-}\text{\TeX}$	5
2.4 Macro for redefinitions	6
2.5 Redefinition of <code>\SOUL@eval</code>	6
2.6 UTF-8 analysis	9
2.6.1 Help strings	9
2.6.2 Support for <code>utf8.def</code>	10
2.6.3 Support for <code>utf8x.def</code>	10
2.7 Actions for UTF-8 sequences	11
2.7.1 Redefinition of <code>\SOUL@splittoken</code>	11
2.8 Patches	12
3 Test	15
3.1 Catcode checks for loading	15
3.2 \LaTeX tests	16
3.2.1 Driver definitions	17
3.2.2 Test macros	19
3.2.3 Testing	22
4 Installation	22
4.1 Download	22
4.2 Bundle installation	23
4.3 Package installation	23
4.4 Refresh file name databases	23
4.5 Some details for the interested	23
5 References	24
6 History	24
[2007/09/09 v1.0]	24
7 Index	24

The `stackrel` package

Abstract

This package adds an optional argument to `\stackrel` for putting something below the relational symbol and defines `\stackbin` for binary symbols.

1 User interface	1
2 Implementation	2
3 Installation	3
3.1 Download	3
3.2 Bundle installation	3
3.3 Package installation	3
3.4 Refresh file name databases	3
3.5 Some details for the interested	4
4 History	4
[2006/12/02 v1.0]	4
[2007/05/06 v1.1]	4
[2007/11/11 v1.2]	4
5 Index	4

The `stampinclude` package

Abstract

The package replaces `\includeonly` and selects the files for `\include` by inspecting the time stamp of the `.aux` file. The file is selected for inclusion if the `.aux` file does not yet exist or is older than the corresponding `.tex` file.

1 Documentation	1
1.1 Introduction	1
1.2 Usage	2
1.3 Limitations	2
1.3.1 Other file dependencies	2
1.3.2 <code>\include</code> dependencies	2
1.3.3 Summary	3
1.4 Requirements	3
2 Implementation	3
3 Installation	4
3.1 Download	4
3.2 Bundle installation	5
3.3 Package installation	5
3.4 Refresh file name databases	5
3.5 Some details for the interested	5
4 References	6
5 History	6
[2008/07/14 v1.0]	6
6 Index	6

The `stringenc` package

Abstract

This package provides `\StringEncodingConvert` for converting a string between different encodings. Both L^AT_EX and plain-T_EX are supported.

1 Documentation	2
1.1 User interface	2
1.2 Supported encodings	3
2 Implementation	3
2.1 Reload check and package identification	4
2.2 Catcodes	5
2.3 Tools	6
2.4 Encoding aliases	16
2.5 Encoding files	18
2.5.1 UTF-32BE, UTF-32LE	18
2.5.2 UTF-8	20
2.5.3 UTF-16LE	26
2.5.4 PDFDocEncoding	26
2.5.5 ISO-8859-1	28
2.5.6 CP1252	29
2.5.7 US-ASCII	30
2.5.8 Encoding ascii-print	31
2.5.9 Clean7Bit	31
2.5.10 Other encodings (8 bit)	33
3 Test	75
3.1 Catcode checks for loading	75
3.2 Conversion tests	76
3.2.1 UTF8/16/32 encodings	77
3.2.2 ASCII	79
3.2.3 PDFDocEncoding	80
3.2.4 ISO-8859-1	80
3.2.5 CP1252	80
3.2.6 KOI8-R	81
3.2.7 DEC-MCS	81
3.3 Removal of byte order marks	81
4 Installation	82
4.1 Download	82
4.2 Bundle installation	82
4.3 Package installation	82
4.4 Refresh file name databases	83
4.5 Some details for the interested	83

5 History	84
[2007/06/14 v1.0]	84
[2007/06/16 v1.1]	84
[2007/09/09 v1.2]	84
[2007/10/22 v1.3]	84
[2007/11/11 v1.4]	84
[2007/11/25 v1.5]	84
[2008/10/27 v1.6]	84
[2009/12/15 v1.7]	85
[2010/03/01 v1.8]	85
6 Index	85

The `tabularht` package

Abstract

This package defines some environments that adds a height specification to tabular and array.

1 Usage	1
1.1 Option <code>vlines</code>	2
1.2 Limitations	3
1.3 Compatibility	3
1.4 Examples	3
1.4.1 Example 1	3
1.4.2 Example 2	3
2 Implementation	4
2.1 Environments	4
2.2 Options	6
2.3 Option <code>vlines</code> , driver independent stuff	7
2.4 Driver pdftex	7
2.5 DVI drivers	11
3 Installation	13
3.1 Download	13
3.2 Bundle installation	13
3.3 Package installation	14
3.4 Refresh file name databases	14
3.5 Some details for the interested	14
4 History	15
[2005/09/22 v1.0]	15
[2005/10/16 v2.0]	15
[2005/10/18 v2.1]	15
[2006/02/20 v2.2]	15
[2006/12/22 v2.3]	15
[2007/03/21 v2.4]	15
[2007/04/11 v2.5]	15
5 Index	15

The **tabularkv** package

Abstract

This package adds a key value interface for tabular by the new environment **tabularkv**. Thus the TeX source code looks better by named parameters, especially if package **tabularht** is used.

1 Usage	1
1.1 Example	2
2 Implementation	2
3 Installation	3
3.1 Download	3
3.2 Bundle installation	3
3.3 Package installation	3
3.4 Refresh file name databases	3
3.5 Some details for the interested	4
4 History	4
[2005/09/22 v1.0]	4
[2006/02/20 v1.1]	4
5 Index	4

The `telprint` package

Abstract

Package `telprint` provides `\telprint` for formatting German phone numbers.

1 Documentation	2
1.1 Introduction	2
1.2 Short overview in English	2
1.2.1 Configuration	2
1.3 Documentation in German	2
2 Implementation	3
2.1 Reload check and package identification	3
2.2 Catcodes	4
2.3 Package macros	5
3 Test	7
3.1 Catcode checks for loading	7
4 Installation	9
4.1 Download	9
4.2 Bundle installation	9
4.3 Package installation	9
4.4 Refresh file name databases	10
4.5 Some details for the interested	10
5 History	10
[1996/11/28 v1.0]	10
[1997/09/16 v1.1]	11
[1997/10/16 v1.2]	11
[1997/12/09 v1.3]	11
[2004/11/02 v1.4]	11
[2005/09/30 v1.5]	11
[2006/02/12 v1.6]	11
[2006/08/26 v1.7]	11
[2007/04/11 v1.8]	11
[2007/09/09 v1.9]	11
[2008/08/11 v1.10]	11
6 Index	12

The **transparent** package

Abstract

Since version 1.40 pdfTeX supports several color stacks. This package shows, how a separate color stack can be used for transparency, a property besides color.

1 User interface	1
2 Implementation	2
2.1 Identification	2
2.2 Initial checks	2
2.2.1 Check for pdfTeX in PDF mode	2
2.2.2 Check pdfTeX version	2
2.3 Transparency	2
3 Installation	4
3.1 Download	4
3.2 Bundle installation	4
3.3 Package installation	5
3.4 Refresh file name databases	5
3.5 Some details for the interested	5
4 History	5
[2007/01/08 v1.0]	5
5 Index	6

The `twoopt` package

Abstract

This package provides commands to define macros with two optional arguments.

1	Usage	1
2	Implementation	2
3	Installation	3
3.1	Download	3
3.2	Bundle installation	4
3.3	Package installation	4
3.4	Refresh file name databases	4
3.5	Some details for the interested	4
4	History	5
[1998/10/30 v1.0]	5
[1998/10/30 v1.1]	5
[1998/11/04 v1.2]	5
[1999/04/12 v1.3]	5
[2006/02/20 v1.4]	5
[2008/08/11 v1.5]	5
5	Index	6

The `uniquecounter` package

Abstract

This package provides a kind of counter that provides unique number values. Several counter can be created by different names. The numeric values are not limited.

1 Documentation	1
1.1 Example	2
2 Implementation	2
2.1 Reload check and package identification	2
2.2 Catcodes	3
3 Test	6
3.1 Catcode checks for loading	6
3.2 Macro tests	8
3.2.1 Test with L ^A T _E X	8
3.2.2 Test with plain-T _E X	9
4 Installation	10
4.1 Download	10
4.2 Bundle installation	11
4.3 Package installation	11
4.4 Refresh file name databases	11
4.5 Some details for the interested	11
5 History	12
[2009/09/11 v1.0]	12
[2009/12/18 v1.1]	12
[2011/01/30 v1.2]	12
6 Index	12

The `zref` package

Abstract

Package `zref` tries to get rid of the restriction in L^AT_EX's reference system that only two properties are supported. The package implements an extensible referencing system, where properties are handled in a more flexible way. It offers an interface for macro programmers for the access to the system and some applications that uses the new reference scheme.

1	Introduction	3
1.1	Standard L ^A T _E X behaviour	4
1.2	Basic idea	4
1.3	Interfaces	4
2	Interface for programmers	5
2.1	Entities	5
2.2	Property list	5
2.3	Property	6
2.4	Reference generation	6
2.5	Data extraction	7
2.6	Setup	8
2.7	Declared properties	9
2.8	Wrapper for advanced situations	9
2.9	Counter for unique names	10
3	User interface	10
3.1	Module <code>user</code>	10
3.2	Module <code>abspage</code>	11
3.3	Module <code>lastpage</code>	11
3.3.1	Tests for last page	12
3.3.2	Example	12
3.4	Module <code>thepage</code>	13
3.5	Module <code>nextpage</code>	13
3.5.1	Configuration	13
3.5.2	Example	14
3.6	Module <code>totpages</code>	14
3.7	Module <code>pagelayout</code>	15
3.8	Module <code>marks</code>	15
3.9	Module <code>runs</code>	15
3.10	Module <code>perpage</code>	16
3.11	Module <code>counter</code>	16
3.12	Module <code>titleref</code>	16
3.13	Module <code>savepos</code>	17
3.14	Module <code>dotfill</code>	18
3.15	Module <code>env</code>	18
3.16	Module <code>xr</code>	18

4	ToDo	19
5	Example	19
6	Implementation	21
6.1	Package <code>zref</code>	21
6.1.1	Identification	21
6.1.2	Load basic module	22
6.1.3	Process options	22
6.2	Module <code>base</code>	22
6.2.1	Prefixes	22
6.2.2	Identification	23
6.2.3	Utilities	23
6.2.4	Check for ε - <code>T_EX</code>	24
6.2.5	Auxiliary file stuff	24
6.2.6	Property lists	24
6.2.7	Properties	28
6.2.8	Reference generation	30
6.2.9	Reference querying and extracting	33
6.2.10	Compatibility with <code>babel</code>	36
6.2.11	Unique counter support	36
6.2.12	Utilities	37
6.2.13	Setup	37
6.3	Module <code>user</code>	38
6.4	Module <code>abspage</code>	39
6.5	Module <code>counter</code>	40
6.6	Module <code>lastpage</code>	40
6.7	Module <code>thepage</code>	41
6.8	Module <code>nextpage</code>	42
6.9	Module <code>totpages</code>	43
6.10	Module <code>pagelayout</code>	44
6.11	Module <code>pageattr</code>	47
6.12	Module <code>marks</code>	50
6.13	Module <code>runs</code>	51
6.14	Module <code>perpage</code>	51
6.15	Module <code>titleref</code>	53
6.15.1	Implementation	54
6.15.2	User interface	55
6.15.3	Patches for section and caption commands	55
6.15.4	Environment description	56
6.15.5	Class <code>memoir</code>	56
6.15.6	Class <code>beamer</code>	57
6.15.7	Package <code>titlesec</code>	57
6.15.8	Package <code>longtable</code>	58
6.15.9	Package <code>listings</code>	58
6.15.10	Theorems	58

6.16 Module <code>xr</code>	58
6.17 Module <code>hyperref</code>	66
6.18 Module <code>savepos</code>	66
6.18.1 Identification	66
6.18.2 Availability	66
6.18.3 Setup	67
6.18.4 User macros	67
6.19 Module <code>abspos</code>	68
6.19.1 Identification	68
6.20 Module <code>dotfill</code>	68
6.21 Module <code>env</code>	69
7 Test	70
7.1 <code>\zref@localaddprop</code>	70
7.2 Module <code>base</code>	70
7.3 Module <code>runs</code>	71
7.4 Module <code>titleref</code>	72
8 Installation	73
8.1 Download	73
8.2 Bundle installation	73
8.3 Package installation	73
8.4 Refresh file name databases	74
8.5 Some details for the interested	74
9 References	75
10 History	75
[2006/02/20 v1.0]	75
[2006/05/03 v1.1]	75
[2006/05/25 v1.2]	75
[2006/09/08 v1.3]	75
[2007/01/23 v1.4]	75
[2007/02/18 v1.5]	76
[2007/04/06 v1.6]	76
[2007/04/17 v1.7]	76
[2007/04/22 v1.8]	76
[2007/05/02 v1.9]	76
[2007/05/06 v2.0]	76
[2007/05/28 v2.1]	76
[2008/09/21 v2.2]	76
[2008/10/01 v2.3]	76
[2009/08/07 v2.4]	76
[2009/12/06 v2.5]	76
[2009/12/07 v2.6]	77
[2009/12/08 v2.7]	77
[2010/03/26 v2.8]	77

[2010/03/29 v2.9]	77
[2010/04/08 v2.10]	77
[2010/04/15 v2.11]	77
[2010/04/17 v2.12]	77
[2010/04/19 v2.13]	77
[2010/04/22 v2.14]	78
[2010/04/23 v2.15]	78
[2010/04/28 v2.16]	78
[2010/05/01 v2.17]	78
[2010/05/13 v2.18]	78
[2010/10/22 v2.19]	78
[2011/02/12 v2.20]	79
[2011/03/18 v2.21]	79
11 Index	79