

# The `scrindex` package

Heiko Oberdiek  
<heiko.oberdiek at gmail.com>

2008/08/11 v1.1

## Abstract

This package redefines environment ‘`theindex`’ of package `index`, if a class from KOMA-Script is loaded. Also option `idxdotoc` is supported. Index preambles can be given either by means of package `index` or via the interface provided by KOMA-Script.

## Contents

|          |  |          |
|----------|--|----------|
| <b>1</b> | <b>Documentation</b>                                   | <b>1</b> |
| 1.1      | Usage  | 2        |
| 1.2      | Preambles  | 2        |
| 1.2.1    | Class <code>scartcl</code>                             | 2        |
| 1.2.2    | Classes <code>scrreprt</code> and <code>scrbook</code> | 2        |
| <b>2</b> | <b>Implementation</b>                                  | <b>3</b> |
| <b>3</b> | <b>Installation</b>                                    | <b>6</b> |
| 3.1      | Download   | 6        |
| 3.2      | Bundle installation                                    | 6        |
| 3.3      | Package installation                                   | 6        |
| 3.4      | Refresh file name databases                            | 7        |
| 3.5      | Some details for the interested                        | 7        |
| <b>4</b> | <b>Catalogue</b>                                       | <b>7</b> |
| <b>5</b> | <b>History</b>   | <b>8</b> |
|          | [2008/07/07 v1.0]                                      | 8        |
|          | [2008/08/11 v1.1]                                      | 8        |
| <b>6</b> | <b>Index</b>   | <b>8</b> |

## 1 Documentation

Package `index`, written by David M. Jones, detects the standard classes `article`, `report`, and `book`. It redefines environment ‘`theindex`’ for its needs. However, it does not know other classes such as KOMA-Script. This package closes the compatibility gap between KOMA-Script’s classes and package `index`.

Environment `theindex` is redefined to support both package `index` and KOMA-Script’s classes. Thus both the prologue of package `index` and the preamble of KOMA-Script’s classes are available. Also class option `idxdotoc` of KOMA-Script is supported.

## 1.1 Usage

The package `scrindex` is loaded without options:

```
\usepackage{scrindex}
```

It loads package `index` and requests version 2004/01/20 or later.  $\text{\LaTeX}$ 's package interface allows multiple calls of the same package. The package is loaded at its first package loading command. At later times  $\text{\LaTeX}$  only checks options and a requested version date. Therefore it does not harm to add `\usepackage{index}` before or after `\usepackage{scrindex}`.

Also the class does not matter. Environment `theindex` is only redefined for a supported class:

- `scrartcl`
- `scrreprt`
- `scrbook`

## 1.2 Preambles

Both the prologue of package `index` and the preamble of KOMA-Script's classes are supported. The position depends on the class.

### 1.2.1 Class `scrartcl`

```
1 <*example1>
2 \documentclass{scrartcl}
3 \usepackage{scrindex}
4 \setindexpreamble{Preamble of \texttt{scrartcl}\dotfill EOL}
5 \makeindex
6 \begin{document}
7 \section{First Section}
8 \index{first}
9 \index{section}
10 \printindex[default]%
11 [Prologue of package \texttt{index}\dotfill EOL]%
12 \end{document}
13 </example1>
```

The prologue of package `index` is first set straight after the section title spanning both columns. Then the preamble of KOMA-Script follows in the first left column.

|  |  |
|--|--|
| <b>Index</b>                                     |  |
| Prologue of package <code>index</code> ..... EOL |  |
| Preamble of <code>scrartcl</code> .. EOL         |  |
| first, 1   |  |
| section, 1                                       |  |

### 1.2.2 Classes `scrreprt` and `scrbook`

```
14 <*example2>
15 \documentclass[openany]{scrbook}% or scrreprt
16 \usepackage{scrindex}
17 \setindexpreamble{Preamble of class \texttt{scrbook}\dotfill EOL}
18 \makeindex
19 \begin{document}
20 \chapter{First Chapter}
21 \index{first}
22 \index{chapter}
23 \printindex[default]%
```

```

24 [Prologue of package \texttt{index}\dotfill EOL]%
25 \end{document}
26 \end{example2}

```

The order of the two preambles are different for the classes `scrreprt` and `scrbook`. First KOMA-Script's chapter preamble is set, then the prologue of package `index` follows. Both are set spanning both columns.

|  |     |
|--|-----|
| <b>Index</b>                                     |     |
| Preamble of class <code>scrbook</code> . . . . . | EOL |
| Prologue of package <code>index</code> . . . . . | EOL |
| chapter, 1                                       |     |
| first, 1   |     |

## 2 Implementation

```

27 \*package)
28 \NeedsTeXFormat{LaTeX2e}
29 \ProvidesPackage{scrindex}
30 [2008/08/11 v1.1 Package index with KOMA-Script classes (HO)]%
31 \RequirePackage{index}[2004/01/20]%
32 \ifclassloaded{scrartcl}{%
33   \renewenvironment{theindex}{%
34     \edef\indexname{%
35       \the\@nameuse{idxtitle@\@indextype}%
36     }%
37     \if@twocolumn
38       \@restonecolfalse
39     \else
40       \@restonecoltrue
41     \fi
42     \idx@heading
43     \thispagestyle{\indexpagestyle}%
44     \columnseprule\z@
45     \columnsep 35\p@
46     \index@preamble\par\nobreak
47     \parindent\z@
48     \parskip\z@ \@plus .3\p@\relax
49     \parfillskip\z@ \@plus 1fil\relax
50     \let\item\@idxitem
51   }{%
52     \if@restonecol
53       \onecolumn
54     \else
55       \clearpage
56     \fi
57   }%
58 \ifclasswith{scrartcl}{idxtotoc}{%
59   \renewcommand*{\idx@heading}{%
60     \twocolumn[%
61       \addsec{\indexname}%
62       \ifx\index@prologue\@empty
63         \else
64           \index@prologue
65           \bigskip
66         \fi
67     ]%
68   \@mkboth{\indexname}{\indexname}%
69 }%
70 }%

```

```

71   \renewcommand*{\idx@heading}{%
72     \twocolumn[%
73       \section*{\indexname}%
74       \ifx\index@prologue\@empty
75         \else
76           \index@prologue
77           \bigskip
78         \fi
79     ]%
80     \@mkboth{\indexname}{\indexname}%
81   }%
82 }%
83 }{}

84 \@ifclassloaded{scrreprt}{%
85   \renewenvironment{theindex}{%
86     \edef\indexname{%
87       \the\@nameuse{idxtitle@\@indextype}%
88     }%
89     \if@twocolumn
90       \@restonecolfalse
91     \else
92       \@restonecoltrue
93     \fi
94     \setchapterpreamble{\index@preamble}%
95     \idx@heading
96     \thispagestyle{\indexpagestyle}%
97     \columnseprule\z@
98     \columnsep 35\p@
99     \parindent\z@
100    \parskip\z@ \@plus .3\p@\relax
101    \parfillskip\z@ \@plus 1fil\relax
102    \let\item\idxitem
103  }{%
104    \if@restonecol
105      \onecolumn
106    \else
107      \clearpage
108    \fi
109  }%
110 \@ifclasswith{scrreprt}{idxtotoc}{%
111   \renewcommand*{\idx@heading}{%
112     \if@openright
113       \cleardoublepage
114     \else
115       \clearpage
116     \fi
117     \twocolumn[%
118       \addchap{\indexname}%
119       \ifx\index@prologue\@empty
120         \else
121           \index@prologue
122           \bigskip
123         \fi
124     ]%
125     \@mkboth{\indexname}{\indexname}%
126   }%
127 }{}
128   \renewcommand*{\idx@heading}{%
129     \if@openright
130       \cleardoublepage
131     \else
132       \clearpage

```

```

133     \fi
134     \twocolumn[%
135         \chapter*{\indexname}%
136         \ifx\index@prologue\@empty
137         \else
138             \index@prologue
139             \bigskip
140         \fi
141     ]%
142     \@mkboth{\indexname}{\indexname}%
143 }%
144 }%
145 }{}

146 \@ifclassloaded{scrbook}{%
147     \renewenvironment{theindex}{%
148         \edef\indexname{%
149             \the\@nameuse{idxtitle@\@indextype}%
150         }%
151         \if@twocolumn
152             \@restonecolfalse
153         \else
154             \@restonecoltrue
155         \fi
156         \setchapterpreamble{\index@preamble}%
157         \idx@heading
158         \thispagestyle{\indexpagestyle}%
159         \columnseprule\z@
160         \columnsep 35\p@
161         \parindent\z@
162         \parskip\z@ \@plus .3\p@\relax
163         \parfillskip\z@ \@plus 1fil\relax
164         \let\item\idxitem
165     }{%
166         \if@restonecol
167             \onecolumn
168         \else
169             \clearpage
170         \fi
171     }%
172 \@ifclasswith{scrbook}{idxtotoc}{%
173     \renewcommand*{\idx@heading}{%
174         \if@openright
175             \cleardoublepage
176         \else
177             \clearpage
178         \fi
179     \twocolumn[%
180         \addchap{\indexname}%
181         \ifx\index@prologue\@empty
182         \else
183             \index@prologue
184             \bigskip
185         \fi
186     ]%
187     \@mkboth{\indexname}{\indexname}%
188 }%
189 }{}
190 \renewcommand*{\idx@heading}{%
191     \if@openright
192         \cleardoublepage
193     \else
194         \clearpage

```

```

195     \fi
196     \twocolumn[%
197         \chapter*{\indexname}%
198         \ifx\index@prologue\@empty
199         \else
200             \index@prologue
201             \bigskip
202         \fi
203     ]%
204     \@mkboth{\indexname}{\indexname}%
205 }%
206 }%
207 }{}
208 </package>

```

## 3 Installation

### 3.1 Download

**Package.** This package is available on CTAN<sup>1</sup>:

[CTAN:macros/latex/contrib/oberdiek/scrindex.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/scrindex.pdf](#) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

*TDS* refers to the standard “A Directory Structure for  $\TeX$  Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

### 3.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

### 3.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting docstrip archive. The files are extracted by running the `.dtx` through plain  $\TeX$ :

```
tex scrindex.dtx
```

---

<sup>1</sup><ftp://ftp.ctan.org/tex-archive/>

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
scrindex.sty      → tex/latex/oberdiek/scrindex.sty
scrindex.pdf      → doc/latex/oberdiek/scrindex.pdf
scrindex-example1.tex → doc/latex/oberdiek/scrindex-example1.tex
scrindex-example2.tex → doc/latex/oberdiek/scrindex-example2.tex
scrindex.dtx      → source/latex/oberdiek/scrindex.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

### 3.4 Refresh file name databases

If your `TEX` distribution (`teTEX`, `mikTEX`, ...) relies on file name databases, you must refresh these. For example, `teTEX` users run `texhash` or `mktextlsr`.

### 3.5 Some details for the interested

**Attached source.** The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk scrindex.pdf unpack_files output.
```

**Unpacking with L<sup>A</sup>T<sub>E</sub>X.** The `.dtx` chooses its action depending on the format:

**plain T<sub>E</sub>X:** Run `docstrip` and extract the files.

**L<sup>A</sup>T<sub>E</sub>X:** Generate the documentation.

If you insist on using L<sup>A</sup>T<sub>E</sub>X for `docstrip` (really, `docstrip` does not need L<sup>A</sup>T<sub>E</sub>X), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{scrindex.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdfLATEX`:

```
pdflatex scrindex.dtx
makeindex -s gind.ist scrindex.idx
pdflatex scrindex.dtx
makeindex -s gind.ist scrindex.idx
pdflatex scrindex.dtx
```

## 4 Catalogue

The following XML file can be used as source for the [T<sub>E</sub>X Catalogue](#). The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `scrindex.xml`.

```
209 <*catalogue>
210 <?xml version='1.0' encoding='us-ascii'?>
```

```

211 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
212 <entry datestamp='$Date$' modifier='$Author$' id='scrindex'>
213   <name>scrindex</name>
214   <caption>Make index package work with Koma-script classes.</caption>
215   <authorref id='auth:oberdiek' />
216   <copyright owner='Heiko Oberdiek' year='2008' />
217   <license type='lppl1.3' />
218   <version number='1.1' />
219   <description>
220     This package redefines environment `theindex' of package `index',
221     if a class from <xref refid='koma-script'>KOMA-Script</xref> is loaded.
222     Also option `idxtotoc' is supported. Index preambles can be given
223     either by means of package `index' or via the interface provided
224     by <xref refid='koma-script'>KOMA-Script</xref>.
225     <p/>
226     The package is part of the <xref refid='oberdiek'>oberdiek</xref>
227     bundle.
228   </description>
229   <documentation details='Package documentation'
230     href='ctan:/macros/latex/contrib/oberdiek/scrindex.pdf' />
231   <ctan file='true' path='/macros/latex/contrib/oberdiek/scrindex.dtx' />
232   <miktex location='oberdiek' />
233   <texlive location='oberdiek' />
234   <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip' />
235 </entry>
236 </catalogue>

```

## 5 History

[2008/07/07 v1.0]

- First version, also published in newsgroup [de.comp.text.tex](#):  
“[Re: Zähler bei \index](#)”<sup>2</sup>

[2008/08/11 v1.1]

- Code is not changed.
- URLs updated.

## 6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

| Symbols  | A  |
|--|--|
| <code>\@empty</code> . . . . . 62, 74, 119, 136, 181, 198  | <code>\addchap</code> . . . . . 118, 180                   |
| <code>\@idxitem</code> . . . . . 50, 102, 164              | <code>\addsec</code> . . . . . 61                          |
| <code>\@ifclassloaded</code> . . . . . 32, 84, 146         | <b>B</b>   |
| <code>\@ifclasswith</code> . . . . . 58, 110, 172          | <code>\begin</code> . . . . . 6, 19                        |
| <code>\@indextype</code> . . . . . 35, 87, 149             | <code>\bigskip</code> . . . . . 65, 77, 122, 139, 184, 201 |
| <code>\@mkboth</code> . . . . . 68, 80, 125, 142, 187, 204 | <b>C</b>   |
| <code>\@nameuse</code> . . . . . 35, 87, 149               | <code>\chapter</code> . . . . . 20, 135, 197               |
| <code>\@plus</code> . . . . . 48, 49, 100, 101, 162, 163   | <code>\cleardoublepage</code> . . 113, 130, 175, 192       |
| <code>\@restonecolfalse</code> . . . . . 38, 90, 152       | <code>\clearpage</code> . . . . .                          |
| <code>\@restonecoltrue</code> . . . . . 40, 92, 154        | . . 55, 107, 115, 132, 169, 177, 194                       |

<sup>2</sup>Url: <http://groups.google.com/group/de.comp.text.tex/msg/39575b5e2f29be1e>

|                                    |   |  |   |
|------------------------------------|---|--|---|
| <code>\columnsep</code> .....      | 45, 98, 160   | <b>O</b>                               |   |
| <code>\columnseprule</code> .....  | 44, 97, 159   | <code>\onecolumn</code> .....          | 53, 105, 167  |
| <b>D</b>                           |   | <b>P</b>                               |   |
| <code>\documentclass</code> .....  | 2, 15   | <code>\p@</code> .....                 | 45, 48, 98, 100, 160, 162                               |
| <code>\dotfill</code> .....        | 4, 11, 17, 24   | <code>\par</code> .....                | 46  |
| <b>E</b>                           |   | <code>\parfillskip</code> .....        | 49, 101, 163  |
| <code>\end</code> .....            | 12, 25  | <code>\parindent</code> .....          | 47, 99, 161   |
| <b>I</b>                           |   | <code>\parskip</code> .....            | 48, 100, 162  |
| <code>\idx@heading</code> .....    | 42,<br>59, 71, 95, 111, 128, 157, 173, 190                                | <code>\printindex</code> .....         | 10, 23  |
| <code>\if@openright</code> .....   | 112, 129, 174, 191  | <code>\ProvidesPackage</code> .....    | 29  |
| <code>\if@restonecol</code> .....  | 52, 104, 166  | <b>R</b>                               |   |
| <code>\if@twocolumn</code> .....   | 37, 89, 151   | <code>\renewcommand</code> .....       | 59, 71, 111, 128, 173, 190                              |
| <code>\ifx</code> .....            | 62, 74, 119, 136, 181, 198  | <code>\renewenvironment</code> .....   | 33, 85, 147   |
| <code>\index</code> .....          | 8, 9, 21, 22  | <code>\RequirePackage</code> .....     | 31  |
| <code>\index@preamble</code> ..... | 46, 94, 156   | <b>S</b>                               |   |
| <code>\index@prologue</code> ..... | 62, 64, 74, 76, 119,<br>121, 136, 138, 181, 183, 198, 200                 | <code>\section</code> .....            | 7, 73   |
| <code>\indexname</code> .....      | 34,<br>61, 68, 73, 80, 86, 118, 125,<br>135, 142, 148, 180, 187, 197, 204 | <code>\setchapterpreamble</code> ..... | 94, 156   |
| <code>\indexpagestyle</code> ..... | 43, 96, 158   | <code>\setindexpreamble</code> .....   | 4, 17   |
| <code>\item</code> .....           | 50, 102, 164  | <b>T</b>                               |   |
| <b>M</b>                           |   | <code>\texttt</code> .....             | 4, 11, 17, 24   |
| <code>\makeindex</code> .....      | 5, 18   | <code>\the</code> .....                | 35, 87, 149   |
| <b>N</b>                           |   | <code>\thispagestyle</code> .....      | 43, 96, 158   |
| <code>\NeedsTeXFormat</code> ..... | 28  | <code>\twocolumn</code> ..             | 60, 72, 117, 134, 179, 196                              |
| <code>\nobreak</code> .....        | 46  | <b>U</b>                               |   |
|                                    |   | <code>\usepackage</code> .....         | 3, 16   |
|                                    |   | <b>Z</b>                               |   |
|                                    |   | <code>\z@</code> .....                 | 44, 47, 48, 49,<br>97, 99, 100, 101, 159, 161, 162, 163 |