

The `hycolor` package

Heiko Oberdiek
<heiko.oberdiek at googlemail.com>

2011/01/30 v1.7

Abstract

Package `hycolor` implements the color option stuff that is used by packages `hyperref` and `bookmark`. It is not intended as package for the user.

Contents

1 Documentation	2
1.1 Summary	2
2 Implementation	3
2.1 Normalization	3
2.1.1 Sanitize value of color option	3
2.1.2 Normalize result	4
2.2 Main algorithm for color options	5
2.3 Package <code>bookmark</code>	5
2.4 Utils	7
2.5 Package <code>hyperref</code>	8
2.5.1 Options Hyp.*color	8
2.5.2 Generic algorithm	10
2.5.3 Field options	12
2.5.4 Detection for naked RGB values	12
2.5.5 Options *bordercolor	14
2.6 Package <code>attachfile2</code>	15
2.7 Patch for package <code>xcolor</code>	17
2.7.1 Fix fragile \framebox	20
3 Test	20
3.1 Test for package <code>attachfile2</code>	24
3.2 Test for package <code>xcolor</code>	26
3.2.1 Test for \framebox/\fbox	27
4 Installation	28
4.1 Download	28
4.2 Bundle installation	28
4.3 Package installation	28
4.4 Refresh file name databases	29
4.5 Some details for the interested	29
5 Catalogue	29

6 History	30
[2007/04/09 v1.0]	30
[2007/04/11 v1.1]	30
[2008/07/29 v1.2]	30
[2008/08/01 v1.3]	30
[2008/09/08 v1.4]	30
[2009/10/02 v1.5]	30
[2009/12/12 v1.6]	30
[2011/01/30 v1.7]	30
7 Index	30

1 Documentation

The package `hycolor` implements color options for packages `hyperref` and `bookmark`.

Package `xcolor` provides macros for extracting color values and converting color data to other color models. If this package is loaded, the full range of color specifications of packages `color` and `xcolor` are supported including the optional argument for the color model.

```
\hypersetup{linkbordercolor=red}% needs xcolor
\hypersetup{linkbordercolor=[named]{red}}% needs xcolor
\hypersetup{linkbordercolor=[rgb]{1,0,0}}
```

Without package `xcolor` some of the options only support some models, if they are given directly, e.g.:

```
\bookmarksetup{color=[rgb]{1,0,0}}
```

Because of compatibility some options of `hyperref` also support space separated RGB values:

```
\hypersetup{linkbordercolor=1 0 0}% is the same as
\hypersetup{linkbordercolor=[rgb]{1,0,0}}
```

Coloring is optional, it can be turned off by using an empty value:

```
\hypersetup{linkbordercolor={}}
```

The PDF specification knows some kind of an empty color setting without values. This applies to form field colors. The new A virtual color model `empty` is introduced for this purpose, e.g.

```
\TextField[backgroundcolor={[empty]}, ...]{...}% or
\TextField[{backgroundcolor=[empty]}, ...]{...}
```

PDF specification 1.7 also allows this for border link colors. But this isn't currently supported by this package, because the tested viewers (AR7/Linux, `xpdf` 3.00, `ghostscript` 8.54) don't support this yet. In contrary `ghostscript` generates an error message.

1.1 Summary

Color option	Models without <code>xcolor</code>	RGB color	Model <code>empty</code>
<code>BKM.color</code>	<code>gray, rgb</code>	no	no
<code>Hyp.*color</code>	<code>all</code>	no	no
<code>Hyp.*bordercolor</code>	<code>gray, rgb</code>	yes	no
<code>Field.*color</code>	<code>gray, rgb, cmyk</code>	yes	yes
<code>AtFi.color</code>	<code>gray, rgb</code>	yes	no

“RGB color” means that the color value can be given as space separated RGB numbers (real numbers in the range from 0 to 1). Explanation of the color option prefixes:

Prefix	Explanation
BKM	Package bookmark
Hyp	Package hyperref: package options or \hypersetup
Field	Package hyperref: Form field options
AtFi	Package attachfile2: option color

2 Implementation

```

1 <*package>
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{hycolor}%
4 [2011/01/30 v1.7 Color options for hyperref/bookmark (HO)]%
5 \RequirePackage{xcolor-patch}[2011/01/30]

```

2.1 Normalization

2.1.1 Sanitize value of color option

Procedure DefSanitized(cmd, value)

Param: cmd (macro)

Param: value (value of color option)

Result: value is expanded, sanitized, and stored in macro cmd.

Initialize active characters;

cmd := Expand value;

Sanitize cmd;

Sanitization means that the string does not contain any macros or special tokens. It consists of characters with catcode 12 (other). The only exception is the space with catcode 10 (space).

\HyColor@DefSanitized

```

6 \begingroup
7  \catcode`!=13 %
8  \catcode`\:=13 %
9  \catcode`\-=13 %
10 \catcode`\+=13 %
11 \catcode`\;=13 %
12 \catcode`\"=13 %
13 \catcode`\>=13 %
14 \edef\x{%
15   \def\noexpand!{\string!}%
16   \def\noexpand:{\string:}%
17   \def\noexpand-{\string-}%
18   \def\noexpand+{\string+}%
19   \def\noexpand;{\string;}%
20   \def\noexpand"{\string"}%
21   \def\noexpand>{\string>}%
22 }%
23 \def\y#1{\endgroup
24   \def\HyColor@DefSanitized##1##2{%
25     \begingroup
26       \csname @safe@activestrue\endcsname
27       #1%
28       \edef\x{\endgroup
29         \def\noexpand##1##2{%
30           }%
31       \x

```

```

32      \@onelvel@sanitize##1%
33    }%
34  }%
35 \expandafter\y\expandafter{\x}

```

2.1.2 Normalize result

Procedure NormalizeNum(value, cmd)

Param: value (Sanitized explicit number)

Param: cmd (Macro that stores result)

Result: cmd contains normalized number

```

if value pt < 0pt then
|   cmd ← 0;
else if number before dot of value < 1 then
|   cmd ← number after dot of value;
|   cmd ← strip trailing zeros from cmd;
|   if dot remains only then
|   |   cmd ← 0;
|   end
|   else
|   |   cmd ← 1;
|   end

```

The number is limited to the range between 0.0 and 1.0 and formatted as short PDF number without leading or trailing zeros. The precision of the number isn't changed.

\HyColor@NormalizeNum

```

36 \def\HyColor@NormalizeNum#1#2{%
37   \ifdim#1pt<\z@
38     \def#2{0}%
39   \else
40     \edef#2{\zap@space#1 \empty}%
41     \expandafter\HyColor@CheckDot#2..\@nil#2%
42   \fi
43 }
44 \def\HyColor@CheckDot#1.#2.#3\@nil#4{%
45   \ifnum0#1<\@ne
46     \ifx\\#2\\%
47       \def#4{0}%
48     \else
49       \edef#4{\HyColor@ReverseString#2\@nil{} }%
50       \edef#4{\expandafter\HyColor@StripLeadingZeros#4\empty}%
51       \ifx#4\empty
52         \def#4{0}%
53       \else
54         \edef#4{.\expandafter\HyColor@ReverseString#4\@nil{} }%
55       \fi
56     \fi
57   \else
58     \def#4{1}%
59   \fi
60 }
61 \def\HyColor@ReverseString#1#2\@nil#3{%
62   \ifx\\#2\\%
63     #1#3%
64   \else
65     \@ReturnAfterFi{%
66       \HyColor@ReverseString#2\@nil{#1#3}%
67     }%

```

```

68   \fi
69 }
70 \long\def\@ReturnAfterFi#1\fi{\fi#1}
71 \def\HyColor@StripLeadingZeros#1{%
72   \ifx#10%
73     \expandafter\HyColor@StripLeadingZeros
74   \else
75     #1%
76   \fi
77 }

\HyColor@NormalizeCommaRGB
78 \def\HyColor@NormalizeCommaRGB#1,#2,#3@nil#4{%
79   \HyColor@NormalizeNum{#1}\HyColor@temp
80   \let#4\HyColor@temp
81   \HyColor@NormalizeNum{#2}\HyColor@temp
82   \edef#4{\#4 \HyColor@temp}%
83   \HyColor@NormalizeNum{#3}\HyColor@temp
84   \edef#4{\#4 \HyColor@temp}%
85 }

\HyColor@NormalizeCommaCMYK
86 \def\HyColor@NormalizeCommaCMYK#1,#2,#3,#4@nil#5{%
87   \HyColor@NormalizeNum{#1}\HyColor@temp
88   \let#5\HyColor@temp
89   \HyColor@NormalizeNum{#2}\HyColor@temp
90   \edef#5{\#5 \HyColor@temp}%
91   \HyColor@NormalizeNum{#3}\HyColor@temp
92   \edef#5{\#5 \HyColor@temp}%
93   \HyColor@NormalizeNum{#4}\HyColor@temp
94   \edef#5{\#5 \HyColor@temp}%
95 }

```

2.2 Main algorithm for color options

Procedure MainColorOptionAlgorithm(key, value, cmd)

Param: *key* (name of color option)

Param: *value* (value of color option)

Param: *cmd* (macro that stores result)

Result: Macro *cmd* contains the calculated color specification string or has the meaning of `\relax` if the color must not set

`DefSanitized(temp, value);`

`Call option specific algorithm(key, temp, cmd);`

2.3 Package bookmark

Since v0.8 2007/03/27 package `bookmark` only provides one color option `color`. Because option `rgbcolor` can easily given as color specification in model `rgb`:

`rgbcolor=<r> <g> ≡ color=[rgb]{<r>,<g>,}`

Package `bookmark` stores the result in macro `\BKM@color`. The empty string is interpreted as *no color*.

Procedure `BookmarkColor(value, cmd, package, option)`

Param: `value` (value of option `color`)
Param: `cmd` (macro for result)
Param: `package` (package name for error message)
Param: `option` (option name for error message)

```

switch value do
  case empty
    | cmd  $\leftarrow$  no color;
  endsw
  case with model
    if with xcolor then
      | cmd  $\leftarrow$  ConvertToRGB(model, values);
    else
      if model = rgb then
        | cmd  $\leftarrow$  values as normalized values;
      else if model = gray then
        | cmd  $\leftarrow$  values as normalized tripled values;
      else
        | error;
      end
    end
  endsw
  otherwise
    if with xcolor then
      | (model, values  $\leftarrow$  get model and values;
      | cmd  $\leftarrow$  ConvertToRGB(model, values);
    else
      | error;
    end
  endsw
endsw

```

```

96 \def\HyColor@BookmarkColor#1#2#3#4{%
97   \HyColor@IfModel{#1}{%
98     \HyColor@IfXcolor{%
99       \convertcolorspec\HyColor@model\HyColor@values
100      \HyColor@model@rgb#2%
101      \expandafter\HyColor@NormalizeCommaRGB#2\@nil#2%
102    }{%
103      \ifx\HyColor@model\HyColor@model@rgb
104        \expandafter\HyColor@NormalizeCommaRGB\HyColor@values\@nil#2%
105      \else
106        \ifx\HyColor@model\HyColor@model@gray
107          \expandafter\HyColor@NormalizeNum
108          \expandafter{\HyColor@values}#2%
109          \edef#2{#2 #2 #2}%
110        \else
111          \let#2\@empty
112          \HyColor@ModelErrorModelNoXcolor{#3}{#4}%
113        \fi
114      \fi
115    }%
116  }{%
117    \let#2\HyColor@values
118    \ifx#2\@empty
119      \else

```

```

120      \HyColor@IfXcolor{%
121          \extractcolorspec{#1}#2%
122          \expandafter\convertcolorspec#2\HyColor@model@rgb#2%
123          \expandafter\HyColor@NormalizeCommaRGB#2@nil#2%
124      }{%
125          \let#2\empty
126          \HyColor@ErrorSpecNoXcolor{#3}{#4}%
127      }%
128  \fi
129 }%
130 }

131 \def\HyColor@ModelErrorNoXcolor#1#2{%
132     \PackageError{#1}{%
133         Color model `\\HyColor@model' is not supported\MessageBreak
134         without package `xcolor' in\MessageBreak
135         `#2=[\\HyColor@model]{\\HyColor@values}'%
136     }\@ehc
137 }

138 \def\HyColor@ErrorSpecNoXcolor#1#2{%
139     \PackageError{#1}{%
140         This color specification is not supported\MessageBreak
141         without package `xcolor' in\MessageBreak
142         `#2=\\HyColor@values'%
143     }\@ehc
144 }

145 \def\HyColor@IfModel#1{%
146     \@ifnextchar[{%
147         \HyColor@WithModel
148     }{%
149         \HyColor@WithoutModel
150     }%
151     #1\@nil
152 }
153 \def\HyColor@WithModel[#1]#2\@nil{%
154     \HyColor@DefSanitized\HyColor@model{#1}%
155     \HyColor@DefSanitized\HyColor@values{#2}%
156     \@firstoftwo
157 }
158 \def\HyColor@WithoutModel#1\@nil{%
159     \let\HyColor@model\relax
160     \HyColor@DefSanitized\HyColor@values{#1}%
161     \@secondoftwo
162 }

```

2.4 Utils

```

\@ReturnAfterFi
163 \long\def\@ReturnAfterFi#1\fi{\fi#1}

\HyColor@IfXcolor
164 \def\HyColor@IfXcolor{%
165     \begingroup\expandafter\expandafter\expandafter\endgroup
166     \expandafter\ifx\csname convertcolorspec\endcsname\relax
167         \expandafter\@secondoftwo
168     \else
169         \expandafter\@firstoftwo
170     \fi
171 }

172 \def\HyColor@model@empty{empty}
173 \onelevel@sanitize\HyColor@model@empty

```

```

174 \def\HyColor@model@gray{gray}
175 @onelvel@sanitize\HyColor@model@gray
176 \def\HyColor@model@rgb{rgb}
177 @onelvel@sanitize\HyColor@model@rgb
178 \def\HyColor@model@cmyk{cmyk}
179 @onelvel@sanitize\HyColor@model@cmyk
180 \def\HyColor@model@Gray{Gray}
181 @onelvel@sanitize\HyColor@model@Gray

```

2.5 Package `hyperref`

2.5.1 Options `Hyp.*color`

```

182 \def\HyColor@UseColor#1{%
183   \ifx#1\relax
184   \else
185     \ifx#1\empty
186     \else
187       \expandafter\HyColor@@UseColor#1\@nil
188     \fi
189   \fi
190 }
191 \def\HyColor@@UseColor{%
192   \@ifnextchar[\HyColor@@@UseColor\HyColor@@@@UseColor
193 }
194 \def\HyColor@@@UseColor[#1]#2\@nil{%
195   \color[{#1}]{#2}%
196 }
197 \def\HyColor@@@@UseColor#1\@nil{%
198   \color{#1}%
199 }

```

Procedure `HyperrefColor(value, cmd)`

Param: *value* (value of the option)

Param: *cmd* (macro for result)

```

switch value do
  case empty
    | cmd  $\leftarrow$  no color;
  endsw
  case with model
    | Call \color with model;
  endsw
  case without model
    | Call \color without model;
  endsw
endsw

```

```

200 \def\HyColor@HyperrefColor#1#2{%
201   \HyColor@IfModel{#1}{%
202     \edef#2{{{\HyColor@model}}{\HyColor@values}}%
203   }{%
204     \let#2\HyColor@values
205     \ifx#2\empty
206       \let#2\relax
207     \fi
208   }%
209 }

```


2.5.2 Generic algorithm

Procedure Algorithm X0134(value, cmd, package, option)

```

Param: value (value of the option)
Param: cmd (macro for result)
Param: package (package name for error message)
Param: option (option name for error message)

switch value do
  case empty
    | cmd ← no color;
  endsw
  case with model
    switch model do
      case empty
        | cmd ← "";
      endsw
      case gray, rgb, cmyk
        | cmd ← output();
      endsw
      case Gray
        | if with xcolor then
          |   (model, values) ← convert to gray;
        | else
          |   error(package, option, "Missing xcolor"), cmd ← no color;
        | end
      endsw
      else
        | if with xcolor then
          |   (model, values) ← convert to rgb;
          |   cmd ← output();
        | else
          |   error(package, option, "Missing xcolor"), cmd ← no color;
        | end
      end
    endsw
  endsw
  case rgb values
    | (model, values) ← ("rgb", (r,g,b));
    | cmd ← output();
  endsw
  case without model
    | if with xcolor then
      |   (model, values) ← get model and values(value);
      switch model do
        case gray, rgb, cmyk
          | cmd ← output();
        endsw
        case Gray
          | (model, values) ← convert to gray;
          | cmd ← output();
        endsw
        else
          | (model, values) ← convert to rgb;
          | cmd ← output();
        end
      endsw
    | else
      |   error(package, option, "Missing xcolor"), cmd ← no color;
    | end
  endsw
endsw

```

```

\HyColor@XZeroOneThreeFour
210 \def\HyColor@XZeroOneThreeFour#1#2#3#4{%
211   \HyColor@IfModel{#1}{%
212     \ifx\HyColor@model\HyColor@model@empty
213       \let#2\empty
214     \else\ifx\HyColor@model\HyColor@model@gray
215       \expandafter\HyColor@NormalizeNum
216       \expandafter{\HyColor@values}#2%
217     \else\ifx\HyColor@model\HyColor@model@rgb
218       \expandafter\HyColor@NormalizeCommaRGB\HyColor@values\@nil#2%
219     \else\ifx\HyColor@model\HyColor@model@cmyk
220       \expandafter\HyColor@NormalizeCommaCMYK\HyColor@values\@nil#2%
221     \else\ifx\HyColor@model\HyColor@model@Gray
222       \HyColor@IfXcolor{%
223         \convertcolorspec\HyColor@model\HyColor@values
224         \HyColor@model@gray#2%
225       \expandafter\HyColor@NormalizeNum\expandafter{#2}#2%
226       \let\HyColor@model\HyColor@model@gray
227     }{%
228       \let#2\relax
229       \HyColor@ModelErrorNoXcolor{#3}{#4}%
230     }%
231   \else
232     \HyColor@IfXcolor{%
233       \convertcolorspec\HyColor@model\HyColor@values
234       \HyColor@model@rgb#2%
235     \expandafter\HyColor@NormalizeCommaRGB#2\@nil#2%
236     \let\HyColor@model\HyColor@model@rgb
237   }{%
238     \let#2\relax
239     \HyColor@ModelErrorNoXcolor{#3}{#4}%
240   }%
241   \fi\fi\fi\fi
242 }{%
243   \let#2\HyColor@values
244   \ifx#2\empty
245     \let#2\relax
246   \else
247     \expandafter\HyColor@IfRGB\expandafter{\HyColor@values}{%
248       \expandafter\HyColor@NormalizeCommaRGB\HyColor@values\@nil#2%
249     }{%
250       \HyColor@IfXcolor{%
251         \expandafter\extractcolorspec\expandafter{\HyColor@values}#2%
252         \edef\HyColor@model{\expandafter\@firstoftwo#2}%
253         \edef\HyColor@values{\expandafter\@secondoftwo#2}%
254         \ifx\HyColor@model\HyColor@model@gray
255           \expandafter\HyColor@NormalizeNum\expandafter
256           {\HyColor@values}#2%
257         \else\ifx\HyColor@model\HyColor@model@rgb
258           \expandafter\HyColor@NormalizeCommaRGB
259           \HyColor@values\@nil#2%
260         \else\ifx\HyColor@model\HyColor@model@cmyk
261           \expandafter\HyColor@NormalizeCommaCMYK
262           \HyColor@values\@nil#2%
263         \else\ifx\HyColor@model\HyColor@model@Gray
264           \convertcolorspec\HyColor@model\HyColor@values
265           \HyColor@model@gray#2%
266         \expandafter\HyColor@NormalizeNum\expandafter
267           {\HyColor@values}#2%
268         \let\HyColor@model\HyColor@model@gray
269       \else
270         \convertcolorspec\HyColor@model\HyColor@values

```

```

271           \HyColor@model@rgb#2%
272           \expandafter\HyColor@NormalizeCommaRGB#2\@nil#2%
273           \let\HyColor@model\HyColor@model@rgb
274           \fi\fi\fi\fi
275       }%
276       \let#2\relax
277       \HyColor@ErrorSpecNoXcolor{#3}{#4}%
278   }%
279 }%
280 \fi
281 }%
282 }

```

2.5.3 Field options

```

\HyColor@FieldBColor
283 \let\HyColor@FieldBColor\HyColor@XZeroOneThreeFour

\HyColor@FieldColor
284 \def\HyColor@FieldColor#1#2#3#4{%
285   \let\HyColor@model\@empty
286   \HyColor@XZeroOneThreeFour{#1}{#2}{#3}{#4}%
287   \ifx#2\relax
288     \let#2\@empty
289   \else
290     \ifx#2\@empty
291     \else
292       \ifx\HyColor@model\HyColor@model@gray
293         \edef#2{\#2 g}%
294       \else\ifx\HyColor@model\HyColor@model@rgb
295         \edef#2{\#2 rg}%
296       \else\ifx\HyColor@model\HyColor@model@cmyk
297         \edef#2{\#2 k}%
298       \else
299         \PackageError{#3}{Internal error: unsupported color model}\@ehc
300       \fi\fi\fi
301   \fi
302 \fi
303 }

```

2.5.4 Detection for naked RGB values

```

\HyColor@IfRGB
304 \newif\ifHyColor@result
305 \begingroup\expandafter\expandafter\expandafter\endgroup
306 \expandafter\ifx\csname pdfmatch\endcsname\relax
307   \expandafter\@firstoftwo
308 \else
309   \expandafter\@secondoftwo
310 \fi
311 }%
312 \begingroup
313   \def\x#1{\endgroup
314   \def\HyColor@IfRGB##1{%
315     \HyColor@IfRGB##1#1#1\@nil
316   }%
317 }%
318 \x{ }%
319 \edef\HyColor@TwoSpaces{\space\space}%
320 \def\HyColor@IfRGB#1 #2 #3 #4\@nil{%
321   \HyColor@resulttrue
322   \def\HyColor@temp{#4}%

```

```

323      \ifx\HyColor@temp\HyColor@TwoSpaces
324          \HyColor@CheckNum{#1}%
325      \ifHyColor@result
326          \HyColor@CheckNum{#2}%
327      \ifHyColor@result
328          \HyColor@CheckNum{#3}%
329      \fi
330  \fi
331 \else
332     \HyColor@resultfalse
333 \fi
334 \ifHyColor@result
335     \let\HyColor@model\HyColor@model@rgb
336     \edef\HyColor@values{#1,#2,#3}%
337     \expandafter\@firstoftwo
338 \else
339     \expandafter\@secondoftwo
340 \fi
341 }%
342 \def\HyColor@zero{0}%
343 \def\HyColor@one{1}%
344 \def\HyColor@dot{.}%
345 \def\HyColor@CheckNum#1{%
346     \def\HyColor@temp{#1}%
347     \ifx\HyColor@temp\@empty
348         \HyColor@resultfalse
349     \else
350         \edef\HyColor@temp{\@car#1\@nil}%
351         \ifx\HyColor@temp\HyColor@zero
352             \else
353                 \ifx\HyColor@temp\HyColor@one
354                     \else
355                         \ifx\HyColor@temp\HyColor@dot
356                             \else
357                                 \HyColor@resultfalse
358                             \fi
359                         \fi
360                     \fi
361                 \fi
362             \fi
363 }%
364 }%
365 \def\HyColor@MatchNum{%
366     (0*1\string\.0*|0*10+\string\..?[0-9]*|\string\. [0-9]+)%
367 }%
368 \def\HyColor@IfRGB#1{%
369     \ifnum\pdfmatchf^{\HyColor@MatchNum}\space\HyColor@MatchNum
370         \space\HyColor@MatchNum$}{#1}>\z@
371     \let\HyColor@model\HyColor@model@rgb
372     \edef\HyColor@values{%
373         \expandafter\strip@prefix\pdflastmatch1,%
374         \expandafter\strip@prefix\pdflastmatch2,%
375         \expandafter\strip@prefix\pdflastmatch3%
376     }%
377     \HyColor@resulttrue
378     \expandafter\@firstoftwo
379 \else
380     \HyColor@resultfalse
381     \expandafter\@secondoftwo
382 \fi
383 }%
384 }

```

2.5.5 Options *bordercolor

Procedure HyperrefBorderColor(value, cmd, package, option)

Param: *value* (value of the option)
Param: *cmd* (macro for result)
Param: *package, option* (package and option for error message)

```

switch value do
  case empty
    | cmd  $\leftarrow$  no color;
  endsw
  case with model
    | if with xcolor then
      | | (model, values)  $\leftarrow$  convert to rgb;
      | | cmd  $\leftarrow$  output values;
    else
      | | switch model do
        | | | case rgb, gray
          | | | | cmd  $\leftarrow$  output values;
        endsw
        | | | else
          | | | | error(package, option, "Missing xcolor");
          | | | | cmd  $\leftarrow$  no color;
        end
      endsw
    end
  endsw
  case rgb values
    | cmd  $\leftarrow$  output values;
  endsw
  case without model
    | if with xcolor then
      | | (model, values)  $\leftarrow$  convert to rgb;
      | | cmd  $\leftarrow$  output values;
    else
      | | error(package, option, "Missing xcolor"); cmd  $\leftarrow$  no color;
    end
  endsw
endsw
```

\HyColor@HyperrefBorderColor

```

384 \def\HyColor@HyperrefBorderColor#1#2#3#4{%
385   \HyColor@IfModel{#1}{%
386     \HyColor@IfXcolor{%
387       \convertcolorspec\HyColor@model\HyColor@values
388       \HyColor@model@rgb#2%
389       \expandafter\HyColor@NormalizeCommaRGB#2\@nil#2%
390     }{%
391       \ifx\HyColor@model\HyColor@model@rgb
392         \expandafter\HyColor@NormalizeCommaRGB\HyColor@values\@nil#2%
393       \else
394         \ifx\HyColor@model\HyColor@model@gray
395           \expandafter\HyColor@NormalizeNum
396             \expandafter{\HyColor@values}#2%
397             \edef#2{#2 #2 #2}%
398       \else
399         \let#2\relax
400         \HyColor@ModelErrorNoXcolor{#3}{#4}%

```

```

401      \fi
402      \fi
403  }%
404  }{%
405    \let#2\HyColor@values
406    \ifx#2\empty
407      \let#2\relax
408    \else
409      \expandafter\HyColor@IfRGB\expandafter{\HyColor@values}{%
410        \expandafter\HyColor@NormalizeCommaRGB\HyColor@values\@nil#2%
411      }{%
412        \HyColor@IfXcolor{%
413          \extractcolorspec{#1}#2%
414          \expandafter\convertcolorspec#2\HyColor@model@rgb#2%
415          \expandafter\HyColor@NormalizeCommaRGB#2\@nil#2%
416        }{%
417          \let#2\relax
418          \HyColor@ErrorSpecNoXcolor{#3}{#4}%
419        }%
420      }%
421    \fi
422  }%
423 }

```

2.6 Package **attachfile2**

Before PDF-1.7 only RGB values are permitted in annotations. Since PDF-1.7 the color entry in annotations understands several color models, depending on the size of the color array:

- Zero entries: means transparent, not useful for file attachments. AR7/Linux and AR8/Linux show black instead.
- One entry: color model ‘gray’.
- Three entries: color model ‘rgb’.
- Four entries: color model ‘cmyk’.

An empty color specification is interpreted as “no color”.

```
\HyColor@DetectPdfVersion
424 \def\HyColor@DetectPdfVersion{%
425   \begingroup\expandafter\expandafter\expandafter\endgroup
426   \expandafter\ifx\csname Hy@pdfversion\endcsname\relax
427     \global\chardef\HyColor@PdfVersion=0 %
428   \else
429     \global\chardef\HyColor@PdfVersion=\Hy@pdfversion\relax
430   \fi
431   \global\let\HyColor@DetectPdfVersion\relax
432 }
```

```
\HyColor@SpaceToComma
433 \def\HyColor@SpaceToComma#1 #2\@nil{%
434   #1%
435   \ifx\relax#2\relax
436     \expandafter\@gobble
437   \else
438     ,%
439     \expandafter\@firstofone
440   \fi
441 }{%
442   \HyColor@SpaceToComma#2\@nil
}
```

```

443  }%
444 }%


\HyColor@AttachfileColor
445 \def\HyColor@AttachfileColor#1#2#3#4#5#6{%
446   \def#2{#1}%
447   \ifx#2\empty
448     \let#3\gobble
449     \let#4\empty
450   \else
451     \HyColor@resultfalse
452     \HyColor@XZeroOneThreeFour{#1}#3{#5}{#6}%
453     \ifHyColor@result
454       \edef#2{%
455         [rgb]{\expandafter\HyColor@SpaceToComma#3 \@nil}%
456       }%
457     \fi
458     \ifx\HyColor@model\HyColor@model@rgb
459       \edef#4{/C[#3]}% hash-ok
460       \edef#3##1{%
461         #3 %
462         \noexpand\csname atfi@SETRGBCOLOR##1\noexpand\endcsname
463       }%
464     \else
465       \ifx\HyColor@model\HyColor@model@gray
466         \HyColor@DetectPdfVersion
467         \ifnum\HyColor@PdfVersion<7 %
468           \edef#4{/C[#3 #3 #3]}% hash-ok
469         \else
470           \edef#4{/C[#3]}% hash-ok
471         \fi
472         \edef#3##1{%
473           #3 %
474           \noexpand\csname atfi@SETGRAYCOLOR##1\noexpand\endcsname
475         }%
476       \else
477         \ifx\HyColor@model\HyColor@model@cmyk
478           \HyColor@DetectPdfVersion
479           \ifnum\HyColor@PdfVersion<7 %
480             \HyColor@IfModel{#1}{%
481               \HyColor@IfXcolor{%
482                 \convertcolorspec{\HyColor@model\HyColor@values}%
483                 \HyColor@model@rgb#4%
484                 \expandafter\HyColor@NormalizeCommaRGB#4\@nil#4%
485                 \edef#4{/C[#4]}% hash-ok
486               }{%
487                 \let#4\empty
488                 \HyColor@ModelErrorNoXcolor{#5}{#6}%
489               }%
490             }{%
491               \HyColor@IfXcolor{%
492                 \extractcolorspec{#1}#4%
493                 \expandafter\convertcolorspec#4%
494                   \HyColor@model@rgb#4%
495                   \expandafter\HyColor@NormalizeCommaRGB#4\@nil#4%
496                   \edef#4{/C[#4]}% hash-ok
497               }{%
498                 \let#4\empty
499                 \HyColor@ModelErrorSpecNoXcolor{#5}{#6}%
500               }%
501             }%
502           \else
503             \edef#4{/C[#3]}% hash-ok

```

```

504          \fi
505          \edef#3##1{%
506              #3 %
507              \noexpand\csname atfi@SETCMYKCOLOR##1\noexpand\endcsname
508          }%
509      \else
510          \ifx\HyColor@model\HyColor@model@empty
511              \PackageError{#5}{%
512                  Color model `empty' is not permitted for option `#6'%
513              }@\ehc
514              \let#2\@empty
515              \let#3\@gobble
516              \let#4\@empty
517          \else
518              \ifx\HyColor@model\relax % (missing xcolor)
519                  \let#3\@gobble
520                  \let#4\@empty
521              \else
522                  \PackageError{#5}{%
523                      Internal error: unsupported color model%
524                  }@\ehc
525                  \fi
526              \fi
527              \fi
528          \fi
529      \fi
530  \fi
531 }

532 </package>

```

2.7 Patch for package `xcolor`

Because the test files triggered a bug in package `xcolor` of version 2007/01/21 v2.11. I contacted the author of `xcolor` Uwe Kern. He responded with a test version 2007/03/27 v2.12a00 that fixes the problem. However, apparently he did not find the time for an official release yet. Thus I have reluctantly written the following patch package using the fixes of v2.12a00.

The patch is immediately applied if package `xcolor` is already loaded. Otherwise the patch is delayed using `\AfterPackage` if package `scrlfile` is loaded. As last resort `\AtBeginDocument` is used.

```

533 <*xcolor>
534 \NeedsTeXFormat{LaTeX2e}
535 \ProvidesPackage{xcolor-patch}[2011/01/30 xcolor patch]
536 \RequirePackage{hopatch}[2011/01/30]
537 \hopatch@AfterPackage{xcolor}{%

```

```

\XC@ifxcase
538 \long\def\reserved@a#1#2#3{%
539     \long\def\@tmp##1##2{%
540         \ifx#1##1%
541             \toks@{##2}%
542             \expandafter\remove@to@nnil
543         \else
544             \expandafter\@tmp
545         \fi
546     }%
547     \@@tmp#2#1{#3}\@nnil\the\toks@
548 }%
549 \ifx\XC@ifxcase\reserved@a
550     \long\def\XC@ifxcase#1#2#3{%

```

```

551      \long\def\XC@if@##1##2{%
552          \ifx#1##1%
553              \toks@{##2}%
554              \expandafter\remove@to@nnil
555          \else
556              \expandafter\XC@if@
557          \fi
558      }%
559      \XC@if@#2#1{#3}\@nnil
560      \the\toks@
561  }%
562 \fi

\XC@ifcase
563 \long\def\reserved@a#1#2#3{%
564     \long\def\@@tmp##1##2{%
565         \@expandtwoargs\in@{,#1,}{,##1,}%
566         \ifin@
567             \toks@{##2}%
568             \expandafter\remove@to@nnil
569         \else
570             \expandafter\@@tmp
571         \fi
572     }%
573     \@@tmp##1{#3}\@nnil
574     \the\toks@
575 }%
576 \ifx\XC@ifcase\reserved@a
577     \long\def\XC@ifcase#1#2#3{%
578         \long\def\XC@if@##1##2{%
579             \@expandtwoargs\in@{,#1,}{,##1,}%
580             \ifin@
581                 \toks@{##2}%
582                 \expandafter\remove@to@nnil
583             \else
584                 \expandafter\XC@if@
585             \fi
586         }%
587         \XC@if@#2#1{#3}\@nnil
588         \the\toks@
589     }%
590 \fi

\XC@cnv@gray
591 \def\reserved@a#1,{%
592     \XC@ifcase\tmf{%
593         \XC@mod@rgb{%
594             \XC@calcN{#1}\@@tmp
595             \edef\@@tmp{\@@tmp,\@@tmp,\@@tmp}%
596     }%
597         \XC@mod@cmy{%
598             \XC@calcC{#1}\@@tmp
599             \edef\@@tmp{\@@tmp,\@@tmp,\@@tmp}%
600     }%
601         \XC@mod@cmyk{%
602             \XC@calcC{#1}\@@tmp
603             \edef\@@tmp{0,0,0,\@@tmp}%
604     }%
605         \XC@mod@RGB{%
606             \edef\@@sc1{\rangeRGB}%
607             \XC@calcM{#1}\@@tmp
608             \edef\@@tmp{\@@tmp,\@@tmp,\@@tmp}%
609     }%

```

```

610      \XC@mod@HTML{%
611          \edef\@@scl{\@cclv}%
612          \XC@calcM{#1}\@@tmp
613          \XC@calcH\@@tmp\@@tmp
614          \edef\@@tmp{\@@tmp\@@tmp\@@tmp\@@tmp}%
615      }%
616      \XC@mod@HSB{%
617          \edef\@@scl{\rangeHSB}%
618          \XC@calcM{#1}\@@tmp
619          \edef\@@tmp{0,0,\@@tmp}%
620      }%
621      \XC@mod@Gray{%
622          \edef\@@scl{\rangeGray}%
623          \XC@calcM{#1}\@@tmp
624      }%
625  }%
626  {%
627      \XC@calcN{#1}\@@tmp
628      \edef\@@tmp{0,0,\@@tmp}%
629  }%
630 }%
631 \ifx\XC@cnv@gray\reserved@a
632     \def\XC@cnv@gray#1,{%
633         \XC@ifxcase\tm{%
634             \XC@mod@rgb{%
635                 \XC@calcN{#1}\@@tmp
636                 \edef\@@tmp{\@@tmp,\@@tmp,\@@tmp}%
637             }%
638             \XC@mod@gray{}%
639             \XC@mod@cmy{%
640                 \XC@calcC{#1}\@@tmp
641                 \edef\@@tmp{\@@tmp,\@@tmp,\@@tmp}%
642             }%
643             \XC@mod@cmyk{%
644                 \XC@calcC{#1}\@@tmp
645                 \edef\@@tmp{0,0,0,\@@tmp}%
646             }%
647             \XC@mod@RGB{%
648                 \edef\@@scl{\rangeRGB}%
649                 \XC@calcM{#1}\@@tmp
650                 \edef\@@tmp{\@@tmp,\@@tmp,\@@tmp}%
651             }%
652             \XC@mod@HTML{%
653                 \edef\@@scl{\@cclv}%
654                 \XC@calcM{#1}\@@tmp
655                 \XC@calcH\@@tmp\@@tmp
656                 \edef\@@tmp{\@@tmp\@@tmp\@@tmp\@@tmp}%
657             }%
658             \XC@mod@HSB{%
659                 \edef\@@scl{\rangeHSB}%
660                 \XC@calcM{#1}\@@tmp
661                 \edef\@@tmp{0,0,\@@tmp}%
662             }%
663             \XC@mod@Gray{%
664                 \edef\@@scl{\rangeGray}%
665                 \XC@calcM{#1}\@@tmp
666             }%
667         }%
668     }%
669     \XC@calcN{#1}\@@tmp
670     \edef\@@tmp{0,0,\@@tmp}%
671 }%

```

```

672     }%
673 \fi

```

2.7.1 Fix fragile \framebx

\fbox becomes fragile, because the internal \framebx is redefined by package xcolor. The redefinition is no longer robust. Test file:

```

\documentclass{article}
\usepackage{xcolor}
\makeatletter
\protected@edef\x{\fbox{abc}}
\@end

674 \@ifundefined{XC@framebx }{%
675   \expandafter\let\csname XC@framebx \endcsname\XC@framebx
676   \edef\XC@framebx{%
677     \noexpand\protect
678     \expandafter\noexpand\csname XC@framebx \endcsname
679   }%
680   \expandafter\ifx\csname XC@framebx \endcsname\@framebx
681   \let\@framebx\XC@framebx
682   \fi
683 }{}%
684 }

685 
```

3 Test

```

686 <*test1>
687 \ProvidesFile{hycolor-test1.tex}[2011/01/30 test file 1]
688 </test1>
689 <*test2>
690 \ProvidesFile{hycolor-test2.tex}[2011/01/30 test file 2]
691 \let\pdfmatch\relax
692 </test2>
693 <test3>\ProvidesFile{hycolor-test3.tex}[2011/01/30 test file 3]
694 <*test>
695 \documentclass{article}
696
697 \usepackage{qstest}
698 \IncludeTests{*}
699 \LogTests{log}{*}{*}
700
701 \makeatletter
702
703 \newcommand*\TestPackageName{test-package}
704 \newcommand*\TestOptionName{test-option}
705
706 \newcommand\Message{ }
707 \def\Message#1{\immediate\write16{#1}}
708
709 \newcommand*\ExpectError[2]{%
710   \begingroup
711     \global\let\saved@errhelp\errhelp
712     \global\let\saved@errmessage\errmessage
713     \let\errhelp\@gobble
714     \def\errmessage##1{%
715       \xdef\@ExpectErrorMessage{##1}%
716     }%

```

```

717  \PackageError\TestPackageName{\#1}\@ehc
718  \def\errhelp##1{%
719    \global\let\errhelp\saved@errhelp
720  }%
721  \global\let\@ResultErrorMessage\@empty
722  \def\errmessage##1{%
723    \xdef\@ResultErrorMessage{\#1}%
724    \global\let\errmessage\saved@errmessage
725    % \Message{[ ##1]}%
726    % \Message[] (ignored error)%
727    % \Message[]%
728  }%
729  #2%
730  \endgroup
731  \Expect*{\@ResultErrorMessage}*{\@ExpectErrorMessage}%
732 }
733 \usepackage{scrlfile}
734 \usepackage{hycolor}[2011/01/30]
735 </test>
736 {*test1}
737 \begin{qstest}{NumNormalize}{num, normalize}
738  \def\test#1#2{%
739    \HyColor@NormalizeNum{\#1}\cmd
740    \Expect*{\cmd}{#2}%
741  }%
742  \test{0}{0}%
743  \test{000}{0}%
744  \test{-1}{0}%
745  \test{ 0 }{0}%
746  \test{1.1}{1}%
747  \test{100}{1}%
748  \test{00100}{1}%
749  \test{99.99}{1}%
750  \test{0.0}{0}%
751  \test{00.00}{0}%
752  \test{0. }{0}%
753  \test{.0}{0}%
754  \test{0.1}{.1}%
755  \test{0.10}{.1}%
756  \test{0.1000}{.1}%
757  \test{.1000}{.1}%
758  \test{0.01}{.01}%
759  \test{0.01010}{.0101}%
760  \test{.0000000001}{.0000000001}%
761  \test{.9999999999}{.9999999999}%
762 \end{qstest}
763
764 \begin{qstest}{BookmarkColor without xcolor}{bookmark, noxcolor}
765  \def\test#1#2{%
766    \HyColor@BookmarkColor{\#1}\cmd\TestPackageName\TestOptionName
767    \Expect*{\cmd}{#2}%
768  }%
769  \test{[rgb]{1,0,0}}{1 0 0}%
770  \test{[gray]{0.10}}{.1 .1 .1}%
771  \test{}{}%
772  \test{[rgb]{ 1 , 1 , 0 }}{1 1 0}%
773  \def\errortest[#1]#2{%
774    \ExpectError{%
775      Color model `#1' is not supported\MessageBreak
776      without package `xcolor' in\MessageBreak
777      `TestOptionName=[#1]{#2}'% hash-ok
778    }{%

```

```

779      \test{[#1]{#2}}{}% hash-ok
780      }%
781  }%
782  \errortest[cmyk]{1,0,0,0}%
783  \errortest[empty]{}%
784  \def\errortest#1{%
785      \ExpectError{%
786          This color specification is not supported\MessageBreak
787          without package `xcolor' in\MessageBreak
788          `TestOptionName=#1'%
789      }{%
790          \test{[#1]}{}%
791      }%
792  }%
793 \end{qstest}
794 
```

$$/test1$$

```

795 {*test1 j test2}
796 \begin{qstest}{X0134 without xcolor}{X0134, noxcolor}
797     \def\test#1#2{%
798         \HyColor@XZeroOneThreeFour{#1}\cmd\TestPackageName\TestOptionName
799         \Expect*{\cmd}{#2}%
800     }%
801     \test{[empty]}{}{}%
802     \test{[rgb]{1,0,0}}{1 0 0}%
803     \test{[gray]{0.10}}{.1}%
804     \test{[cmyk]{0,1,0,0}}{0 1 0 0}%
805     \test{[rgb]{ 1 , 1 , 0 }}{1 1 0}%
806     \def\errortest[#1]{%
807         \ExpectError{%
808             Color model `#1' is not supported\MessageBreak
809             without package `xcolor' in\MessageBreak
810             `test-option=[#1]{#2}'% hash-ok
811         }{%
812             \HyColor@XZeroOneThreeFour{[#1]{#2}}\cmd
813                 \TestPackageName\TestOptionName
814             \Expect{true}*{\ifx\cmd\relax true\else false\fi}%
815         }%
816     }%
817     \errortest[Gray]{10}%
818     \errortest[cmy]{1,0,0}%
819     \def\errortest#1{%
820         \ExpectError{%
821             This color specification is not supported\MessageBreak
822             without package `xcolor' in\MessageBreak
823             `test-option=#1'%
824         }{%
825             \HyColor@XZeroOneThreeFour{#1}\cmd\TestPackageName\TestOptionName
826             \Expect{true}*{\ifx\cmd\relax true\else false\fi}%
827         }%
828     }%
829     \errortest{yellow}%
830 \end{qstest}
831
832 \begin{qstest}{HyperrefBorderColor without xcolor}%
833     {hyperef bordercolor, noxcolor}%
834     \def\test#1#2{%
835         \HyColor@HyperrefBorderColor{#1}\cmd\TestPackageName\TestOptionName
836         \Expect*{\cmd}{#2}%
837     }%
838     \test{[rgb]{1,0,0}}{1 0 0}%
839     \test{[gray]{0.10}}{.1 .1 .1}%
840     \test{[rgb]{ 1 , 1 , 0 }}{1 1 0}%

```

```

841 \def\errortest[#1]#2{%
842   \ExpectError{%
843     Color model '#1' is not supported\MessageBreak
844     without package `xcolor' in\MessageBreak
845     `test-option=[#1]{#2}'% hash-ok
846   }{%
847     \HyColor@HyperrefBorderColor{[#1]{#2}}\cmd
848       \TestPackageName\TestOptionName
849     \Expect{true}*{\ifx\cmd\relax true\else false\fi}%
850   }%
851 }%
852 \errortest[Gray]{10}%
853 \errortest[cmy]{1,0,0}%
854 \errortest[cmyk]{0,1,0,0}%
855 \def\errortest#1{%
856   \ExpectError{%
857     This color specification is not supported\MessageBreak
858     without package `xcolor' in\MessageBreak
859     `test-option=#1'%
860   }{%
861     \HyColor@HyperrefBorderColor{#1}\cmd
862       \TestPackageName\TestOptionName
863     \Expect{true}*{\ifx\cmd\relax true\else false\fi}%
864   }%
865 }%
866 \errortest{yellow}%
867 \end{qstest}
868 </test1 j test2>
869 <*test1 j test2>
870 \usepackage{xcolor}
871 \definecolor[named]{MyGreen}{rgb}{0,0.7,0}
872 \definecolor{mygreen}{named}{MyGreen}
873 </test1 j test2>
874 <*test1>
875 \begin{qstest}{BookmarkColor with xcolor}{bookmark, xcolor}
876 \def\test#1#2{%
877   \HyColor@BookmarkColor{#1}\cmd\PackageName\OptionName
878   \Expect*{\cmd}{#2}%
879 }%
880 \test{[rgb]{1,0,0}}{1 0 0}%
881 \test{[gray]{0.10}}{.1 .1 .1}%
882 \test{}{}%
883 \test{[rgb]{ 1 , 1 , 0 }}{1 1 0}%
884 \test{[cmyk]{1,0,0,0}}{0 1 1}%
885 \test{[red]{1 0 0}}%
886 \test{[cyan]{0 1 1}}%
887 \test{[red!40!blue]{.4 0 .6}}%
888 \test{[Gray]{10}}{.66667 .66667 .66667}%
889 \test{[RGB]{100,200,50}}{.39217 .78432 .19609}%
890 \test{[wave]{363}}{.00316 0 .00316}%
891 \test{[wave]{814}}{.00797 0 0}%
892 \test{[HSB]{100,200,50}}{.03473 .20833 .12152}%
893 \test{[HTML]{A800FF}}{.65881 0 1}%
894 \test{[cmy]{.3,.5,.2}}{.7 .5 .8}%
895 \test{[cmyk]{.3,.5,.2,.1}}{.6 .4 .7}%
896 \test{[hsb]{.3,.5,.2}}{.12 .2 .1}%
897 \test{[Hsb]{120,.5,.2}}{.1 .2 .1}%
898 \test{[tHsb]{120,.5,.2}}{.2 .2 .1}%
899 \test{[named]{MyGreen}}{0 .7 0}%
900 \test{[mygreen]}{0 .7 0}%
901 \end{qstest}
902

```

```

903 \begin{qstest}{HyperrefColor}{hyperref, color}
904   \def\test#1#2{%
905     \HyColor@HyperrefColor{#1}\cmd
906     \Expect*\{\cmd\}{#2}%
907   }%
908   \test{red}{red}%
909   \test{[rgb]{1,0,0}}{[rgb]{1,0,0}}%
910   \HyColor@HyperrefColor{}{\cmd}
911   \Expect{true}*{\ifx\cmd\relax true\else false\fi}%
912 \end{qstest}
913 </test1>
914 <*test1 j test2>
915 \begin{qstest}{X0134 with xcolor}{hyperref, X0134, xcolor}
916   \def\test#1#2{%
917     \HyColor@XZeroOneThreeFour{#1}\cmd\PackageName\OptionName
918     \Expect*\{\cmd\}{#2}%
919   }%
920   \test{}{}%
921   \test{[gray]{0.1}}{.1}%
922   \test{[rgb]{1,0.5,0.0}}{1 .5 0}%
923   \test{[cmyk]{0,1,0,0.5}}{0 1 0 .5}%
924   \test{[Gray]{10}}{.66667}%
925   \test{red}{1 0 0}%
926   \test{1 0 0}{1 0 0}%
927   \test{001.0 .23 0}{1 .23 0}%
928   \test{[named]{MyGreen}}{0 .7 0}%
929   \test{mygreen}{0 .7 0}%
930   \HyColor@XZeroOneThreeFour{}{\cmd\PackageName\OptionName
931   \Expect{true}*{\ifx\cmd\relax true\else false\fi}%
932 \end{qstest}
933
934 \begin{qstest}{FieldColor}{hyperref, field, FieldColor}
935   \def\test#1#2{%
936     \HyColor@FieldColor{#1}\cmd\PackageName\OptionName
937     \Expect*\{\cmd\}{#2}%
938   }%
939   \test{}{}%
940   \test{[gray]{0.7}}{.7 g}%
941   \test{[rgb]{1,0,0}}{1 0 0 rg}%
942   \test{[cmyk]{0,1,0,0}}{0 1 0 0 k}%
943   \test{[cmy]{.5,.4,.3}}{.5 .6 .7 rg}%
944 \end{qstest}
945 </test1 j test2>

```

3.1 Test for package **attachfile2**

```

946 <*test3>
947 \def\atfi@SETRGBCOLORtest{set-rgb}
948 \def\atfi@SETGRAYCOLORtest{set-gray}
949 \def\atfi@SETCMYKCOLORtest{set-cmyk}
950 \def\Test#1#2#3#4#5{%
951   \begingroup
952     \setbox0=\hbox{%
953       \begingroup
954         \chardef\HyColor@PdfVersion=6 %
955         \HyColor@AttachfileColor{#1}\spec\inlinemacro\annot
956         \TestPackageName\TestOptionName
957         \edef\inline{\inlinemacro{test}}%
958         \expandafter\Expect\expandafter{\spec}{#2}%
959         \expandafter\Expect\expandafter{\inline}{#3}%
960         \expandafter\Expect\expandafter{\annot}{#4}%
961     \endgroup
962     \begingroup

```

```

963      \chardef\HyColor@PdfVersion=7 %
964      \HyColor@AttachfileColor{#1}\spec\inlinemacro\annot
965          \TestPackageName\TestOptionName
966          \edef\inline{\inlinemacro{test}}%
967          \expandafter\Expect\expandafter{\spec}{#2}%
968          \expandafter\Expect\expandafter{\inline}{#3}%
969          \expandafter\Expect\expandafter{\annot}{#5}%
970      \endgroup
971  }%
972  \Expect*\the\wd0}{0.0pt}%
973 \endgroup
974 }
975 \newif\ifError
976 \def\TestError[#1]{#2#3#4#5#6}%
977 \begingroup
978     \global\Errorfalse
979     \let\OrgPackageError\PackageError
980     \def\PackageError##1##2##3{%
981         \edef\TestTemp{##1}%
982         \ifx\TestTemp\TestPackageName
983             \Expect*\ifError too many errors\else ok\fi}{ok}%
984             \Expect*{#6}{##2}%
985             \global\Errortrue
986         \else
987             \OrgPackageError##1##2##3}%
988         \fi
989     }%
990 \setbox0=\hbox{%
991     \begingroup
992         \chardef\HyColor@PdfVersion=#1 %
993         \HyColor@AttachfileColor{#2}\spec\inlinemacro\annot
994             \TestPackageName\TestOptionName
995             \edef\inline{\inlinemacro{test}}%
996             \expandafter\Expect\expandafter{\spec}{#3}%
997             \expandafter\Expect\expandafter{\inline}{#4}%
998             \expandafter\Expect\expandafter{\annot}{#5}%
999     \endgroup
1000     \ifx\#6\%
1001     \else
1002         \Expect*\ifError ok\else missing error\fi}{ok}%
1003     \fi
1004 }%
1005     \Expect*\the\wd0}{0.0pt}%
1006 \endgroup
1007 }
1008 \def\NoEmptyModel{%
1009     Color model `empty' is not permitted for option `\\TestOptionName'%
1010 }
1011 \def\ModelNoXcolor#1#2{%
1012     Color model `#1' is not supported\MessageBreak
1013     without package `xcolor' in\MessageBreak
1014     `\\TestOptionName=[#1]{#2}'% hash-ok
1015 }
1016 \def\SpecNoXColor#1{%
1017     This color specification is not supported\MessageBreak
1018     without package `xcolor' in\MessageBreak
1019     `test-option=#1'%
1020 }
1021 \begin{qstest}{AttachfileColor}{AttachfileColor}
1022     \Test{}{}{}{}{}%
1023     \Test{0.1 0.2 0.3}{[rgb]{.1,.2,.3}}{.1 .2 .3 set-rgb}%
1024         {/C [.1 .2 .3] {/C [.1 .2 .3]}%
```

```

1025 \Test{[gray]{0.4}}{[gray]{0.4}}{.4 set-gray}%
1026     {/C [.4 .4 .4]}{/C [.4]}%
1027 \Test{[rgb]{0.3,.2,.1}}{[rgb]{0.3,.2,.1}}{.3 .2 .1 set-rgb}%
1028     {/C [.3 .2 .1]}{/C [.3 .2 .1]}%
1029 \Test{0.0 1.0 1}{[rgb]{0,1,1}}{0 1 1 set-rgb}%
1030     {/C [0 1 1]}{/C [0 1 1]}%
1031 \Test{[gray]1}{[gray]1}{1 set-gray}{/C [1 1 1]}{/C [1]}%
1032 \TestError[6]{[empty]{}{}{}{}{}{}{\NoEmptyModel}}
1033 \TestError[7]{[empty]{}{}{}{}{}{}{\NoEmptyModel}}
1034 \TestError[6]{[cmyk]{.1,.2,.3,.4}}{[cmyk]{.1,.2,.3,.4}}%
1035     {.1 .2 .3 .4 set-cmyk}{}%
1036     {\ModelNoXcolor{cmyk}{.1,.2,.3,.4}}%
1037 \TestError[7]{[cmyk]{.1,.2,.3,.4}}{[cmyk]{.1,.2,.3,.4}}%
1038     {.1 .2 .3 .4 set-cmyk}{/C [.1 .2 .3 .4]}{}%
1039 \TestError[6]{red}{red}{}{\SpecNoXColor{red}}%
1040 \TestError[7]{red}{red}{}{\SpecNoXColor{red}}%
1041 \end{qstest}

1042 \usepackage{xcolor}
1043 \definecolor[named]{MyGreen}{rgb}{0,0.7,0}
1044 \definecolor{mygreen}{named}{MyGreen}
1045 \definecolor{graynine}{gray}{0.9}
1046 \definecolor{GraySix}{Gray}{9}

1047 \begin{qstest}{AttachfileColorX}{AttachfileColorX}
1048 \Test{}{}{}{}{}%
1049 \Test{0.1 0.2 0.3}{[rgb]{.1,.2,.3}}{.1 .2 .3 set-rgb}%
1050     {/C [.1 .2 .3]}{/C [.1 .2 .3]}%
1051 \Test{[gray]{0.4}}{[gray]{0.4}}{.4 set-gray}%
1052     {/C [.4 .4 .4]}{/C [.4]}%
1053 \Test{[rgb]{0.3,.2,.1}}{[rgb]{0.3,.2,.1}}{.3 .2 .1 set-rgb}%
1054     {/C [.3 .2 .1]}{/C [.3 .2 .1]}%
1055 \Test{0.0 1.0 1}{[rgb]{0,1,1}}{0 1 1 set-rgb}%
1056     {/C [0 1 1]}{/C [0 1 1]}%
1057 \Test{[gray]1}{[gray]1}{1 set-gray}{/C [1 1 1]}{/C [1]}%
1058 \Test{red}{red}{1 0 0 set-rgb}{/C [1 0 0]}{/C [1 0 0]}%
1059 \Test{black}{black}{0 set-gray}{/C [0 0 0]}{/C [0]}%
1060 \Test{cyan}{cyan}{1 0 0 0 set-cmyk}{/C [0 1 1]}{/C [1 0 0 0]}%
1061 \Test{[named]{black}}{[named]{black}}{0 0 0 set-rgb}%
1062     {/C [0 0 0]}{/C [0 0 0]}%
1063 \Test{[Gray]{9}}{[Gray]{9}}{.6 set-gray}{/C [.6 .6 .6]}{/C [.6]}%
1064 \Test{[HTML]{0080FF}}{[HTML]{0080FF}}{0 .50195 1 set-rgb}%
1065     {/C [0 .50195 1]}{/C [0 .50195 1]}%
1066 \Test{graynine}{graynine}{.9 set-gray}{/C [.9 .9 .9]}{/C [.9]}%
1067 \Test{GraySix}{GraySix}{.6 set-gray}{/C [.6 .6 .6]}{/C [.6]}%
1068 \Test{wave}{500}{wave}{500}{0 1 .49846 set-rgb}%
1069     {/C [0 1 .49846]}{/C [0 1 .49846]}%
1070 \TestError[6]{[empty]{}{}{}{}{}{}{\NoEmptyModel}}
1071 \TestError[7]{[empty]{}{}{}{}{}{}{\NoEmptyModel}}
1072 \end{qstest}

1073 </test3>
1074 <*test>
1075 \begin{document}
1076 \end{document}
1077 </test>

```

3.2 Test for package **xcolor**

```

1078 <*test-xcolor>
1079 \NeedsTeXFormat{LaTeX2e}
1080 \nofiles
1081 \documentclass{minimal}
1082 <*xcol1>
1083 \usepackage{xcolor}

```

```

1084 \usepackage{xcolor-patch}[2011/01/30]
1085 </xcol1>
1086 <*xcol2>
1087 \usepackage{scrlfile}
1088 \usepackage{xcolor-patch}[2011/01/30]
1089 \usepackage{xcolor}
1090 </xcol2>
1091 <*xcol3>
1092 \usepackage{xcolor-patch}[2011/01/30]
1093 \usepackage{xcolor}
1094 \begin{document}
1095 </xcol3>
1096 \makeatletter
1097 \newcommand*\ColModList{%
1098   rgb,%
1099   cmy,%
1100   cmyk,%
1101   hsb,%
1102   Hsb,%
1103   tHsb,%
1104   gray,%
1105   RGB,%
1106   HTML,%
1107   HSB,%
1108   Gray,%
1109   % wave,
1110 }
1111 \newcommand*\StartModel{rgb}
1112 \newcommand*\StartValues{.1,.2,.3}
1113 @for\x:=\ColModList\do{%
1114   \ifx\x\empty
1115   \else
1116     \convertcolorspec\StartModel\StartValues\x\y
1117     \typeout{* [\StartModel]{\StartValues} ==> [\x]{\y}}%
1118   @for\xx:=\ColModList\do{%
1119     \ifx\xx\empty
1120     \else
1121       \convertcolorspec\x\y\xx\yy
1122       \typeout{* [\x]{\y} ==> [\xx]{\yy}}%
1123     \fi
1124   }%
1125   \fi
1126 }
1127 <xcol3>\end{document}
1128 <xcol1 j xcol2> @@
1129 </test-xcolor>

```

3.2.1 Test for \@frameb@x/\fbox

```

1130 <*test-xcolor-fbox>
1131 \NeedsTeXFormat{LaTeX2e}
1132 \documentclass{article}
1133 \usepackage{xcolor}
1134 \usepackage{xcolor-patch}[2011/01/30]
1135 \makeatletter
1136 \protected@edef\x{\fbox{abc}}
1137 \let\@tempa\@undefined
1138 \protected@edef\x{\fbox{abc}}
1139 \makeatother
1140 \begin{document}
1141 \MakeUppercase{\fbox{abc}}
1142 \end{document}
1143 </test-xcolor-fbox>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

<CTAN:macros/latex/contrib/oberdiek/hycolor.dtx> The source file.

<CTAN:macros/latex/contrib/oberdiek/hycolor.pdf> Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

<CTAN:install/macros/latex/contrib/oberdiek.tds.zip>

TDS refers to the standard “A Directory Structure for TeX Files” (<CTAN:tds/tds.pdf>). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDSScripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain TeX:

```
tex hycolor.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>hycolor.sty</code>	→ <code>tex/latex/oberdiek/hycolor.sty</code>
<code>xcolor-patch.sty</code>	→ <code>tex/latex/oberdiek/xcolor-patch.sty</code>
<code>hycolor.pdf</code>	→ <code>doc/latex/oberdiek/hycolor.pdf</code>
<code>test/hycolor-test1.tex</code>	→ <code>doc/latex/oberdiek/test/hycolor-test1.tex</code>
<code>test/hycolor-test2.tex</code>	→ <code>doc/latex/oberdiek/test/hycolor-test2.tex</code>
<code>test/hycolor-test3.tex</code>	→ <code>doc/latex/oberdiek/test/hycolor-test3.tex</code>
<code>test/hycolor-test-xcol1.tex</code>	→ <code>doc/latex/oberdiek/test/hycolor-test-xcol1.tex</code>
<code>test/hycolor-test-xcol2.tex</code>	→ <code>doc/latex/oberdiek/test/hycolor-test-xcol2.tex</code>
<code>test/hycolor-test-xcol3.tex</code>	→ <code>doc/latex/oberdiek/test/hycolor-test-xcol3.tex</code>
<code>test/hycolor-test-xcol4.tex</code>	→ <code>doc/latex/oberdiek/test/hycolor-test-xcol4.tex</code>
<code>hycolor.dtx</code>	→ <code>source/latex/oberdiek/hycolor.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

¹<ftp://ftp.ctan.org/tex-archive/>

4.4 Refresh file name databases

If your \TeX distribution (teTeX , mikTeX , ...) relies on file name databases, you must refresh these. For example, teTeX users run `texhash` or `mktexlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk hycolor.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain \TeX : Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{hycolor.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex hycolor.dtx
makeindex -s gind.ist hycolor.idx
pdflatex hycolor.dtx
makeindex -s gind.ist hycolor.idx
pdflatex hycolor.dtx
```

5 Catalogue

The following XML file can be used as source for the [TeX Catalogue](#). The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `hycolor.xml`.

```
1144 <catalogue>
1145 <?xml version='1.0' encoding='us-ascii'?>
1146 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
1147 <entry datestamp='$Date$' modifier='$Author$' id='hycolor'>
1148   <name>hycolor</name>
1149   <caption>Implements colour for packages hyperref and bookmark.</caption>
1150   <authorref id='auth:oberdiek' />
1151   <copyright owner='Heiko Oberdiek' year='2007-2011' />
1152   <license type='lppl1.3' />
1153   <version number='1.7' />
1154   <description>
1155     This package provides the code for the color option
1156     that is used by packages <xref refid='hyperref'>hyperref</xref>
1157     and <xref refid='bookmark'>bookmark</xref>.
1158     It is not intended as package for the user.
1159   <p/>
```

```

1160      The package is part of the <xref refid='oberdiek'>oberdiek</xref> bundle.
1161  </description>
1162  <documentation details='Package documentation'
1163      href='ctan:/macros/latex/contrib/oberdiek/hycolor.pdf'/
1164  <ctan file='true' path='/macros/latex/contrib/oberdiek/hycolor.dtx'/
1165  <miktex location='oberdiek'/
1166  <texlive location='oberdiek'/
1167  <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip'/
1168 </entry>
1169 </catalogue>
```

6 History

[2007/04/09 v1.0]

- First version.

[2007/04/11 v1.1]

- Line ends sanitized.

[2008/07/29 v1.2]

- Support for package `attachfile2` added.

[2008/08/01 v1.3]

- Patch package `xcolor-patch` added that fixes bugs in package `xcolor` to get the test files running.

[2008/09/08 v1.4]

- Fix added to package `xcolor-patch`: Fragile `\@framebox` (used in `\fbox`) is made robust.

[2009/10/02 v1.5]

- Doku fixes (Herbert Voss).

[2009/12/12 v1.6]

- Short info shortened.

[2011/01/30 v1.7]

- Package `xcolor-patch` uses package `hopatch`.

7 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols		
<code>\!</code>	<code>\:</code>	8
<code>\!"</code>	<code>\;</code>	11
<code>\+/-\.</code>	<code>\></code>	13
<code>\+\-\.</code>	<code>\@end</code>	1128
<code>\+\-\.</code>	<code>\@scl</code>	606,
<code>\+\-\.</code>		611, 617, 622, 648, 653, 659, 664

\@tmp 539,
 544, 547, 564, 570, 573, 594,
 595, 598, 599, 602, 603, 607,
 608, 612, 613, 614, 618, 619,
 623, 627, 628, 635, 636, 640,
 641, 644, 645, 649, 650, 654,
 655, 656, 660, 661, 665, 669, 670
\@ExpectErrorMessage 715, 731
\@ResultErrorMessage 721, 723, 731
\@ReturnAfterFi 65, 70, 163
\@car 350
\@cclv 611, 653
\@ehc 136, 143, 299, 513, 524, 717
\@empty ... 40, 50, 51, 111, 118, 125,
 185, 205, 213, 244, 285, 288,
 290, 347, 406, 447, 449, 487,
 498, 514, 516, 520, 721, 1114, 1119
\@expandtwoargs 565, 579
\@firstofone 439
\@firstoftwo 156, 169, 252, 307, 337, 377
\@for 1113, 1118
\@frameb@x 680, 681
\@gobble 436, 448, 515, 519, 713
\@ifnextchar 146, 192
\@ifundefined 674
\@ne 45
\@nil 41, 44, 49,
 54, 61, 66, 78, 86, 101, 104, 123,
 151, 153, 158, 187, 194, 197,
 218, 220, 235, 248, 259, 262,
 272, 315, 320, 350, 389, 392,
 410, 415, 433, 442, 455, 484, 495
\@nnil 547, 559, 573, 587
\@onellevel@sanitize
 ... 32, 173, 175, 177, 179, 181
\@secondoftwo
 ... 161, 167, 253, 309, 339, 380
\@tempa 1137
\@undefined 1137
\\ 46, 62, 1000

A

\annot 955, 960, 964, 969, 993, 998
\atfi@SETCMYKCOLORtest 949
\atfi@SETGRAYCOLORtest 948
\atfi@SETRGBCOLORtest 947

B

\begin 737,
 764, 796, 832, 875, 903, 915,
 934, 1021, 1047, 1075, 1094, 1140

C

\catcode 7, 8, 9, 10, 11, 12, 13
\chardef 427, 429, 954, 963, 992
\cmd 739, 740, 766,
 767, 798, 799, 812, 814, 825,
 826, 835, 836, 847, 849, 861,
 863, 877, 878, 905, 906, 910,
 911, 917, 918, 930, 931, 936, 937
\ColModList 1097, 1113, 1118
\color 195, 198

\convertcolorspec
 ... 99, 122, 223, 233, 264,
 270, 387, 414, 482, 493, 1116, 1121
\csname 26, 166, 306,
 426, 462, 474, 507, 675, 678, 680

D

\definecolor
 ... 871, 872, 1043, 1044, 1045, 1046
\do 1113, 1118
\documentclass 695, 1081, 1132

E

\end 762, 793, 830, 867, 901, 912, 932,
 944, 1041, 1072, 1076, 1127, 1142
\endcsname 26, 166, 306,
 426, 462, 474, 507, 675, 678, 680
\errhelp 711, 713, 718, 719
\errmessage 712, 714, 722, 724
\Errorfalse 978
\errortest 773, 782,
 783, 784, 806, 817, 818, 819,
 829, 841, 852, 853, 854, 855, 866
\Errortrue 985
\Expect 731, 740, 767, 799,
 814, 826, 836, 849, 863, 878,
 906, 911, 918, 931, 937, 958,
 959, 960, 967, 968, 969, 972,
 983, 984, 996, 997, 998, 1002, 1005
\ExpectError
 ... 709, 774, 785, 807, 820, 842, 856
\extractcolorspec 121, 251, 413, 492

F

\fbox 1136, 1138, 1141

H

\hbox 952, 990
\hopatch@AfterPackage 537
\HyColor@pdfversion 429
\HyColor@UseColor 192, 197
\HyColor@UseColor 192, 194
\HyColor@IfRGB 315, 320
\HyColor@UseColor 187, 191
\HyColor@AttachfileColor
 ... 445, 955, 964, 993
\HyColor@BookmarkColor ... 96, 766, 877
\HyColor@CheckDot 41, 44
\HyColor@CheckNum ... 324, 326, 328, 345
\HyColor@DefSanitized ... 6, 154, 155, 160
\HyColor@DetectPdfVersion
 ... 424, 466, 478
\HyColor@dot 344, 355
\HyColor@ModelErrorNoXcolor ...
 ... 112, 131, 229, 239, 400, 488
\HyColor@ErrorSpecNoXcolor ...
 ... 126, 138, 277, 418, 499
\HyColor@FieldBColor 283
\HyColor@FieldColor 284, 936
\HyColor@HyperrefBorderColor ...
 ... 384, 835, 847, 861
\HyColor@HyperrefColor ... 200, 905, 910

\HyColor@IfModel	97, 145, 201, 211, 385, 480	\ifError	975, 983, 1002
\HyColor@IfRGB	247, 304, 409	\ifHyColor@result	304, 325, 327, 334, 453
\HyColor@IfXcolor	98, 120, 164, 222, 232, 250, 386, 412, 481, 491	\ifin@	566, 580
\HyColor@MatchNum	364, 368, 369	\ifnum	45, 368, 467, 479
\HyColor@model	99, 103, 106, 133, 135, 154, 159, 202, 212, 214, 217, 219, 221, 223, 226, 233, 236, 252, 254, 257, 260, 263, 264, 268, 270, 273, 285, 292, 294, 296, 335, 370, 387, 391, 394, 458, 465, 477, 482, 510, 518	\ifx	46, 51, 62, 72, 103, 106, 118, 166, 183, 185, 205, 212, 214, 217, 219, 221, 244, 254, 257, 260, 263, 287, 290, 292, 294, 296, 306, 323, 347, 351, 353, 355, 391, 394, 406, 426, 435, 447, 458, 465, 477, 510, 518, 540, 549, 552, 576, 631, 680, 814, 826, 849, 863, 911, 931, 982, 1000, 1114, 1119
\HyColor@model@cmyk	178, 179, 219, 260, 296, 477	\immediate	707
\HyColor@model@empty	172, 173, 212, 510	\in@	565, 579
\HyColor@model@Gray	180, 181, 221, 263	\IncludeTests	698
\HyColor@model@gray	106, 174, 175, 214, 224, 226, 254, 265, 268, 292, 394, 465	\inline	957, 959, 966, 968, 995, 997
\HyColor@model@rgb	100, 103, 122, 176, 177, 217, 234, 236, 257, 271, 273, 294, 335, 370, 388, 391, 414, 458, 483, 494	\inlinemacro	955, 957, 964, 966, 993, 995
\HyColor@NormalizeCommaCMYK	86, 220, 261	L	
\HyColor@NormalizeCommaRGB	78, 101, 104, 123, 218, 235, 248, 258, 272, 389, 392, 410, 415, 484, 495	\LogTests	699
\HyColor@NormalizeNum	36, 79, 81, 83, 87, 89, 91, 93, 107, 215, 225, 255, 266, 395, 739	M	
\HyColor@one	343, 353	\makeatletter	701, 1096, 1135
\HyColor@PdfVersion	427, 429, 467, 479, 954, 963, 992	\makeatother	1139
\HyColor@resultfalse	332, 348, 357, 379, 451	\MakeUppercase	1141
\HyColor@resulttrue	321, 376	\Message	706, 707, 725, 726, 727
\HyColor@ReverseString	49, 54, 61, 66	\MessageBreak	133, 134, 140, 141, 775, 776, 786, 787, 808, 809, 821, 822, 843, 844, 857, 858, 1012, 1013, 1017, 1018
\HyColor@SpaceToComma	433, 455	\ModelNoXcolor	1011, 1036
\HyColor@StripLeadingZeros	50, 71, 73	N	
\HyColor@temp	79, 80, 81, 82, 83, 84, 87, 88, 89, 90, 91, 92, 93, 94, 322, 323, 346, 347, 350, 351, 353, 355	\NeedsTeXFormat	2, 534, 1079, 1131
\HyColor@TwoSpaces	319, 323	\newcommand	703, 704, 706, 709, 1097, 1111, 1112
\HyColor@UseColor	182	\newif	304, 975
\HyColor@values	99, 104, 108, 117, 135, 142, 155, 160, 202, 204, 216, 218, 220, 223, 233, 243, 247, 248, 251, 253, 256, 259, 262, 264, 267, 270, 336, 371, 387, 392, 396, 405, 409, 410, 482	\NoEmptyModel	1008, 1032, 1033, 1070, 1071
\HyColor@WithModel	147, 153	\nofiles	1080
\HyColor@WithoutModel	149, 158	O	
\HyColor@XZeroOneThreeFour	210, 283, 286, 452, 798, 812, 825, 917, 930	\OptionName	877, 917, 930, 936
\HyColor@zero	342, 351	\OrgPackageError	979, 987
I		P	
\ifdim	37	\PackageError	132, 139, 299, 511, 522, 717, 979, 980
R		\PackageName	877, 917, 930, 936
\rangeGray	622, 664	\pdflastmatch	372, 373, 374
\rangeHSB	617, 659	\pdfmatch	368, 691
\rangeRGB	606, 648	\protect	677
\remove@to@nnil	542, 554, 568, 582	\protected@edef	1136, 1138
\RequirePackage	5, 536	\ProvidesFile	687, 690, 693
\ProvidesPackage	3, 535	\ProvidesPackage	3

\reserved@a	538, 549, 563, 576, 591, 631	\toks@	541,
S		547, 553, 560, 567, 574, 581, 588	
\saved@errhelp	711, 719	\typeout	1117, 1122
\saved@errmessage	712, 724	U	
\setbox	952, 990	\usepackage	697, 733, 734,
\space	319, 368, 369	870, 1042, 1083, 1084, 1087,	
\spec	955, 958, 964, 967, 993, 996	1088, 1089, 1092, 1093, 1133, 1134	
\SpecNoXColor	1016, 1039, 1040	W	
\StartModel	1111, 1116, 1117	\wd	972, 1005
\StartValues	1112, 1116, 1117	\write	707
\strip@prefix	372, 373, 374		
T		X	
\Test	950, 1022, 1023, 1025, 1027, 1029, 1031, 1048, 1049, 1051, 1053, 1055, 1057, 1058, 1059, 1060, 1061, 1063, 1064, 1066, 1067, 1068	\x	14, 28, 31, 35, 313, 318, 1113, 1114, 1116, 1117, 1121, 1122, 1136, 1138
\test	738, 742, 743, 744, 745, 746, 747, 748, 749, 750, 751, 752, 753, 754, 755, 756, 757, 758, 759, 760, 761, 765, 769, 770, 771, 772, 779, 790, 797, 801, 802, 803, 804, 805, 834, 838, 839, 840, 876, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 898, 899, 900, 904, 908, 909, 916, 920, 921, 922, 923, 924, 925, 926, 927, 928, 929, 935, 939, 940, 941, 942, 943	\XC@calcC	598, 602, 640, 644
\TestError	976, 1032, 1033, 1034, 1037, 1039, 1040, 1070, 1071	\XC@calcH	613, 655
\TestOptionName	704, 766, 777, 788, 798, 813, 825, 835, 848, 862, 956, 965, 994, 1009, 1014	\XC@calcM	607, 612, 618, 623, 649, 654, 660, 665
\TestPackageName	.	\XC@calcN	594, 627, 635, 669
	703, 717, 766, 798, 813, 825, 835, 848, 862, 956, 965, 982, 994	\XC@cnv@gray	591
\TestTemp	981, 982	\XC@frameb@x	675, 676, 681
\the	547, 560, 574, 588, 972, 1005	\XC@if@ ...	551, 556, 559, 578, 584, 587
\tm	592, 633	\XC@ifcase	563
		\XC@ifxcase	538, 592, 633
		\XC@mod@cmy	597, 639
		\XC@mod@cmyk	601, 643
		\XC@mod@Gray	621, 663
		\XC@mod@gray	638
		\XC@mod@HSB	616, 658
		\XC@mod@HTML	610, 652
		\XC@mod@RGB	605, 647
		\XC@mod@rgb	593, 634
		\xx	1118, 1119, 1121, 1122
		Y	
		\y	23, 35, 1116, 1117, 1121, 1122
		\yy	1121, 1122
		Z	
		\z@	37, 369
		\zap@space	40