

L^AT_EX: Structured documents for T_EX

unofficial L^AT_EX reference manual
May 2012

<http://home.gna.org/latexrefman>

This document is an unofficial reference manual for L^AT_EX, a document preparation system, version of May 2012.

This manual was originally translated from ‘L^AT_EX.HLP’ v1.0a in the VMS Help Library. The pre-translation version was written by George D. Greenwade of Sam Houston State University. The L^AT_EX 2.09 version was written by Stephen Gilmore. The L^AT_EX2e version was adapted from this by Torsten Martinsen. Karl Berry made further updates and additions, and gratefully acknowledges using *Hypertext Help with L^AT_EX*, by Sheldon Green, and the *L^AT_EX Command Summary* (for L^AT_EX 2.09) by L. Botway and C. Biemesderfer (published by the T_EX Users Group as *T_EXniques* number 10), as reference material (no text was directly copied).

Copyright © 2007, 2008, 2009, 2010, 2011, 2012 Karl Berry.

Copyright © 1988, 1994, 2007 Stephen Gilmore.

Copyright © 1994, 1995, 1996 Torsten Martinsen.

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this manual under the conditions for verbatim copying, provided that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this manual into another language, under the above conditions for modified versions.

Short Contents

L ^A T _E X2e	1
1 About this document	2
2 Overview of L ^A T _E X	3
3 Starting & ending	4
4 Document classes	5
5 Typefaces	7
6 Layout	11
7 Sectioning	14
8 Cross references	15
9 Environments	16
10 Line breaking	36
11 Page breaking	38
12 Footnotes	39
13 Definitions	41
14 Counters	44
15 Lengths	46
16 Making paragraphs	47
17 Math formulas	49
18 Modes	61
19 Page styles	62
20 Spaces	64
21 Boxes	67
22 Special insertions	70
23 Splitting the input	76
24 Front/back matter	77
25 Letters	79
26 Terminal input/output	82
27 Command line	83
A Document templates	84
Concept Index	87
Command Index	92

Table of Contents

L^AT_EX2e	1
1 About this document	2
2 Overview of L^AT_EX	3
3 Starting & ending	4
4 Document classes	5
4.1 Document class options	5
5 Typefaces	7
5.1 Font styles	7
5.2 Font sizes	8
5.3 Low-level font commands	9
6 Layout	11
6.1 <code>\onecolumn</code>	11
6.2 <code>\twocolumn</code>	11
6.3 <code>\flushbottom</code>	12
6.4 <code>\raggedbottom</code>	12
6.5 Page layout parameters	12
7 Sectioning	14
8 Cross references	15
8.1 <code>\label</code>	15
8.2 <code>\pageref{key}</code>	15
8.3 <code>\ref{key}</code>	15
9 Environments	16
9.1 <code>abstract</code>	16
9.2 <code>array</code>	16
9.3 <code>center</code>	17
9.3.1 <code>\centering</code>	17
9.4 <code>description</code>	17
9.5 <code>displaymath</code>	17
9.6 <code>document</code>	18
9.7 <code>enumerate</code>	18

9.8	<code>eqnarray</code>	19
9.9	<code>equation</code>	19
9.10	<code>figure</code>	19
9.11	<code>flushleft</code>	21
9.11.1	<code>\raggedright</code>	21
9.12	<code>flushright</code>	21
9.12.1	<code>\raggedleft</code>	22
9.13	<code>itemize</code>	22
9.14	letter environment: writing letters.....	23
9.15	<code>list</code>	23
9.16	<code>math</code>	24
9.17	<code>minipage</code>	24
9.18	<code>picture</code>	24
9.18.1	<code>\circle</code>	25
9.18.2	<code>\makebox</code>	26
9.18.3	<code>\framebox</code>	26
9.18.4	<code>\dashbox</code>	26
9.18.5	<code>\frame</code>	26
9.18.6	<code>\line</code>	26
9.18.7	<code>\linethickness</code>	27
9.18.8	<code>\thicklines</code>	27
9.18.9	<code>\thinlines</code>	27
9.18.10	<code>\multiput</code>	27
9.18.11	<code>\oval</code>	27
9.18.12	<code>\put</code>	27
9.18.13	<code>\shortstack</code>	28
9.18.14	<code>\vector</code>	28
9.19	<code>quotation</code>	28
9.20	<code>quote</code>	28
9.21	<code>tabbing</code>	28
9.22	<code>table</code>	30
9.23	<code>tabular</code>	30
9.23.1	<code>\multicolumn</code>	32
9.23.2	<code>\cline</code>	32
9.23.3	<code>\hline</code>	32
9.23.4	<code>\vline</code>	33
9.24	<code>thebibliography</code>	33
9.24.1	<code>\bibitem</code>	33
9.24.2	<code>\cite</code>	33
9.24.3	<code>\nocite</code>	33
9.24.4	Using BibTeX.....	34
9.25	<code>theorem</code>	34
9.26	<code>titlepage</code>	34
9.27	<code>verbatim</code>	35
9.27.1	<code>\verb</code>	35
9.28	<code>verse</code>	35

10	Line breaking	36
10.1	<code>\[*][morespace]</code>	36
10.2	<code>\obeycr & \restorecr</code>	36
10.3	<code>\newline</code>	36
10.4	<code>\-</code> (discretionary hyphen)	36
10.5	<code>\fussy</code>	36
10.6	<code>\sloppy</code>	36
10.7	<code>\hyphenation</code>	37
10.8	<code>\linebreak & \nolinebreak</code>	37
11	Page breaking	38
11.1	<code>\cleardoublepage</code>	38
11.2	<code>\clearpage</code>	38
11.3	<code>\newpage</code>	38
11.4	<code>\enlargethispage</code>	38
11.5	<code>\pagebreak & \nepagebreak</code>	38
12	Footnotes	39
12.1	<code>\footnote</code>	39
12.2	<code>\footnotemark</code>	39
12.3	<code>\footnotetext</code>	39
12.4	Symbolic footnotes	39
12.5	Footnote parameters	40
13	Definitions	41
13.1	<code>\newcommand & \renewcommand</code>	41
13.2	<code>\newcounter</code>	41
13.3	<code>\newlength</code>	41
13.4	<code>\newsavebox</code>	42
13.5	<code>\newenvironment & \renewenvironment</code>	42
13.6	<code>\newtheorem</code>	42
13.7	<code>\newfont</code>	43
13.8	<code>\protect</code>	43
14	Counters	44
14.1	<code>\alph \Alph \arabic \roman \Roman \fnsymbol</code> : Printing counters	44
14.2	<code>\usecounter{counter}</code>	44
14.3	<code>\value{counter}</code>	44
14.4	<code>\setcounter{counter}{value}</code>	45
14.5	<code>\addtocounter{counter}{value}</code>	45
14.6	<code>\refstepcounter{counter}</code>	45
14.7	<code>\stepcounter{counter}</code>	45
14.8	<code>\day \month \year</code> : Predefined counters	45

15	Lengths	46
15.1	<code>\setlength{\len}{value}</code>	46
15.2	<code>\addtolength{\len}{amount}</code>	46
15.3	<code>\settodepth</code>	46
15.4	<code>\settoheight</code>	46
15.5	<code>\settowidth{\len}{text}</code>	46
15.6	Predefined lengths	46
16	Making paragraphs	47
16.1	<code>\indent</code>	47
16.2	<code>\noindent</code>	47
16.3	<code>\parskip</code>	47
16.4	Marginal notes	47
17	Math formulas	49
17.1	Subscripts & superscripts	49
17.2	Math symbols	49
17.3	Math functions	57
17.4	Math accents	58
17.5	Spacing in math mode	59
17.6	Math miscellany	59
18	Modes	61
19	Page styles	62
19.1	<code>\maketitle</code>	62
19.2	<code>\pagenumbering</code>	62
19.3	<code>\pagestyle</code>	62
19.4	<code>\thispagestyle{style}</code>	63
20	Spaces	64
20.1	<code>\hspace</code>	64
20.2	<code>\hfill</code>	64
20.3	<code>\SPACE</code>	64
20.4	<code>\@</code>	64
20.5	<code>\thinspace</code>	64
20.6	<code>\/</code>	65
20.7	<code>\hrulefill</code>	65
20.8	<code>\dotfill</code>	65
20.9	<code>\addvspace</code>	65
20.10	<code>\bigskip</code> <code>\medskip</code> <code>\smallskip</code>	65
20.11	<code>\vfill</code>	65
20.12	<code>\vspace[*]{length}</code>	66

21	Boxes	67
21.1	<code>\mbox{<i>text</i>}</code>	67
21.2	<code>\fbox</code> and <code>\framebox</code>	67
21.3	<code>lrbox</code>	67
21.4	<code>\makebox</code>	67
21.5	<code>\parbox</code>	68
21.6	<code>\raisebox</code>	68
21.7	<code>\savebox</code>	68
21.8	<code>\sbox{\boxcmd}{<i>text</i>}</code>	69
21.9	<code>\usebox{\boxcmd}</code>	69
22	Special insertions	70
22.1	Reserved characters	70
22.2	Text symbols	70
22.3	Accents	73
22.4	Non-English characters	74
22.5	<code>\rule</code>	75
22.6	<code>\today</code>	75
23	Splitting the input	76
23.1	<code>\include</code>	76
23.2	<code>\includeonly</code>	76
23.3	<code>\input</code>	76
24	Front/back matter	77
24.1	Tables of contents	77
24.1.1	<code>\addcontentsline</code>	77
24.1.2	<code>\addtocontents</code>	77
24.2	Glossaries	78
24.3	Indexes	78
25	Letters	79
25.1	<code>\address{<i>return-address</i>}</code>	79
25.2	<code>\cc</code>	79
25.3	<code>\closing</code>	79
25.4	<code>\encl</code>	80
25.5	<code>\location</code>	80
25.6	<code>\makelabels</code>	80
25.7	<code>\name</code>	80
25.8	<code>\opening{<i>text</i>}</code>	80
25.9	<code>\ps</code>	80
25.10	<code>\signature{<i>text</i>}</code>	80
25.11	<code>\startbreaks</code>	80
25.12	<code>\stopbreaks</code>	80
25.13	<code>\telephone</code>	81

26	Terminal input/output	82
26.1	<code>\typein[cmd]{msg}</code>	82
26.2	<code>\typeout{msg}</code>	82
27	Command line	83
Appendix A	Document templates	84
A.1	book template	84
A.2	beamer template	84
A.3	tugboat template	85
	Concept Index	87
	Command Index	92

L^AT_EX2e

This document is an unofficial reference manual for L^AT_EX, a document preparation system, version as of May 2012. It is intended to cover L^AT_EX2e, which has been the standard version of L^AT_EX for many years.

1 About this document

The \LaTeX document preparation system is implemented as a macro package for Donald E. Knuth's \TeX typesetting program. \LaTeX was originally created by Leslie Lamport; it is now maintained by a group of volunteers (<http://latex-project.org>). The official documentation written by the \LaTeX project is available from their web site.

The present document is completely unofficial and has not been reviewed by the \LaTeX maintainers. Do not send bug reports or anything else about this document to them. Instead, please send all comments to latexrefman-discuss@gn.org.

The home page for this document is <http://home.gna.org/latexrefman>. That page has links to the current output in various formats, sources, mailing lists, and other infrastructure.

Of course, there are many, many other sources of information about \LaTeX . Here are a few:

<http://www.ctan.org/pkg/latex-doc-ptr>

Two pages of recommended references to \LaTeX documentation.

<http://www.ctan.org/pkg/first-latex-doc>

Writing your first document, with a bit of both text and math.

<http://www.ctan.org/pkg/usrguide>

The guide for document authors maintained as part of \LaTeX ; there are several others.

<http://tug.org/begin.html>

Introduction to the \TeX system, including \LaTeX .

2 Overview of L^AT_EX

What is L^AT_EX?

L^AT_EX typesets a file of text using the T_EX program and the L^AT_EX “macro package” for T_EX. That is, it processes an input file containing the text of a document with interspersed commands that describe how the text should be formatted. L^AT_EX files are plain text that can be written in any reasonable editor. It produces at least three files as output:

1. The main output file, which is one of:

.dvi If invoked as `latex`, a “Device Independent” (‘.dvi’) file is produced. This contains commands that can be translated into commands for virtually any output device. You can view such ‘.dvi’ output of L^AT_EX by using a program such as `xdvi` (display directly), `dvips` (convert to PostScript), or `dvipdfmx` (convert to PDF).

.pdf If invoked as `pdflatex`, a “Portable Document Format” (‘.pdf’) file. Typically, this is a self-contained file, with all fonts and images embedded. This can be very useful, but it does make the output much larger than the ‘.dvi’ produced from the same document.

If invoked as `lualatex`, a ‘.pdf’ file is created using the LuaT_EX engine (<http://luatex.org>).

If invoked as `xelatex`, a ‘.pdf’ file is created using the XeT_EX engine (<http://tug.org/xetex>).

Many other less-common variants of L^AT_EX (and T_EX) exist, which can produce HTML, XML, and other things.

2. The “transcript” or ‘.log’ file that contains summary information and diagnostic messages for any errors discovered in the input file.
3. An “auxiliary” or ‘.aux’ file. This is used by L^AT_EX itself, for things such as cross-references.

An open-ended list of other files might be created. We won’t try to list them all. Xxx components?

In the L^AT_EX input file, a command name starts with a `\`, followed by either (a) a string of letters or (b) a single non-letter. Arguments contained in square brackets, `[]`, are optional while arguments contained in braces, `{}`, are required.

L^AT_EX is case sensitive. Enter all commands in lower case unless explicitly directed to do otherwise.

3 Starting & ending

A minimal input file looks like the following:

```
\documentclass{class}
\begin{document}
your text
\end{document}
```

where the *class* is a valid document class for L^AT_EX. See [Chapter 4 \[Document classes\]](#), [page 5](#), for details of the various document classes available locally.

You may include other L^AT_EX commands between the `\documentclass` and the `\begin{document}` commands (this area is called the *preamble*).

4 Document classes

The class of a given document is defined with the command:

```
\documentclass[options]{class}
```

The `\documentclass` command must be the first command in a \LaTeX source file.

Built-in \LaTeX document *class* names are (many other document classes are available as add-ons; see [Chapter 2 \[Overview\], page 3](#)):

```
article report book letter slides
```

Standard *options* are described below.

4.1 Document class options

You can specify so-called *global options* or *class options* to the `\documentclass` command by enclosing them in square brackets as usual. To specify more than one *option*, separate them with a comma:

```
\documentclass[option1,option2,...]{class}
```

Here is the list of the standard class options.

All of the standard classes except `slides` accept the following options for selecting the typeface size (default is 10pt):

```
10pt 11pt 12pt
```

All of the standard classes accept these options for selecting the paper size (default is `letterpaper`):

```
a4paper a5paper b5paper executivepaper legalpaper letterpaper
```

Miscellaneous other options:

`draft`, `final`

mark/do not mark overfull boxes with a big black box; default is `final`.

`fleqn` Put displayed formulas flush left; default is centered.

`landscape`

Selects landscape format; default is portrait.

`leqno` Put equation numbers on the left side of equations; default is the right side.

`openbib` Use “open” bibliography format.

`titlepage`, `notitlepage`

Specifies whether the title page is separate; default depends on the class.

These options are not available with the slides class:

`onecolumn`

`twocolumn`

Typeset in one or two columns; default is `onecolumn`.

`oneside`

`twoside` Selects one- or two-sided layout; default is `oneside`, except for the `book` class.

The `\evensidemargin` (`\oddsidemargin` parameter determines the distance on even (odd) numbered pages between the left side of the page and the

text's left margin. The defaults vary with the paper size and whether one- or two-side layout is selected. For one-sided printing the text is centered, for two-sided, `\oddsidemargin` is 40% of the difference between `\paperwidth` and `\textwidth`, with `\evensidemargin` the remainder.

`openright`

`openany` Determines if a chapter should start on a right-hand page; default is `openright` for book.

The `slides` class offers the option `clock` for printing the time at the bottom of each note.

Additional packages are loaded like this:

```
\usepackage[options]{pkg}
```

To specify more than one *pkg*, you can separate them with a comma, or use multiple `\usepackage` commands.

Any options given in the `\documentclass` command that are unknown by the selected document class are passed on to the packages loaded with `\usepackage`.

5 Typefaces

Two important aspects of selecting a *font* are specifying a size and a style. The L^AT_EX commands for doing this are described here.

5.1 Font styles

The following type style commands are supported by L^AT_EX.

This first group of commands is typically used like `\textit{italic text}`. The corresponding command in parenthesis is the “declaration form”, which takes no arguments. The scope of the declaration form lasts until the next type style command or the end of the current group.

The declaration forms are cumulative; i.e., you can say either `\sffamily\bfseries` or `\bfseries\sffamily` to get bold sans serif.

You can alternatively use an environment form of the declarations; for instance, `\begin{ttfamily}...\end{ttfamily}`.

These commands automatically supply an italic correction if the

<code>\textrm (\rmfamily)</code>	Roman.
<code>\textit (\itshape)</code>	Italics.
<code>\emph</code>	Emphasis (switches between <code>\textit</code> and <code>\textrm</code>).
<code>\textmd (\mdseries)</code>	Medium weight (default).
<code>\textbf (\bfseries)</code>	Boldface.
<code>\textup (\upshape)</code>	Upright (default). The opposite of slanted.
<code>\textsl (\slshape)</code>	Slanted.
<code>\textsf (\sffamily)</code>	Sans serif.
<code>\textsc (\scshape)</code>	Small caps.
<code>\texttt (\ttfamily)</code>	Typewriter.
<code>\textnormal (\normalfont)</code>	Main document font.
<code>\mathrm</code>	Roman, for use in math mode.
<code>\mathbf</code>	Boldface, for use in math mode.

<code>\mathsf</code>	Sans serif, for use in math mode.
<code>\mathtt</code>	Typewriter, for use in math mode.
<code>\mathit</code> (<code>\mit</code>)	Italics, for use in math mode.
<code>\mathnormal</code>	For use in math mode, e.g. inside another type style declaration.
<code>\mathcal</code>	‘Calligraphic’ letters, for use in math mode.

In addition, the command `\mathversion{bold}` can be used for switching to bold letters and symbols in formulas. `\mathversion{normal}` restores the default.

L^AT_EX also provides these commands, which unconditionally switch to the given style, that is, are *not* cumulative. They are used differently than the above commands, too: `{\cmd ...}` instead of `\cmd{...}`. These are two very different things.

<code>\bf</code>	Switch to bold face .
<code>\cal</code>	Switch to calligraphic letters for math.
<code>\em</code>	Emphasis (italics within roman, roman within italics).
<code>\it</code>	Italics.
<code>\rm</code>	Roman.
<code>\sc</code>	Small caps.
<code>\sf</code>	Sans serif.
<code>\sl</code>	Slanted (oblique).
<code>\tt</code>	Typewriter (monospace, fixed-width).

5.2 Font sizes

The following standard type size commands are supported by L^AT_EX. The table shows the command name and the corresponding actual font size used (in points) with the ‘10pt’, ‘11pt’, and ‘12pt’ document size options, respectively (see [Section 4.1 \[Document class options\]](#), page 5).

Command	10pt	11pt	12pt
<code>\tiny</code>	5	6	6
<code>\scriptsize</code>	7	8	8
<code>\footnotesize</code>	8	9	10
<code>\small</code>	9	10	10.95
<code>\normalsize</code> (default)	10	10.95	12
<code>\large</code>	12	12	14.4
<code>\Large</code>	14.4	14.4	17.28
<code>\LARGE</code>	17.28	17.28	20.74
<code>\huge</code>	20.74	20.74	24.88
<code>\Huge</code>	24.88	24.88	24.88

The commands as listed here are “declaration forms”. The scope of the declaration form lasts until the next type style command or the end of the current group. You can also use the environment form of these commands; for instance, `\begin{tiny}... \end{tiny}`.

5.3 Low-level font commands

These commands are primarily intended for writers of macros and packages. The commands listed here are only a subset of the available ones.

`\fontencoding{enc}`

Select font encoding. Valid encodings include `OT1` and `T1`.

`\fontfamily{family}`

Select font family. Valid families include:

- `cmr` for Computer Modern Roman
- `cmss` for Computer Modern Sans Serif
- `cmtt` for Computer Modern Typewriter

and numerous others.

`\fontseries{series}`

Select font series. Valid series include:

- `m` Medium (normal)
- `b` Bold
- `c` Condensed
- `bc` Bold condensed
- `bx` Bold extended

and various other combinations.

`\fontshape{shape}`

Select font shape. Valid shapes are:

- `n` Upright (normal)
- `it` Italic
- `sl` Slanted (oblique)
- `sc` Small caps
- `ui` Upright italics
- `ol` Outline

The two last shapes are not available for most font families.

`\fontsize{size}{skip}`

Set font size. The first parameter is the font size to switch to and the second is the line spacing to use; this is stored in a parameter named `\baselineskip`. The unit of both parameters defaults to `pt`. The default `\baselineskip` for the Computer Modern typeface is 1.2 times the `\fontsize`.

The line spacing is also multiplied by the value of the `\baselinestretch` parameter when the type size changes; the default is 1. However, the best way

to “double space” a document, if you should be unlucky enough to have to produce such, is to use the `setspace` package; see <http://www.tex.ac.uk/cgi-bin/texfaq2html?label=linespace>.

`\linespread{factor}`

Equivalent to `\renewcommand{\baselinestretch}{factor}`, and therefore must be followed by `\selectfont` to have any effect. Best specified in the preamble, or use the `setspace` package, as described just above.

The changes made by calling the font commands described above do not come into effect until `\selectfont` is called.

`\usefont{enc}{family}{series}{shape}`

The same as invoking `\fontencoding`, `\fontfamily`, `\fontseries` and `\fontshape` with the given parameters, followed by `\selectfont`.

6 Layout

Miscellaneous commands for controlling the general layout of the page.

6.1 `\onecolumn`

The `\onecolumn` declaration starts a new page and produces single-column output. This is the default.

6.2 `\twocolumn`

Synopsis:

```
\twocolumn[text1col]
```

The `\twocolumn` declaration starts a new page and produces two-column output. If the optional *text1col* argument is present, it is typeset in one-column mode before the two-column typesetting starts.

These parameters control typesetting in two-column output:

`\columnsep`

The distance between columns (35pt by default).

`\columnseprule`

The width of the rule between columns; the default is 0pt, so there is no rule.

`\columnwidth`

The width of the current column; this is equal to `\textwidth` in single-column text.

These parameters control float behavior in two-column output:

`\dbltopfraction`

Maximum fraction at the top of a two-column page that may be occupied by floats. Default `‘.7’`, can be usefully redefined to (say) `‘.9’` to avoid going to float pages so soon.

`\dblfloatpagefraction`

The minimum fraction of a float page that must be occupied by floats, for a two-column float page. Default `‘.5’`.

`\dblfloatsep`

Distance between floats at the top or bottom of a two-column float page. Default `‘12pt plus2pt minus2pt’` for `‘10pt’` and `‘11pt’` documents, `‘14pt plus2pt minus4pt’` for `‘12pt’`.

`\dbltextfloatsep`

Distance between a multi-column float at the top or bottom of a page and the main text. Default `‘20pt plus2pt minus4pt’`.

6.3 `\flushbottom`

The `\flushbottom` declaration makes all text pages the same height, adding extra vertical space where necessary to fill out the page.

This is the default if `twocolumn` mode is selected (see [Section 4.1 \[Document class options\]](#), page 5).

6.4 `\raggedbottom`

The `\raggedbottom` declaration makes all pages the natural height of the material on that page. No rubber lengths will be stretched.

6.5 Page layout parameters

`\headheight`

Height of the box that contains the running head. Default is ‘30pt’, except in the `book` class, where it varies with the type size.

`\headsep`

Vertical distance between the bottom of the header line and the top of the main text. Default is ‘25pt’, except in the `book` class, where it varies with the type size.

`\footskip`

Distance from the baseline of the last line of text to the baseline of the page footer. Default is ‘30pt’, except in the `book` class, where it varies with the type size.

`\linewidth`

Width of the current line, decreased for each nested `list` (see [Section 9.15 \[list\]](#), page 23). Specifically, it is smaller than `\textwidth` by the sum of `\leftmargin` and `\rightmargin` (see [Section 9.13 \[itemize\]](#), page 22). The default varies with the font size, paper width, two-column mode, etc. For an `article` document in ‘10pt’, it’s set to ‘345pt’; in two-column mode, that becomes ‘229.5pt’.

`\textheight`

The normal vertical height of the page body; the default varies with the font size, document class, etc. For an `article` or `report` document in ‘10pt’, it’s set to ‘43\baselineskip’; for `book`, it’s ‘41\baselineskip’. For ‘11pt’, it’s ‘38\baselineskip’ and for ‘12pt’, ‘36\baselineskip’.

`\textwidth`

The full horizontal width of the entire page body; the default varies as usual. For an `article` or `report` document, it’s ‘345pt’ at ‘10pt’, ‘360pt’ at ‘11pt’, and ‘390pt’ at ‘12pt’. For a `book` document, it’s ‘4.5in’ at ‘10pt’, and ‘5in’ at ‘11pt’ or ‘12pt’.

In multi-column output, `\textwidth` remains the width of the entire page body, while `\columnwidth` is the width of one column (see [Section 6.2 \[\twocolumn\]](#), page 11).

In lists (see [Section 9.15 \[list\]](#), page 23), `\textwidth` remains the width of the entire page body (and `\columnwidth` the width of the entire column), while `\linewidth` may decrease for nested lists.

Inside a `minipage` (see [Section 9.17 \[minipage\], page 24](#)) or `\parbox` (see [Section 21.5 \[\parbox\], page 68](#)), all the width-related parameters are set to the specified width, and revert to their normal values at the end of the `minipage` or `\parbox`.

For completeness: `\hsize` is the T_EX primitive parameter used when text is broken into lines. It should not be used in normal L^AT_EX documents.

`\topmargin`

Space between the top of the T_EX page (one inch from the top of the paper, by default) and the top of the header. The default is computed based on many other parameters: `\paperheight - 2in - \headheight - \headsep - \textheight - \footskip`, and then divided by two.

`\topskip`

Minimum distance between the top of the page body and the baseline of the first line of text. For the standard classes, the default is the same as the font size, e.g., ‘10pt’ at ‘10pt’.

7 Sectioning

Sectioning commands provide the means to structure your text into units:

```
\part
\chapter (report and book class only)
\section
\subsection
\subsubsection
\paragraph
\subparagraph
```

All sectioning commands take the same general form, e.g.,

```
\chapter[toctitle]{title}
```

In addition to providing the heading *title* in the main text, the section title can appear in two other places:

1. The table of contents.
2. The running head at the top of the page.

You may not want the same text in these places as in the main text. To handle this, the sectioning commands have an optional argument *toctitle* that, when given, specifies the text for these other places.

Also, all sectioning commands have *-forms that print *title* as usual, but do not include a number and do not make an entry in the table of contents. For instance:

```
\section*{Preamble}
```

The `\appendix` command changes the way following sectional units are numbered. The `\appendix` command itself generates no text and does not affect the numbering of parts. The normal use of this command is something like

```
\chapter{A Chapter}
...
\appendix
\chapter{The First Appendix}
```

The `secnumdepth` counter controls printing of section numbers. The setting

```
\setcounter{secnumdepth}{level}
```

suppresses heading numbers at any depth $>$ *level*, where `chapter` is level zero. (See [Section 14.4](#) [`\setcounter`], page 45.)

8 Cross references

One reason for numbering things like figures and equations is to refer the reader to them, as in “See Figure 3 for more details.”

8.1 `\label`

Synopsis:

```
\label{key}
```

A `\label` command appearing in ordinary text assigns to *key* the number of the current sectional unit; one appearing inside a numbered environment assigns that number to *key*.

A *key* name can consist of any sequence of letters, digits, or punctuation characters. Upper and lowercase letters are distinguished.

To avoid accidentally creating two labels with the same name, it is common to use labels consisting of a prefix and a suffix separated by a colon or period. Some conventionally-used prefixes:

<code>ch</code>	for chapters
<code>sec</code>	for lower-level sectioning commands
<code>fig</code>	for figures
<code>tab</code>	for tables
<code>eq</code>	for equations

Thus, a label for a figure would look like `fig:snark` or `fig.snark`.

8.2 `\pageref{key}`

Synopsis:

```
\pageref{key}
```

The `\pageref{key}` command produces the page number of the place in the text where the corresponding `\label{key}` command appears.

8.3 `\ref{key}`

Synopsis:

```
\ref{key}
```

The `\ref` command produces the number of the sectional unit, equation, footnote, figure, . . . , of the corresponding `\label` command (see [Section 8.1 \[`\label`\], page 15](#)). It does not produce any text, such as the word ‘Section’ or ‘Figure’, just the bare number itself.

9 Environments

L^AT_EX provides many environments for marking off certain text. Each environment begins and ends in the same manner:

```
\begin{envname}
...
\end{envname}
```

9.1 abstract

Synopsis:

```
\begin{abstract}
...
\end{abstract}
```

Environment for producing an abstract, possibly of multiple paragraphs.

9.2 array

Synopsis:

```
\begin{array}{template}
col1 text&col1 text&coln}\\
...
\end{array}
```

Math arrays are produced with the `array` environment, normally within an `equation` environment (see [Section 9.9 \[equation\]](#), page 19). It has a single mandatory *template* argument describing the number of columns and the alignment within them. Each column *col* is specified by a single letter that tells how items in that row should be formatted, as follows:

c	centered
l	flush left
r	flush right

Column entries are separated by `&`. Column entries may include other L^AT_EX commands. Each row of the array is terminated with `\\`.

In the template, the construct `@{text}` puts *text* between columns in each row.

Here's an example:

```
\begin{equation}
\begin{array}{lrc}
left1 & right1 & centered1 \\
left2 & right2 & centered2 \\
\end{array}
\end{equation}
```

The `\arraycolsep` parameter defines half the width of the space separating columns; the default is '5pt'. See [Section 9.23 \[tabular\]](#), page 30, for other parameters which affect formatting in `array` environments, namely `\arrayrulewidth` and `\arraystretch`.

The `array` environment can only be used in math mode.

9.3 center

Synopsis:

```
\begin{center}
line1 \\
line2 \\
\end{center}
```

The `center` environment allows you to create a paragraph consisting of lines that are centered within the left and right margins on the current page. Each line is terminated with the string `\\`.

9.3.1 \centering

The `\centering` declaration corresponds to the `center` environment. This declaration can be used inside an environment such as `quote` or in a `parbox`. Thus, the text of a figure or table can be centered on the page by putting a `\centering` command at the beginning of the figure or table environment.

Unlike the `center` environment, the `\centering` command does not start a new paragraph; it simply changes how L^AT_EX formats paragraph units. To affect a paragraph unit's format, the scope of the declaration must contain the blank line or `\end` command (of an environment such as `quote`) that ends the paragraph unit.

Here's an example:

```
\begin{quote}
\centering
first line \\
second line \\
\end{quote}
```

9.4 description

Synopsis:

```
\begin{description}
\item [label1] item1
\item [label2] item2
...
\end{description}
```

The `description` environment is used to make labelled lists. Each *label* is typeset in bold, flush right. The *item* text may contain multiple paragraphs.

Another variation: since the bold style is applied to the labels, if you typeset a label in typewriter using `\texttt`, you'll get bold typewriter: `\item[\texttt{bold and typewriter}]`. This may be too bold, among other issues. To get just typewriter, use `\tt`, which resets all other style variations: `\item[{\tt plain typewriter}]`.

For details about list spacing, see [Section 9.13 \[itemize\], page 22](#).

9.5 displaymath

Synopsis:

```
\begin{displaymath}
math
\end{displaymath}
```

or

```
\[math\]
```

The `displaymath` environment (`\[...\]` is a synonym) typesets the *math* text on its own line, centered by default. The global `fleqn` option makes equations flush left; see [Section 4.1 \[Document class options\]](#), page 5.

No equation number is added to `displaymath` text; to get an equation number, use the `equation` environment (see [Section 9.9 \[equation\]](#), page 19).

9.6 document

The `document` environment encloses the body of a document. It is required in every L^AT_EX document. See [Chapter 3 \[Starting & ending\]](#), page 4.

9.7 enumerate

Synopsis:

```
\begin{enumerate}
\item item1
\item item2
...
\end{enumerate}
```

The `enumerate` environment produces a numbered list. Enumerations can be nested within one another, up to four levels deep. They can also be nested within other paragraph-making environments, such as `itemize` (see [Section 9.13 \[itemize\]](#), page 22) and `description` (see [Section 9.4 \[description\]](#), page 17).

Each item of an enumerated list begins with an `\item` command. There must be at least one `\item` command within the environment.

By default, the numbering at each level is done like this:

1. 1., 2., ...
2. (a), (b), ...
3. i., ii., ...
4. A., B., ...

The `enumerate` environment uses the counters `\enumi` through `\enumiv` counters (see [Chapter 14 \[Counters\]](#), page 44). If the optional argument to `\item` is given, the counter is not incremented for that item.

The `enumerate` environment uses the commands `\labelenumi` through `\labelenumiv` to produce the default label. So, you can use `\renewcommand` to change the labels (see [Section 13.1 \[\newcommand & \renewcommand\]](#), page 41). For instance, to have the first level use uppercase letters:

```
\renewcommand{\labelenumi}{\Alph{enumi}}
```

9.8 eqnarray

First, a caveat: the `eqnarray` environment has some infelicities which cannot be overcome; the article “Avoid eqnarray!” by Lars Madsen describes them in detail (<http://tug.org/TUGboat/tb33-1/tb103madsen.pdf>). The bottom line is that it is better to use the `align` environment (and others) from the `amsmath` package.

Nevertheless, here is a description of `eqnarray`:

```
\begin{eqnarray} (or eqnarray*)
  formula1 \\
  formula2 \\
  ...
\end{eqnarray}
```

The `eqnarray` environment is used to display a sequence of equations or inequalities. It is very much like a three-column `array` environment, with consecutive rows separated by `\\` and consecutive items within a row separated by an `&`.

`*` can also be used to separate equations, with its normal meaning of not allowing a page break at that line.

An equation number is placed on every line unless that line has a `\nonumber` command. Alternatively, The `*`-form of the environment (`\begin{eqnarray*} ... \end{eqnarray*}`) will omit equation numbering entirely, while otherwise being the same as `eqnarray`.

The command `\lefteqn` is used for splitting long formulas across lines. It typesets its argument in display style flush left in a box of zero width.

9.9 equation

Synopsis:

```
\begin{equation}
  math
\end{equation}
```

The `equation` environment starts a `displaymath` environment (see [Section 9.5 \[display-math\], page 17](#)), e.g., centering the `math` text on the page, and also places an equation number in the right margin.

9.10 figure

```
\begin{figure[*]}[placement]
  figbody
\label{label}
\caption[loftitle]{text}
\end{figure}
```

Figures are objects that are not part of the normal text, and are instead “floated” to a convenient place, such as the top of a page. Figures will not be split between two pages.

When typesetting in double-columns, the starred form produces a full-width figure (across both columns).

The optional argument `[placement]` determines where \LaTeX will try to place your figure. There are four places where \LaTeX can possibly put a float:

- t** (Top)—at the top of a text page.
- b** (Bottom)—at the bottom of a text page. However, **b** is not allowed for full-width floats (`figure*`) with double-column output. To ameliorate this, use the `stfloats` or `dblfloatfix` package, but see the discussion at caveats in the FAQ: <http://www.tex.ac.uk/cgi-bin/texfaq2html?label=2colfloat>.
- h** (Here)—at the position in the text where the figure environment appears. However, this is not allowed by itself; **t** is automatically added. To absolutely force a figure to appear “here”, you can `\usepackage{float}` and use the `H` specifier which it defines. For further discussion, see the FAQ entry at <http://www.tex.ac.uk/cgi-bin/texfaq2html?label=figurehere>.
- p** (Page of floats)—on a separate float page, which is a page containing no text, only floats.
- !** Used in addition to one of the above; for this float only, L^AT_EX ignores the restrictions on both the number of floats that can appear and the relative amounts of float and non-float text on the page. The **!** specifier does *not* mean “put the float here”; see above.

The standard report and article classes use the default placement `tbp`.

The body of the figure is made up of whatever text, L^AT_EX commands, etc. you wish.

The `\caption` command specifies caption *text* for the figure. The caption is numbered by default. If `loftitle` is present, it is used in the list of figures instead of *text* (see [Section 24.1 \[Tables of contents\]](#), page 77).

Parameters relating to fractions of pages occupied by float and non-float text:

The maximum fraction of the page allowed to be occupied by floats at the bottom; default ‘.3’.

`\floatpagefraction`

The minimum fraction of a float page that must be occupied by floats; default ‘.5’.

`\textfraction`

Minimum fraction of a page that must be text; if floats take up too much space to preserve this much text, floats will be moved to a different page. The default is ‘.2’.

`\topfraction`

Maximum fraction at the top of a page that may be occupied before floats; default ‘.7’.

Parameters relating to vertical space around floats:

`\floatsep`

Space between floats at the top or bottom of a page; default ‘12pt plus2pt minus2pt’.

`\intextsep`

Space above and below a float in the middle of the main text; default ‘12pt plus2pt minus2pt’ for ‘10pt’ and ‘11pt’ styles, ‘14pt plus4pt minus4pt’ for ‘12pt’.

\textfloatsep

Space between the last (first) float at the top (bottom) of a page; default ‘20pt plus2pt minus4pt’.

Parameters relating to the number of floats on a page:

\bottomnumber

Maximum number of floats that can appear at the bottom of a text page; default 1.

\topnumber

Maximum number of floats that can appear at the top of a text page; default 2.

\totalnumber

Maximum number of floats that can appear on a text page; default 3.

The principal T_EX FAQ entry relating to floats: <http://www.tex.ac.uk/cgi-bin/texfaq2html?label=floats>.

9.11 flushleft

```
\begin{flushleft}
line1 \\
line2 \\
...
\end{flushleft}
```

The `flushleft` environment allows you to create a paragraph consisting of lines that are flush to the left-hand margin and ragged right. Each line must be terminated with the string `\\`.

9.11.1 \raggedright

The `\raggedright` declaration corresponds to the `flushleft` environment. This declaration can be used inside an environment such as `quote` or in a `parbox`.

Unlike the `flushleft` environment, the `\raggedright` command does not start a new paragraph; it only changes how L^AT_EX formats paragraph units. To affect a paragraph unit’s format, the scope of the declaration must contain the blank line or `\end` command that ends the paragraph unit.

9.12 flushright

```
\begin{flushright}
line1 \\
line2 \\
...
\end{flushright}
```

The `flushright` environment allows you to create a paragraph consisting of lines that are flush to the right-hand margin and ragged left. Each line must be terminated with the string `\\`.

9.12.1 `\raggedleft`

The `\raggedleft` declaration corresponds to the `flushright` environment. This declaration can be used inside an environment such as `quote` or in a `parbox`.

Unlike the `flushright` environment, the `\raggedleft` command does not start a new paragraph; it only changes how L^AT_EX formats paragraph units. To affect a paragraph unit's format, the scope of the declaration must contain the blank line or `\end` command that ends the paragraph unit.

9.13 `itemize`

Synopsis:

```
\begin{itemize}
  \item item1
  \item item2
  ...
\end{itemize}
```

The `itemize` environment produces an “unordered”, “bulleted” list. Itemizations can be nested within one another, up to four levels deep. They can also be nested within other paragraph-making environments, such as `enumerate` (see [Section 9.7 \[enumerate\], page 18](#)).

Each item of an `itemize` list begins with an `\item` command. There must be at least one `\item` command within the environment.

By default, the marks at each level look like this:

1. • (bullet)
2. -- (bold en-dash)
3. * (asterisk)
4. · (centered dot)

The `itemize` environment uses the commands `\labelitemi` through `\labelitemiv` to produce the default label. So, you can use `\renewcommand` to change the labels. For instance, to have the first level use diamonds:

```
\renewcommand{\labelitemi}{\diamond$}
```

The `\leftmargini` through `\leftmarginvi` parameters define the distance between the left margin of the enclosing environment and the left margin of the list. By convention, `\leftmargin` is set to the appropriate `\leftmarginN` when a new level of nesting is entered.

The defaults vary from `‘.5em’` (highest levels of nesting) to `‘2.5em’` (first level), and are a bit reduced in two-column mode. This example greatly reduces the margin space for outermost lists:

```
\setlength{\leftmargini}{1.25em} % default 2.5em
```

Some parameters that affect list formatting:

`\itemindent`

Extra indentation before each item in a list; default zero.

`\labelsep`

Space between the label and text of an item; default `‘.5em’`.

- `\labelwidth` Width of the label; default ‘2em’, or ‘1.5em’ in two-column mode.
- `\listparindent` Extra indentation added to second and subsequent paragraphs within a list item; default ‘0pt’.
- `\rightmargin` Horizontal distance between the right margin of the list and the enclosing environment; default ‘0pt’, except in the `quote`, `quotation`, and `verse` environments, where it is set equal to `\leftmargin`.
- Parameters affecting vertical spacing between list items (rather loose, by default).
- `\itemsep` Vertical space between items. The default is `2pt plus1pt minus1pt` for 10pt documents, `3pt plus2pt minus1pt` for 11pt, and `4.5pt plus2pt minus1pt` for 12pt.
- `\parsep` Extra vertical space between paragraphs within a list item. Defaults are the same as `\itemsep`.
- `\topsep` Vertical space between the first item and the preceding paragraph. For top-level lists, the default is `8pt plus2pt minus4pt` for 10pt documents, `9pt plus3pt minus5pt` for 11pt, and `10pt plus4pt minus6pt` for 12pt. These are reduced for nested lists.
- `\partopsep` Extra space added to `\topsep` when the list environment starts a paragraph. The default is `2pt plus1pt minus1pt` for 10pt documents, `3pt plus1pt minus1pt` for 11pt, and `3pt plus2pt minus2pt` for 12pt.

Especially for lists with short items, it may be desirable to elide space between items. Here is an example defining an `itemize*` environment with no extra spacing between items, or between paragraphs within a single item (`\parskip` is not list-specific, see [Section 16.3](#) [`\parskip`], page 47):

```
\newenvironment{itemize*}%
  {\begin{itemize}%
   \setlength{\itemsep}{0pt}%
   \setlength{\parsep}{0pt}}%
  {\setlength{\parskip}{0pt}}%
  {\end{itemize}}
```

9.14 letter environment: writing letters

This environment is used for creating letters. See [Chapter 25](#) [Letters], page 79.

9.15 list

The `list` environment is a generic environment which is used for defining many of the more specific environments. It is seldom used in documents, but often in macros.

```
\begin{list}{labeling}{spacing}
\item item1
```

```

\item item2
...
\end{list}

```

The mandatory *labeling* argument specifies how items should be labelled (unless the optional argument is supplied to `\item`). This argument is a piece of text that is inserted in a box to form the label. It can and usually does contain other L^AT_EX commands.

The mandatory *spacing* argument contains commands to change the spacing parameters for the list. This argument will most often be empty, i.e., `{}`, which leaves the default spacing.

The width used for typesetting the list items is specified by `\linewidth` (see [Section 6.5 \[Page layout parameters\]](#), page 12).

9.16 math

Synopsis:

```

\begin{math}
math
\end{math}

```

The `math` environment inserts the given *math* within the running text. `\(...\)` and `$. . . $` are synonyms. See [Chapter 17 \[Math formulas\]](#), page 49.

9.17 minipage

```

\begin{minipage}[position][height][inner-pos]{width}
text
\end{minipage}

```

The `minipage` environment typesets its body *text* in a block that will not be broken across pages. This is similar to the `\parbox` command (see [Section 21.5 \[\parbox\]](#), page 68), but unlike `\parbox`, other paragraph-making environments can be used inside a `minipage`.

The arguments are the same as for `\parbox` (see [Section 21.5 \[\parbox\]](#), page 68).

By default, paragraphs are not indented in the `minipage` environment. You can restore indentation with a command such as `\setlength{\parindent}{1pc}` command.

Footnotes in a `minipage` environment are handled in a way that is particularly useful for putting footnotes in figures or tables. A `\footnote` or `\footnotetext` command puts the footnote at the bottom of the `minipage` instead of at the bottom of the page, and it uses the `\mpfootnote` counter instead of the ordinary `footnote` counter (see [Chapter 14 \[Counters\]](#), page 44).

However, don't put one `minipage` inside another if you are using footnotes; they may wind up at the bottom of the wrong `minipage`.

9.18 picture

```

\begin{picture}(width,height)(x offset,y offset)
... picture commands ...
\end{picture}

```

The `picture` environment allows you to create just about any kind of picture you want containing text, lines, arrows and circles. You tell \LaTeX where to put things in the picture by specifying their coordinates. A coordinate is a number that may have a decimal point and a minus sign—a number like 5, 0.3 or -3.1416. A coordinate specifies a length in multiples of the unit length `\unitlength`, so if `\unitlength` has been set to 1cm, then the coordinate 2.54 specifies a length of 2.54 centimeters. You should only change the value of `\unitlength`, using the `\setlength` command, outside of a `picture` environment.

A position is a pair of coordinates, such as (2.4,-5), specifying the point with x-coordinate 2.4 and y-coordinate -5. Coordinates are specified in the usual way with respect to an origin, which is normally at the lower-left corner of the picture. Note that when a position appears as an argument, it is not enclosed in braces; the parentheses serve to delimit the argument.

The `picture` environment has one mandatory argument, which is a **position**. It specifies the size of the picture. The environment produces a rectangular box with width and height determined by this argument's x- and y-coordinates.

The `picture` environment also has an optional **position** argument, following the **size** argument, that can change the origin. (Unlike ordinary optional arguments, this argument is not contained in square brackets.) The optional argument gives the coordinates of the point at the lower-left corner of the picture (thereby determining the origin). For example, if `\unitlength` has been set to 1mm, the command

```
\begin{picture}(100,200)(10,20)
```

produces a picture of width 100 millimeters and height 200 millimeters, whose lower-left corner is the point (10,20) and whose upper-right corner is therefore the point (110,220). When you first draw a picture, you typically omit the optional argument, leaving the origin at the lower-left corner. If you then want to modify your picture by shifting everything, you can just add the appropriate optional argument.

The environment's mandatory argument determines the nominal size of the picture. This need bear no relation to how large the picture really is; \LaTeX will happily allow you to put things outside the picture, or even off the page. The picture's nominal size is used by \LaTeX in determining how much room to leave for it.

Everything that appears in a picture is drawn by the `\put` command. The command

```
\put (11.3,-.3){...}
```

puts the object specified by `...` in the picture, with its reference point at coordinates (11.3, -.3). The reference points for various objects will be described below.

The `\put` command creates an *LR* box. You can put anything that can go in an `\mbox` (see [Section 21.1 \[`\mbox`\], page 67](#)) in the text argument of the `\put` command. When you do this, the reference point will be the lower left corner of the box.

The `picture` commands are described in the following sections.

9.18.1 `\circle`

```
\circle[*]{diameter}
```

The `\circle` command produces a circle with a diameter as close to the specified one as possible. The `*`-form of the command draws a solid circle.

Circles up to 40 pt can be drawn.

9.18.2 `\makebox`

`\makebox(width,height)[position]{...}`

The `\makebox` command for the `picture` environment is similar to the normal `\makebox` command except that you must specify a `width` and `height` in multiples of `\unitlength`.

The optional argument, `[position]`, specifies the quadrant that your text appears in. You may select up to two of the following:

- `t` Moves the item to the top of the rectangle.
- `b` Moves the item to the bottom.
- `l` Moves the item to the left.
- `r` Moves the item to the right.

See [Section 21.4 \[`\makebox`\], page 67](#).

9.18.3 `\framebox`

Synopsis:

`\framebox(width,height)[pos]{...}`

The `\framebox` command is like `\makebox` (see previous section), except that it puts a frame around the outside of the box that it creates.

The `\framebox` command produces a rule of thickness `\fboxrule`, and leaves a space `\fboxsep` between the rule and the contents of the box.

9.18.4 `\dashbox`

Draws a box with a dashed line. Synopsis:

`\dashbox{dlen}(rwidth,rheight)[pos]{text}`

`\dashbox` creates a dashed rectangle around `text` in a `picture` environment. Dashes are `dlen` units long, and the rectangle has overall width `rwidth` and height `rheight`. The `text` is positioned at optional `pos`.

A dashed box looks best when the `rwidth` and `rheight` are multiples of the `dlen`.

9.18.5 `\frame`

Synopsis:

`\frame{text}`

The `\frame` command puts a rectangular frame around `text`. The reference point is the bottom left corner of the frame. No extra space is put between the frame and the object.

9.18.6 `\line`

Synopsis:

`\line(xslope,yslope){length}`

The `\line` command draws a line with the given `length` and slope `xslope/yslope`.

Standard \LaTeX can only draw lines with $slope = x/y$, where x and y have integer values from -6 through 6 . For lines of any slope, not to mention other shapes, see the `curve2e` and many many other packages on CTAN.

9.18.7 `\linethickness`

The `\linethickness{dim}` command declares the thickness of horizontal and vertical lines in a picture environment to be *dim*, which must be a positive length.

`\linethickness` does not affect the thickness of slanted lines, circles, or the quarter circles drawn by `\oval`.

9.18.8 `\thicklines`

The `\thicklines` command is an alternate line thickness for horizontal and vertical lines in a picture environment; cf. [Section 9.18.7 \[`\linethickness`\], page 27](#) and [Section 9.18.9 \[`\thinlines`\], page 27](#).

9.18.9 `\thinlines`

The `\thinlines` command is the default line thickness for horizontal and vertical lines in a picture environment; cf. [Section 9.18.7 \[`\linethickness`\], page 27](#) and [Section 9.18.8 \[`\thicklines`\], page 27](#).

9.18.10 `\multiput`

Synopsis:

```
\multiput(x,y)(delta_x,delta_y){n}{obj}
```

The `\multiput` command copies the object *obj* in a regular pattern across a picture. *obj* is first placed at position (x, y) , then at $(x + \delta x, y + \delta y)$, and so on, *n* times.

9.18.11 `\oval`

Synopsis:

```
\oval(width,height)[portion]
```

The `\oval` command produces a rectangle with rounded corners. The optional argument *portion* allows you to select part of the oval via the following:

- t** selects the top portion;
- b** selects the bottom portion;
- r** selects the right portion;
- l** selects the left portion.

The “corners” of the oval are made with quarter circles with a maximum radius of 20 pt, so large “ovals” will look more like boxes with rounded corners.

9.18.12 `\put`

```
\put(x coord,y coord){ ... }
```

The `\put` command places the item specified by the mandatory argument at the given coordinates.

9.18.13 `\shortstack`

Synopsis:

```
\shortstack[position]{...\\...\\...}
```

The `\shortstack` command produces a stack of objects. The valid positions are:

- r Move the objects to the right of the stack.
- l Move the objects to the left of the stack
- c Move the objects to the centre of the stack (default)

Objects are separated with `\\`.

9.18.14 `\vector`

Synopsis:

```
\vector(x-slope,y-slope){length}
```

The `\vector` command draws a line with an arrow of the specified length and slope. The x and y values must lie between -4 and $+4$, inclusive.

9.19 quotation

Synopsis:

```
\begin{quotation}
  text
\end{quotation}
```

The margins of the `quotation` environment are indented on both the left and the right. The text is justified at both margins. Leaving a blank line between text produces a new paragraph.

Unlike the `quote` environment, each paragraph is indented normally.

9.20 quote

Snyopsis:

```
\begin{quote}
  text
\end{quote}
```

The margins of the `quote` environment are indented on both the left and the right. The text is justified at both margins. Leaving a blank line between text produces a new paragraph.

Unlike the `quotation` environment, paragraphs are not indented.

9.21 tabbing

Synopsis:

```
\begin{tabbing}
  row1col1 \= row1col2 \= row1col3 \= row1col4 \\
  row2col1 \>                    \> row2col3 \\
```

```
...
\end{tabbing}
```

The `tabbing` environment provides a way to align text in columns. It works by setting tab stops and tabbing to them much as was done on an ordinary typewriter. It is best suited for cases where the width of each column is constant and known in advance.

This environment can be broken across pages, unlike the `tabular` environment.

The following commands can be used inside a `tabbing` environment:

- `\` (tabbing) End a line.
- `\=` (tabbing) Sets a tab stop at the current position.
- `\>` (tabbing) Advances to the next tab stop.
- `\<` Put following text to the left of the local margin (without changing the margin). Can only be used at the start of the line.
- `\+` Moves the left margin of the next and all the following commands one tab stop to the right, beginning tabbed line if necessary.
- `\-` Moves the left margin of the next and all the following commands one tab stop to the left, beginning tabbed line if necessary.
- `\'` (tabbing) Moves everything that you have typed so far in the current column, i.e. everything from the most recent `\>`, `\<`, `\'`, `\`, or `\kill` command, to the right of the previous column, flush against the current column's tab stop.
- `\‘` (tabbing) Allows you to put text flush right against any tab stop, including tab stop 0. However, it can't move text to the right of the last column because there's no tab stop there. The `\‘` command moves all the text that follows it, up to the `\` or `\end{tabbing}` command that ends the line, to the right margin of the `tabbing` environment. There must be no `\>` or `\'` command between the `\‘` and the command that ends the line.
- `\a` (tabbing) In a `tabbing` environment, the commands `\=`, `\'` and `\‘` do not produce accents as usual (see [Section 22.3 \[Accents\]](#), page 73). Instead, the commands `\a=`, `\a'` and `\a‘` are used.
- `\kill` Sets tab stops without producing text. Works just like `\` except that it throws away the current line instead of producing output for it. The effect of any `\=`, `\+` or `\-` commands in that line remain in effect.
- `\poptabs` Restores the tab stop positions saved by the last `\pushtabs`.
- `\pushtabs` Saves all current tab stop positions. Useful for temporarily changing tab stop positions in the middle of a `tabbing` environment.

`\tabbingsep`

Distance to left of tab stop moved by `\'`.

This example typesets a Pascal function in a traditional format:

```
\begin{tabbing}
function \= fact(n : integer) : integer;\
  \> begin \= \+ \\\
    \> if \= n $>$ 1 then \+ \\\
      fact := n * fact(n-1) \- \\\
    else \+ \\\
      fact := 1; \- \- \\\
  end;\
\end{tabbing}
```

9.22 table

Synopsis:

```
\begin{table}[placement]

  body of the table

\caption{table title}
\end{table}
```

Tables are objects that are not part of the normal text, and are usually “floated” to a convenient place, like the top of a page. Tables will not be split between two pages.

The optional argument `[placement]` determines where \LaTeX will try to place your table. There are four places where \LaTeX can possibly put a float; these are the same as that used with the `figure` environment, and described there (see [Section 9.10 \[figure\]](#), page 19).

The standard `report` and `article` classes use the default placement `[tbp]`.

The body of the table is made up of whatever text, \LaTeX commands, etc., you wish. The `\caption` command allows you to title your table.

9.23 tabular

Synopsis:

```
\begin{tabular}[pos]{cols}
column 1 entry & column 2 entry ... & column n entry \\\
...
\end{tabular}
```

or

```
\begin{tabular*}{width}[pos]{cols}
column 1 entry & column 2 entry ... & column n entry \\\
...
\end{tabular*}
```

These environments produce a box consisting of a sequence of rows of items, aligned vertically in columns.

`\` must be used to specify the end of each row of the table, except for the last, where it is optional—unless an `\hline` command (to put a rule below the table) follows.

The mandatory and optional arguments consist of:

<code>width</code>	Specifies the width of the <code>tabular*</code> environment. There must be rubber space between columns that can stretch to fill out the specified width.
<code>pos</code>	Specifies the vertical position; default is alignment on the centre of the environment. <ul style="list-style-type: none"> <code>t</code> align on top row <code>b</code> align on bottom row
<code>cols</code>	Specifies the column formatting. It consists of a sequence of the following specifiers, corresponding to the sequence of columns and intercolumn material. <ul style="list-style-type: none"> <code>l</code> A column of left-aligned items. <code>r</code> A column of right-aligned items. <code>c</code> A column of centered items. <code> </code> A vertical line the full height and depth of the environment. <code>@{text}</code> This inserts <i>text</i> in every row. An @-expression suppresses the intercolumn space normally inserted between columns; any desired space before the adjacent item must be included in <i>text</i>. To insert commands that are automatically executed before a given column, you have to load the <code>array</code> package and use the <code>>{...}</code> specifier. An <code>\extracolsep{wd}</code> command in an @-expression causes an extra space of width <i>wd</i> to appear to the left of all subsequent columns, until countermanded by another <code>\extracolsep</code> command. Unlike ordinary intercolumn space, this extra space is not suppressed by an @-expression. An <code>\extracolsep</code> command can be used only in an @-expression in the <code>cols</code> argument. <code>p{wd}</code> Produces a column with each item typeset in a parbox of width <i>wd</i>, as if it were the argument of a <code>\parbox[t]{wd}</code> command. However, a <code>\</code> may not appear in the item, except in the following situations: <ol style="list-style-type: none"> 1. inside an environment like <code>minipage</code>, <code>array</code>, or <code>tabular</code>. 2. inside an explicit <code>\parbox</code>. 3. in the scope of a <code>\centering</code>, <code>\raggedright</code>, or <code>\raggedleft</code> declaration. The latter declarations must appear inside braces or an environment when used in a <code>p</code>-column element. <code>*{num}{cols}</code> Equivalent to <i>num</i> copies of <i>cols</i>, where <i>num</i> is a positive integer and <i>cols</i> is any list of column-specifiers, which may contain another *-expression.

Parameters that control formatting:

`\arrayrulewidth`

Thickness of the rule created by `|`, `\hline`, and `\vline` in the `tabular` and `array` environments; the default is `’.4pt’`.

`\arraystretch`

Scaling of spacing between rows in the `tabular` and `array` environments; default is `’1’`, for no scaling.

`\doublerulesep`

Horizontal distance between the vertical rules produced by `||` in the `tabular` and `array` environments; default is `’2pt’`.

`\tabcolsep`

Half the width of the space between columns; default is `’6pt’`.

The following commands can be used inside a `tabular` environment:

9.23.1 `\multicolumn`

Synopsis:

```
\multicolumn{cols}{pos}{text}
```

The `\multicolumn` command makes an entry that spans several columns. The first mandatory argument, `cols`, specifies the number of columns to span. The second mandatory argument, `pos`, specifies the formatting of the entry; `c` for centered, `l` for flushleft, `r` for flushright. The third mandatory argument, `text`, specifies what text to put in the entry.

Here’s an example showing two columns separated by an en-dash; `\multicolumn` is used for the heading:

```
\begin{tabular}{r@{--}l}
\multicolumn{2}{c}{\bf Unicode}\cr
0x80&0x7FFF \cr
0x800&0xFFFF \cr
0x10000&0x1FFFF \cr
\end{tabular}
```

9.23.2 `\cline`

Synopsis:

```
\cline{i-j}
```

The `\cline` command draws horizontal lines across the columns specified, beginning in column `i` and ending in column `j`, which are specified in the mandatory argument.

9.23.3 `\hline`

The `\hline` command draws a horizontal line the width of the enclosing `tabular` or `array` environment. It’s most commonly used to draw a line at the top, bottom, and between the rows of a table.

9.23.4 `\vline`

The `\vline` command will draw a vertical line extending the full height and depth of its row. An `\hfill` command can be used to move the line to the edge of the column. It can also be used in an `@`-expression.

9.24 `thebibliography`

Synopsis:

```
\begin{thebibliography}{widest-label}
  \bibitem[label]{cite_key}
  ...
\end{thebibliography}
```

The `thebibliography` environment produces a bibliography or reference list.

In the `article` class, this reference list is labelled “References”; in the `report` class, it is labelled “Bibliography”. You can change the label (in the standard classes) by redefining the command `\refname`. For instance, this eliminates it entirely:

```
\renewcommand{\refname}{} 
```

The mandatory *widest-label* argument is text that, when typeset, is as wide as the widest item label produced by the `\bibitem` commands. It is typically given as 9 for bibliographies with less than 10 references, 99 for ones with less than 100, etc.

9.24.1 `\bibitem`

Synopsis:

```
\bibitem[label]{cite_key}
```

The `\bibitem` command generates an entry labelled by *label*. If the *label* argument is missing, a number is automatically generated using the `enumi` counter. The *cite_key* is any sequence of letters, numbers, and punctuation symbols not containing a comma.

This command writes an entry to the ‘.aux’ file containing the item’s *cite_key* and label. When the ‘.aux’ file is read by the `\begin{document}` command, the item’s label is associated with *cite_key*, causing references to *cite_key* with a `\cite` command (see next section) to produce the associated label.

9.24.2 `\cite`

Synopsis:

```
\cite[subcite]{keys}
```

The *keys* argument is a list of one or more citation keys, separated by commas. This command generates an in-text citation to the references associated with *keys* by entries in the ‘.aux’ file.

The text of the optional *subcite* argument appears after the citation. For example, `\cite[p. ~314]{knuth}` might produce ‘[Knuth, p. 314]’.

9.24.3 `\nocite`

```
\nocite{key_list}
```

The `\nocite` command produces no text, but writes *key_list*, which is a list of one or more citation keys, on the ‘.aux’ file.

9.24.4 Using BibTeX

If you use the BibTeX program by Oren Patashnik (highly recommended if you need a bibliography of more than a couple of titles) to maintain your bibliography, you don't use the `thebibliography` environment (see [Section 9.24 \[thebibliography\]](#), page 33). Instead, you include the lines

```
\bibliographystyle{bibstyle}
\bibliography{bibfile1,bibfile2}
```

The `\bibliographystyle` command does not produce any output of its own. Rather, it defines the style in which the bibliography will be produced: *bibstyle* refers to a file *bibstyle*'.bst', which defines how your citations will look. The standard *style* names distributed with BibTeX are:

- `alpha` Sorted alphabetically. Labels are formed from name of author and year of publication.
- `plain` Sorted alphabetically. Labels are numeric.
- `unsrt` Like `plain`, but entries are in order of citation.
- `abbrv` Like `plain`, but more compact labels.

In addition, numerous other BibTeX style files exist tailored to the demands of various publications. See <http://www.ctan.org/tex-archive/biblio/bibtex/contrib>.

The `\bibliography` command is what actually produces the bibliography. The argument to `\bibliography` refers to files named '*bibfile*.bib', which should contain your database in BibTeX format. Only the entries referred to via `\cite` and `\nocite` will be listed in the bibliography.

9.25 theorem

Synopsis:

```
\begin{theorem}
theorem-text
\end{theorem}
```

The `theorem` environment produces "Theorem *n*" in boldface followed by *theorem-text*, where the numbering possibilities for *n* are described under `\newtheorem` (see [Section 13.6 \[\newtheorem\]](#), page 42).

9.26 titlepage

Synopsis:

```
\begin{titlepage}
text
\end{titlepage}
```

The `titlepage` environment creates a title page, i.e., a page with no printed page number or heading. It also causes the following page to be numbered page one. Formatting the title page is left to you. The `\today` command may be useful on title pages (see [Section 22.6 \[\today\]](#), page 75).

You can use the `\maketitle` command (see [Section 19.1 \[\maketitle\]](#), page 62) to produce a standard title page without a `titlepage` environment.

9.27 verbatim

Synopsis:

```
\begin{verbatim}
literal-text
\end{verbatim}
```

The `verbatim` environment is a paragraph-making environment in which \LaTeX produces exactly what you type in; for instance the `\` character produces a printed ‘\’. It turns \LaTeX into a typewriter with carriage returns and blanks having the same effect that they would on a typewriter.

The `verbatim` uses a monospaced typewriter-like font (`\tt`).

9.27.1 \verb

Synopsis:

```
\verbcharliteral-textchar
\verb*charliteral-textchar
```

The `\verb` command typesets *literal-text* as it is input, including special characters and spaces, using the typewriter (`\tt`) font. No spaces are allowed between `\verb` or `\verb*` and the delimiter *char*, which begins and ends the verbatim text. The delimiter must not appear in *literal-text*.

The `*-form` differs only in that spaces are printed with a “visible space” character. (Namely, `_`.)

9.28 verse

Synopsis:

```
\begin{verse}
line1 \\
line2 \\
...
\end{verse}
```

The `verse` environment is designed for poetry, though you may find other uses for it.

The margins are indented on the left and the right, paragraphs are not indented, and the text is not justified. Separate the lines of each stanza with `\\`, and use one or more blank lines to separate the stanzas.

10 Line breaking

The first thing \LaTeX does when processing ordinary text is to translate your input file into a sequence of glyphs and spaces. To produce a printed document, this sequence must be broken into lines (and these lines must be broken into pages).

\LaTeX usually does the line (and page) breaking for you, but in some environments, you do the line breaking yourself with the `\` command, and you can always manually force breaks.

10.1 `\[*][morespace]`

The `\` command tells \LaTeX to start a new line. It has an optional argument, *morespace*, that specifies how much extra vertical space is to be inserted before the next line. This can be a negative amount.

The `*` command is the same as the ordinary `\` command except that it tells \LaTeX not to start a new page after the line.

10.2 `\obeycr` & `\restorecr`

The `\obeycr` command makes a return in the input file (`^M`, internally) the same as `\` (followed by `\relax`). So each new line in the input will also be a new line in the output.

`\restorecr` restores normal line-breaking behavior.

10.3 `\newline`

The `\newline` command breaks the line at the present point, with no stretching of the text before it. It can only be used in paragraph mode.

10.4 `\-` (discretionary hyphen)

The `\-` command tells \LaTeX that it may hyphenate the word at that point. \LaTeX is very good at hyphenating, and it will usually find most of the correct hyphenation points, and almost never use an incorrect one. The `\-` command is used for the exceptional cases.

When you insert `\-` commands in a word, the word will only be hyphenated at those points and not at any of the hyphenation points that \LaTeX might otherwise have chosen.

10.5 `\fussy`

The declaration `\fussy` (which is the default) makes \TeX picky about line breaking. This usually avoids too much space between words, at the cost of an occasional overfull box.

This command cancels the effect of a previous `\sloppy` command (see [Section 10.6](#) [`\sloppy`], page 36).

10.6 `\sloppy`

The declaration `\sloppy` makes \TeX less fussy about line breaking. This will avoid overfull boxes, at the cost of loose interword spacing.

Lasts until a `\fussy` command is issued (see [Section 10.5](#) [`\fussy`], page 36).

10.7 `\hyphenation`

Synopsis:

```
\hyphenation{word-one word-two}
```

The `\hyphenation` command declares allowed hyphenation points with a - character in the given words. The words are separated by spaces. `TeX` will only hyphenate if the word matches exactly, no inflections are tried. Multiple `\hyphenation` commands accumulate. Some examples (the default `TeX` hyphenation patterns misses the hyphenations in these words):

```
\hyphenation{ap-pen-dix col-umns data-base data-bases}
```

10.8 `\linebreak` & `\nolinebreak`

Synopses:

```
\linebreak[priority]
```

```
\nolinebreak[priority]
```

By default, the `\linebreak` (`\nolinebreak`) command forces (prevents) a line break at the current position. For `\linebreak`, the spaces in the line are stretched out so that it extends to the right margin as usual.

With the optional argument *priority*, you can convert the command from a demand to a request. The *priority* must be a number from 0 to 4. The higher the number, the more insistent the request.

11 Page breaking

L^AT_EX starts new pages asynchronously, when enough material has accumulated to fill up a page. Usually this happens automatically, but sometimes you may want to influence the breaks.

11.1 `\cleardoublepage`

The `\cleardoublepage` command ends the current page and causes all figures and tables that have so far appeared in the input to be printed. In a two-sided printing style, it also makes the next page a right-hand (odd-numbered) page, producing a blank page if necessary.

11.2 `\clearpage`

The `\clearpage` command ends the current page and causes all figures and tables that have so far appeared in the input to be printed.

11.3 `\newpage`

The `\newpage` command ends the current page, but does not clear floats (see `\clearpage` above).

11.4 `\enlargethispage`

`\enlargethispage{size}`

`\enlargethispage*{size}`

Enlarge the `\textheight` for the current page by the specified amount; e.g. `\enlargethispage{\baselineskip}` will allow one additional line.

The starred form tries to squeeze the material together on the page as much as possible. This is normally used together with an explicit `\pagebreak`.

11.5 `\pagebreak` & `\nopagebreak`

Synopses:

`\pagebreak[priority]`

`\nopagebreak[priority]`

By default, the `\pagebreak` (`\nopagebreak`) command forces (prevents) a page break at the current position. With `\pagebreak`, the vertical space on the page is stretched out where possible so that it extends to the normal bottom margin.

With the optional argument *priority*, you can convert the `\pagebreak` command from a demand to a request. The number must be a number from 0 to 4. The higher the number, the more insistent the request is.

12 Footnotes

Footnotes can be produced in one of two ways. They can be produced with one command, the `\footnote` command. They can also be produced with two commands, the `\footnotemark` and the `\footnotetext` commands.

12.1 `\footnote`

Synopsis:

```
\footnote[number]{text}
```

The `\footnote` command places the numbered footnote *text* at the bottom of the current page. The optional argument *number* changes the default footnote number.

This command can only be used in outer paragraph mode; i.e., you cannot use it in sectioning commands like `\chapter`, in figures, tables or in a `tabular` environment. (See following sections.)

12.2 `\footnotemark`

With no optional argument, the `\footnotemark` command puts the current footnote number in the text. This command can be used in inner paragraph mode. You give the text of the footnote separately, with the `\footnotetext` command.

This command can be used to produce several consecutive footnote markers referring to the same footnote with

```
\footnotemark[\value{footnote}]
```

after the first `\footnote` command.

12.3 `\footnotetext`

Synopsis:

```
\footnotetext[number]{text}
```

The `\footnotetext` command places *text* at the bottom of the page as a footnote. This command can come anywhere after the `\footnotemark` command. The `\footnotetext` command must appear in outer paragraph mode.

The optional argument *number* changes the default footnote number.

12.4 Symbolic footnotes

If you want to use symbols for footnotes, rather than increasing numbers, redefine `\thefootnote` like this:

```
\renewcommand{\thefootnote}{\fnsymbol{footnote}}
```

The `\fnsymbol` command produces a predefined series of symbols (see [Section 14.1](#) [`\alph` `\Alph` `\arabic` `\roman` `\Roman` `\fnsymbol`], page 44). If you want to use a different symbol as your footnote mark, you'll need to also redefine `\@fnsymbol`.

12.5 Footnote parameters

`\footnoterule`

Produces the rule separating the main text on a page from the page's footnotes. Default dimensions: `0.4pt` thick (or wide), and `0.4\columnwidth` long in the standard document classes (except slides, where it does not appear).

`\footnotesep`

The height of the strut placed at the beginning of the footnote. By default, this is set to the normal strut for `\footnotesize` fonts (see [Section 5.2 \[Font sizes\]](#), [page 8](#)), therefore there is no extra space between footnotes. This is `'6.65pt'` for `'10pt'`, `'7.7pt'` for `'11pt'`, and `'8.4pt'` for `'12pt'`.

13 Definitions

L^AT_EX has support for making new commands of many different kinds.

13.1 `\newcommand` & `\renewcommand`

`\newcommand` and `\renewcommand` define and redefine a command, respectively. Synopses:

```

\newcommand{cmd}[nargs]{defn}
\renewcommand{cmd}[nargs]{defn}
\newcommand{cmd}[nargs][default]{defn}
\renewcommand{cmd}[nargs][default]{defn}

```

cmd The command name beginning with `\`. For `\newcommand`, it must not be already defined and must not begin with `\end`; for `\renewcommand`, it must already be defined.

nargs An optional integer from 1 to 9 specifying the number of arguments that the command will take. The default is for the command to have no arguments.

default If this optional parameter is present, it means that the command's first argument is optional. When the new command is called, the default value of the optional argument (i.e., if it is not specified in the call) is the string `'def'`.

defn The text to be substituted for every occurrence of *cmd*; a construct of the form `#n` in *defn* is replaced by the text of the *n*th argument.

13.2 `\newcounter`

Synopsis:

```
\newcounter{cnt}[countername]
```

The `\newcounter` command defines a new counter named *cnt*. The new counter is initialized to zero.

Given the optional argument [*countername*], *cnt* will be reset whenever *countername* is incremented.

See [Chapter 14 \[Counters\]](#), page 44, for more information about counters.

13.3 `\newlength`

Synopsis:

```
\newlength{\arg}
```

The `\newlength` command defines the mandatory argument as a `length` command with a value of 0in. The argument must be a control sequence, as in `\newlength{\foo}`. An error occurs if `\foo` is already defined.

See [Chapter 15 \[Lengths\]](#), page 46, for how to set the new length to a nonzero value, and for more information about lengths in general.

13.4 `\newsavebox`

Synopsis:

```
\newsavebox{cmd}
```

Defines `\cmd`, which must be a command name not already defined, to refer to a new bin for storing boxes.

13.5 `\newenvironment` & `\renewenvironment`

Synopses:

```
\newenvironment{env}[nargs]{begdef}{enddef}
\newenvironment{env}[nargs][default]{begdef}{enddef}
\renewenvironment{env}[nargs]{begdef}{enddef}
```

These commands define or redefine an environment `env`, that is, `\begin{env} ... \end{env}`.

- env* The name of the environment. For `\newenvironment`, *env* must not be an existing environment, and the command `\env` must be undefined. For `\renewenvironment`, *env* must be the name of an existing environment.
- nargs* An integer from 1 to 9 denoting the number of arguments of the newly-defined environment. The default is no arguments.
- default* If this is specified, the first argument is optional, and *default* gives the default value for that argument.
- begdef* The text expanded at every occurrence of `\begin{env}`; a construct of the form `#n` in *begdef* is replaced by the text of the *n*th argument.
- enddef* The text expanded at every occurrence of `\end{env}`. It may not contain any argument parameters.

13.6 `\newtheorem`

```
\newtheorem{newenv}{label}[within]
\newtheorem{newenv}[numbered_like]{label}
```

This command defines a theorem-like environment. Arguments:

- newenv* The name of the environment to be defined; must not be the name of an existing environment or otherwise defined.
- label* The text printed at the beginning of the environment, before the number. For example, ‘Theorem’.
- numbered_like*
(Optional.) The name of an already defined theorem-like environment; the new environment will be numbered just like *numbered_like*.
- within* (Optional.) The name of an already defined counter, a sectional unit. The new theorem counter will be reset at the same time as the *within* counter.

At most one of *numbered_like* and *within* can be specified, not both.

13.7 `\newfont`

Synopsis:

```
\newfont{cmd}{fontname}
```

Defines a control sequence `\cmd`, which must not already be defined, to make `fontname` be the current font. The file looked for on the system is named '`fontname.tfm`'.

This is a low-level command for setting up to use an individual font. More commonly, fonts are defined in families through '`.fd`' files.

13.8 `\protect`

Footnotes, line breaks, any command that has an optional argument, and many more are so-called *fragile* commands. When a fragile command is used in certain contexts, called *moving arguments*, it must be preceded by `\protect`. In addition, any fragile commands within the arguments must have their own `\protect`.

Some examples of moving arguments are `\caption` (see Section 9.10 [figure], page 19), `\thanks` (see Section 19.1 [`\maketitle`], page 62), and expressions in `tabular` and `array` environments (see Section 9.23 [tabular], page 30).

Commands which are not fragile are called *robust*. They must not be preceded by `\protect`.

See also:

<http://www-h.eng.cam.ac.uk/help/tpl/textprocessing/teTeX/latex/latex2e-html/fragile.html>
<http://www.tex.ac.uk/cgi-bin/texfaq2html?label=protect>

14 Counters

Everything L^AT_EX numbers for you has a counter associated with it. The name of the counter is the same as the name of the environment or command that produces the number, except with no `\`. (`enumi`–`enumiv` are used for the nested enumerate environment.) Below is a list of the counters used in L^AT_EX's standard document classes to control numbering.

<code>part</code>	<code>paragraph</code>	<code>figure</code>	<code>enumi</code>
<code>chapter</code>	<code>subparagraph</code>	<code>table</code>	<code>enumii</code>
<code>section</code>	<code>page</code>	<code>footnote</code>	<code>enumiii</code>
<code>subsection</code>	<code>equation</code>	<code>mpfootnote</code>	<code>enumiv</code>
<code>subsubsection</code>			

14.1 `\alph` `\Alph` `\arabic` `\roman` `\Roman` `\fnsymbol`: Printing counters

All of these commands take a single counter as an argument, for instance, `\alph{enumi}`.

`\alph` prints *counter* using lowercase letters: ‘a’, ‘b’, ...

`\Alph` uses uppercase letters: ‘A’, ‘B’, ...

`\arabic` uses Arabic numbers: ‘1’, ‘2’, ...

`\roman` uses lowercase roman numerals: ‘i’, ‘ii’, ...

`\Roman` uses uppercase roman numerals: ‘I’, ‘II’, ...

`\fnsymbol`

prints the value of *counter* in a specific sequence of nine symbols (conventionally used for labeling footnotes). The value of *counter* must be between 1 and 9, inclusive.

Here are the symbols: * † ‡ § ¶ || ** †† ‡‡

14.2 `\usecounter{counter}`

Synopsis:

```
\usecounter{counter}
```

The `\usecounter` command is used in the second argument of the `list` environment to specify *counter* to be used to number the list items.

14.3 `\value{counter}`

Synopsis:

```
\value{counter}
```

The `\value` command produces the value of *counter*. It can be used anywhere L^AT_EX expects a number, for example:

```
\setcounter{myctr}{3}
\addtocounter{myctr}{1}
\hspace{\value{myctr}\parindent}
```

14.4 `\setcounter{counter}{value}`

Synopsis:

```
\setcounter{\counter}{value}
```

The `\setcounter` command sets the value of `\counter` to the `value` argument.

14.5 `\addtocounter{counter}{value}`

The `\addtocounter` command increments `counter` by the amount specified by the `value` argument, which may be negative.

14.6 `\refstepcounter{counter}`

The `\refstepcounter` command works in the same way as `\stepcounter` See [Section 14.7](#) [`\stepcounter`], [page 45](#), except it also defines the current `\ref` value to be the result of `\thecounter`.

14.7 `\stepcounter{counter}`

The `\stepcounter` command adds one to `counter` and resets all subsidiary counters.

14.8 `\day \month \year`: Predefined counters

\LaTeX defines counters for the day of the month (`\day`, 1–31), month of the year (`\month`, 1–12), and year (`\year`, Common Era). When \TeX starts up, they are set to the current values on the system where \TeX is running. They are not updated as the job progresses.

The related command `\today` produces a string representing the current day (see [Section 22.6](#) [`\today`], [page 75](#)).

15 Lengths

A `length` is a measure of distance. Many \LaTeX commands take a length as an argument.

15.1 `\setlength{\len}{value}`

The `\setlength` sets the value of `\len` to the *value* argument, which can be expressed in any units that \LaTeX understands, i.e., inches (`in`), millimeters (`mm`), points (`pt`), big points (`bp`), etc.

15.2 `\addtolength{\len}{amount}`

The `\addtolength` command increments a “length command” `\len` by the amount specified in the *amount* argument, which may be negative.

15.3 `\settodepth`

```
\settodepth{\gnat}{text}
```

The `\settodepth` command sets the value of a `length` command equal to the depth of the `text` argument.

15.4 `\settoheight`

```
\settoheight{\gnat}{text}
```

The `\settoheight` command sets the value of a `length` command equal to the height of the `text` argument.

15.5 `\settowidth{\len}{text}`

The `\settowidth` command sets the value of the command `\len` to the width of the *text* argument.

15.6 Predefined lengths

```
\width
```

```
\height
```

```
\depth
```

```
\totalheight
```

These length parameters can be used in the arguments of the box-making commands (see [Chapter 21 \[Boxes\]](#), page 67). They specify the natural width, etc., of the text in the box. `\totalheight` equals `\height + \depth`. To make a box with the text stretched to double the natural size, e.g., say

```
\makebox[2\width]{Get a stretcher}
```

16 Making paragraphs

A paragraph is ended by one or more completely blank lines—lines not containing even a %. A blank line should not appear where a new paragraph cannot be started, such as in math mode or in the argument of a sectioning command.

16.1 `\indent`

`\indent` produces a horizontal space whose width equals the width of the `\parindent` length, the normal paragraph indentation. It is used to add paragraph indentation where it would otherwise be suppressed.

The default value for `\parindent` is 1em in two-column mode, otherwise 15pt for 10pt documents, 17pt for 11pt, and 1.5em for 12pt.

16.2 `\noindent`

When used at the beginning of the paragraph, `\noindent` suppresses any paragraph indentation. It has no effect when used in the middle of a paragraph.

16.3 `\parskip`

`\parskip` is a rubber length defining extra vertical space added before each paragraph. The default is 0pt plus1pt.

16.4 Marginal notes

Synopsis:

```
\marginpar[left]{right}
```

The `\marginpar` command creates a note in the margin. The first line of the note will have the same baseline as the line in the text where the `\marginpar` occurs.

When you only specify the mandatory argument *right*, the text will be placed

- in the right margin for one-sided layout;
- in the outside margin for two-sided layout;
- in the nearest margin for two-column layout.

The command `\reversemarginpar` places subsequent marginal notes in the opposite (inside) margin. `\normalmarginpar` places them in the default position.

When you specify both arguments, *left* is used for the left margin, and *right* is used for the right margin.

The first word will normally not be hyphenated; you can enable hyphenation there by beginning the node with `\hspace{0pt}`.

These parameters affect the formatting of the note:

```
\marginparpush
```

Minimum vertical space between notes; default ‘7pt’ for ‘12pt’ documents, ‘5pt’ else.

`\marginparsep`

Horizontal space between the main text and the note; default ‘11pt’ for ‘10pt’ documents, ‘10pt’ else.

`\marginparwidth`

Width of the note itself; default for a one-sided ‘10pt’ document is ‘90pt’, ‘83pt’ for ‘11pt’, and ‘68pt’ for ‘12pt’; ‘17pt’ more in each case for a two-sided document. In two column mode, the default is ‘48pt’.

The standard \LaTeX routine for marginal notes does not prevent notes from falling off the bottom of the page.

17 Math formulas

There are three environments that put L^AT_EX in math mode:

`math` For formulas that appear right in the text.

`displaymath`
For formulas that appear on their own line.

`equation` The same as the `displaymath` environment except that it adds an equation number in the right margin.

The `math` environment can be used in both paragraph and LR mode, but the `displaymath` and `equation` environments can be used only in paragraph mode. The `math` and `displaymath` environments are used so often that they have the following short forms:

`\(...\)` instead of `\begin{math}...\end{math}`
`\[...\]` instead of `\begin{displaymath}...\end{displaymath}`

In fact, the `math` environment is so common that it has an even shorter form:

`$... $` instead of `\(...\)`

The `\boldmath` command changes math letters and symbols to be in a bold font. It is used *outside* of math mode. Conversely, the `\unboldmath` command changes math glyphs to be in a normal font; it too is used *outside* of math mode.

The `\displaystyle` declaration forces the size and style of the formula to be that of `displaymath`, e.g., with limits above and below summations. For example

```
\displaystyle \sum_{n=0}^{\infty} x_n
```

17.1 Subscripts & superscripts

To get an expression *exp* to appear as a subscript, you just type `_{exp}`. To get *exp* to appear as a superscript, you type `^{exp}`. L^AT_EX handles superscripted superscripts and all of that stuff in the natural way. It even does the right thing when something has both a subscript and a superscript.

17.2 Math symbols

L^AT_EX provides almost any mathematical symbol you're likely to need. The commands for generating them can be used only in math mode. For example, if you include `\pi` in your source, you will get the pi symbol (π) in your output.

| \l

`\aleph` \aleph

`\alpha` α

`\amalg` \amalg (binary operation)

`\angle` \angle

`\approx` \approx (relation)

`\ast` \ast (binary operation)

<code>\asymp</code>	\asymp (relation)
<code>\backslash</code>	\backslash (delimiter)
<code>\beta</code>	β
<code>\bigcap</code>	\bigcap
<code>\bigcirc</code>	\bigcirc (binary operation)
<code>\bigcup</code>	\bigcup
<code>\bigodot</code>	\bigodot
<code>\bigoplus</code>	\bigoplus
<code>\bigotimes</code>	\bigotimes
<code>\bigtriangledown</code>	\bigtriangledown (binary operation)
<code>\bigtriangleup</code>	\bigtriangleup (binary operation)
<code>\bigsqcup</code>	\bigsqcup
<code>\biguplus</code>	\biguplus
<code>\bigvee</code>	\bigvee
<code>\bigwedge</code>	\bigwedge
<code>\bot</code>	\perp
<code>\bowtie</code>	\bowtie (relation)
<code>\Box</code>	(square open box symbol)
<code>\bullet</code>	\bullet (binary operation)
<code>\cap</code>	\cap (binary operation)
<code>\cdot</code>	\cdot (binary operation)
<code>\chi</code>	χ
<code>\circ</code>	\circ (binary operation)
<code>\clubsuit</code>	\clubsuit
<code>\cong</code>	\cong (relation)
<code>\coprod</code>	\coprod

<code>\cup</code>	\cup (binary operation)
<code>\dagger</code>	\dagger (binary operation)
<code>\dashv</code>	\dashv (relation)
<code>\ddagger</code>	\ddagger (binary operation)
<code>\Delta</code>	Δ
<code>\delta</code>	δ
<code>\Diamond</code>	bigger \diamond
<code>\diamond</code>	\diamond (binary operation)
<code>\diamondsuit</code>	\diamondsuit
<code>\div</code>	\div (binary operation)
<code>\doteq</code>	\doteq (relation)
<code>\downarrow</code>	\downarrow (delimiter)
<code>\Downarrow</code>	\Downarrow (delimiter)
<code>\ell</code>	ℓ
<code>\emptyset</code>	\emptyset
<code>\epsilon</code>	ϵ
<code>\equiv</code>	\equiv (relation)
<code>\eta</code>	η
<code>\exists</code>	\exists
<code>\flat</code>	\flat
<code>\forall</code>	\forall
<code>\frown</code>	\frown (relation)
<code>\Gamma</code>	Γ
<code>\gamma</code>	γ
<code>\ge</code>	\geq
<code>\geq</code>	\geq (relation)
<code>\gets</code>	\leftarrow
<code>\gg</code>	\gg (relation)
<code>\hbar</code>	\hbar
<code>\heartsuit</code>	\heartsuit

<code>\hookleftarrow</code>	\hookleftarrow
<code>\hookrightarrow</code>	\hookrightarrow
<code>\iff</code>	\iff
<code>\Im</code>	\Im
<code>\in</code>	\in (relation)
<code>\infty</code>	∞
<code>\int</code>	\int
<code>\iota</code>	ι
<code>\Join</code>	condensed bowtie symbol (relation)
<code>\kappa</code>	κ
<code>\Lambda</code>	Λ
<code>\lambda</code>	λ
<code>\land</code>	\land
<code>\langle</code>	\langle (delimiter)
<code>\lbrace</code>	\lbrace (delimiter)
<code>\lbrack</code>	\lbrack (delimiter)
<code>\lceil</code>	\lceil (delimiter)
<code>\le</code>	\leq
<code>\leadsto</code>	
<code>\Leftarrow</code>	\Leftarrow
<code>\leftarrow</code>	\leftarrow
<code>\leftharpoondown</code>	\leftharpoondown
<code>\leftharpoonup</code>	\leftharpoonup
<code>\Leftrightarrow</code>	\Leftrightarrow
<code>\leftrightharpoonup</code>	\leftrightharpoonup
<code>\leq</code>	\leq (relation)
<code>\lfloor</code>	\lfloor (delimiter)

<code>\lhd</code>	(left-pointing arrow head)
<code>\ll</code>	\ll (relation)
<code>\lnot</code>	\neg
<code>\longleftarrow</code>	\longleftarrow
<code>\longlefttrightarrow</code>	\longleftrightarrow
<code>\longmapsto</code>	\longmapsto
<code>\longrightarrow</code>	\longrightarrow
<code>\lor</code>	\vee
<code>\mapsto</code>	\mapsto
<code>\mho</code>	
<code>\mid</code>	$ $ (relation)
<code>\models</code>	\models (relation)
<code>\mp</code>	\mp (binary operation)
<code>\mu</code>	μ
<code>\nabla</code>	∇
<code>\natural</code>	\natural
<code>\ne</code>	\neq
<code>\nearrow</code>	\nearrow
<code>\neg</code>	\neg
<code>\neq</code>	\neq (relation)
<code>\ni</code>	\ni (relation)
<code>\not</code>	Overstrike a following operator with a $/$, as in \neq .
<code>\notin</code>	\notin
<code>\nu</code>	ν
<code>\nwarrow</code>	\nwarrow
<code>\odot</code>	\odot (binary operation)
<code>\oint</code>	\oint
<code>\Omega</code>	Ω
<code>\omega</code>	ω
<code>\ominus</code>	\ominus (binary operation)

<code>\oplus</code>	\oplus (binary operation)
<code>\oslash</code>	\oslash (binary operation)
<code>\otimes</code>	\otimes (binary operation)
<code>\owns</code>	\ni
<code>\parallel</code>	\parallel (relation)
<code>\partial</code>	∂
<code>\perp</code>	\perp (relation)
<code>\phi</code>	ϕ
<code>\Pi</code>	Π
<code>\pi</code>	π
<code>\pm</code>	\pm (binary operation)
<code>\prec</code>	\prec (relation)
<code>\preceq</code>	\preceq (relation)
<code>\prime</code>	$'$
<code>\prod</code>	\prod
<code>\propto</code>	\propto (relation)
<code>\Psi</code>	Ψ
<code>\psi</code>	ψ
<code>\rangle</code>	\rangle (delimiter)
<code>\rbrace</code>	$\}$ (delimiter)
<code>\rbrack</code>	$\]$ (delimiter)
<code>\rceil</code>	\lceil (delimiter)
<code>\Re</code>	\Re
<code>\rfloor</code>	\rfloor
<code>\rhd</code>	(binary operation)
<code>\rho</code>	ρ
<code>\Rightarrow</code>	\Rightarrow
<code>\rightarrow</code>	\rightarrow
<code>\rightharpoondown</code>	\searrow
<code>\rightharpoonup</code>	\nearrow

<code>\rightleftharpoons</code>	\rightleftharpoons
<code>\searrow</code>	\searrow
<code>\setminus</code>	\setminus (binary operation)
<code>\sharp</code>	\sharp
<code>\Sigma</code>	Σ
<code>\sigma</code>	σ
<code>\sim</code>	\sim (relation)
<code>\simeq</code>	\simeq (relation)
<code>\smallint</code>	\int
<code>\smile</code>	\smile (relation)
<code>\spadesuit</code>	\spadesuit
<code>\sqcap</code>	\sqcap (binary operation)
<code>\sqcup</code>	\sqcup (binary operation)
<code>\sqsubset</code>	(relation)
<code>\sqsubseteq</code>	\sqsubseteq (relation)
<code>\sqsupset</code>	(relation)
<code>\sqsupseteq</code>	\sqsupseteq (relation)
<code>\star</code>	\star (binary operation)
<code>\subset</code>	\subset (relation)
<code>\subseteq</code>	\subseteq (relation)
<code>\succ</code>	\succ (relation)
<code>\succeq</code>	\succeq (relation)
<code>\sum</code>	\sum
<code>\supset</code>	\supset (relation)
<code>\supseteq</code>	\supseteq (relation)
<code>\surd</code>	\surd

<code>\swarrow</code>	\swarrow
<code>\tau</code>	τ
<code>\theta</code>	θ
<code>\times</code>	\times (binary operation)
<code>\to</code>	\rightarrow
<code>\top</code>	\top
<code>\triangle</code>	\triangle
<code>\triangleleft</code>	\triangleleft (binary operation)
<code>\triangleright</code>	\triangleright (binary operation)
<code>\unlhd</code>	left-pointing arrowhead with line under (binary operation)
<code>\unrhd</code>	right-pointing arrowhead with line under (binary operation)
<code>\Uparrow</code>	\Uparrow (delimiter)
<code>\uparrow</code>	\uparrow (delimiter)
<code>\Updownarrow</code>	\Updownarrow (delimiter)
<code>\updownarrow</code>	\updownarrow (delimiter)
<code>\uplus</code>	\uplus (binary operation)
<code>\Upsilon</code>	Υ
<code>\upsilon</code>	υ
<code>\varepsilon</code>	ε
<code>\varphi</code>	φ
<code>\varpi</code>	ϖ
<code>\varrho</code>	ϱ
<code>\varsigma</code>	ς
<code>\vartheta</code>	ϑ
<code>\vdash</code>	\vdash (relation)
<code>\vee</code>	\vee (binary operation)
<code>\Vert</code>	\parallel (delimiter)

<code>\vert</code>	(delimiter)
<code>\wedge</code>	\wedge (binary operation)
<code>\wp</code>	\wp
<code>\wr</code>	\wr (binary operation)
<code>\Xi</code>	Ξ
<code>\xi</code>	ξ
<code>\zeta</code>	ζ

17.3 Math functions

These commands produce roman function names in math mode with proper spacing.

<code>\arccos</code>	arccos
<code>\arcsin</code>	arcsin
<code>\arctan</code>	arctan
<code>\arg</code>	arg
<code>\bmod</code>	Binary modulo operator ($x \bmod y$)
<code>\cos</code>	cos
<code>\cosh</code>	cosh
<code>\cot</code>	cos
<code>\coth</code>	cosh
<code>\csc</code>	csc
<code>\deg</code>	deg
<code>\det</code>	deg
<code>\dim</code>	dim
<code>\exp</code>	exp
<code>\gcd</code>	gcd
<code>\hom</code>	hom
<code>\inf</code>	inf
<code>\ker</code>	ker
<code>\lg</code>	lg
<code>\lim</code>	lim
<code>\liminf</code>	lim inf
<code>\limsup</code>	lim sup
<code>\ln</code>	ln

<code>\log</code>	log
<code>\max</code>	max
<code>\min</code>	min
<code>\pmod</code>	parenthesized modulus, as in $(\pmod{2}^n - 1)$
<code>\Pr</code>	Pr
<code>\sec</code>	sec
<code>\sin</code>	sin
<code>\sinh</code>	sinh
<code>\sup</code>	sup
<code>\tan</code>	tan
<code>\tanh</code>	tanh

17.4 Math accents

\LaTeX provides a variety of commands for producing accented letters in math. These are different from accents in normal text (see [Section 22.3 \[Accents\]](#), page 73).

<code>\acute</code>	Math acute accent: \acute{x} .
<code>\bar</code>	Math bar-over accent: \bar{x} .
<code>\breve</code>	Math breve accent: \breve{x} .
<code>\check</code>	Math háček (check) accent: \check{x} .
<code>\ddot</code>	Math dieresis accent: \ddot{x} .
<code>\dot</code>	Math dot accent: \dot{x} .
<code>\grave</code>	Math grave accent: \grave{x} .
<code>\hat</code>	Math hat (circumflex) accent: \hat{x} .
<code>\imath</code>	Math dotless i.
<code>\jmath</code>	Math dotless j.
<code>\mathring</code>	Math ring accent: \mathring{x} .
<code>\tilde</code>	Math tilde accent: \tilde{x} .
<code>\vec</code>	Math vector symbol: \vec{x} .
<code>\widehat</code>	Math wide hat accent: $\widehat{x+y}$.
<code>\widetilde</code>	Math wide tilde accent: $\widetilde{x+y}$.

17.5 Spacing in math mode

In a `math` environment, \LaTeX ignores the spaces you type and puts in the spacing according to the normal rules for mathematics texts. If you want different spacing, \LaTeX provides the following commands for use in math mode:

- `\;` A thick space ($\frac{5}{18}$ quad).
- `\:`
- `\>` Both of these produce a medium space ($\frac{2}{9}$ quad).
- `\,` A thin space ($\frac{1}{6}$ quad); not restricted to math mode.
- `\!` A negative thin space ($-\frac{1}{6}$ quad).

17.6 Math miscellany

- `*` A “discretionary” multiplication symbol, at which a line break is allowed.
- `\cdots` A horizontal ellipsis with the dots raised to the center of the line. As in: ‘ \cdots ’.
- `\ddots` A diagonal ellipsis: ‘ \ddots ’.
- `\frac{num}{den}`
Produces the fraction `num` divided by `den`.
eg. $\frac{1}{4}$
- `\left delim1 ... \right delim2`
The two delimiters need not match; ‘.’ acts as a null delimiter, producing no output. The delimiters are sized according to the math in between. Example: `\left(\sum_{i=1}^{10} a_i \right)`.
- `\overbrace{text}`
Generates a brace over `text`. For example, $x + \overbrace{\cdots}^{k \text{ times}} + x$.
- `\overline{text}`
Generates a horizontal line over `tex`. For example, $\overline{x + y}$.
- `\sqrt[root]{arg}`
Produces the representation of the square root of `arg`. The optional argument `root` determines what root to produce. For example, the cube root of `x+y` would be typed as `\sqrt[3]{x+y}`. In \TeX , the result looks like this: $\sqrt[3]{x} + y$.
- `\stackrel{text}{relation}`
Puts `text` above `relation`. For example, `\stackrel{f}{\longrightarrow}`. In \TeX , the result looks like this: \xrightarrow{f} .
- `\underbrace{math}`
Generates `math` with a brace underneath. In \TeX , the result looks like this:
$$\underbrace{x + y + z}_{>0}$$
- `\underline{text}`
Causes `text`, which may be either math mode or not, to be underlined. The line is always below the text, taking account of descenders. In \TeX , the result looks like this: \underline{xyz}

`\vdots` Produces a vertical ellipsis. In $\text{T}_{\text{E}}\text{X}$, the result looks like this: \vdots .

18 Modes

When \LaTeX is processing your input text, it is always in one of three modes:

- Paragraph mode
- Math mode
- Left-to-right mode, called LR mode for short

\LaTeX changes mode only when it goes up or down a staircase to a different level, though not all level changes produce mode changes. Mode changes occur only when entering or leaving an environment, or when \LaTeX is processing the argument of certain text-producing commands.

“Paragraph mode” is the most common; it’s the one \LaTeX is in when processing ordinary text. In that mode, \LaTeX breaks your text into lines and breaks the lines into pages. \LaTeX is in “math mode” when it’s generating a mathematical formula. In “LR mode”, as in paragraph mode, \LaTeX considers the output that it produces to be a string of words with spaces between them. However, unlike paragraph mode, \LaTeX keeps going from left to right; it never starts a new line in LR mode. Even if you put a hundred words into an \mbox , \LaTeX would keep typesetting them from left to right inside a single box, and then complain because the resulting box was too wide to fit on the line.

\LaTeX is in LR mode when it starts making a box with an \mbox command. You can get it to enter a different mode inside the box - for example, you can make it enter math mode to put a formula in the box. There are also several text-producing commands and environments for making a box that put \LaTeX in paragraph mode. The box make by one of these commands or environments will be called a **parbox**. When \LaTeX is in paragraph mode while making a box, it is said to be in “inner paragraph mode”. Its normal paragraph mode, which it starts out in, is called “outer paragraph mode”.

19 Page styles

The `\documentclass` command determines the size and position of the page’s head and foot. The page style determines what goes in them.

19.1 `\maketitle`

The `\maketitle` command generates a title on a separate title page—except in the `article` class, where the title is placed at the top of the first page. Information used to produce the title is obtained from the following declarations:

`\author{name \and name2}`

The `\author` command declares the document author(s), where the argument is a list of authors separated by `\and` commands. Use `\\` to separate lines within a single author’s entry—for example, to give the author’s institution or address.

`\date{text}`

The `\date` command declares *text* to be the document’s date. With no `\date` command, the current date (see [Section 22.6](#) [`\today`], page 75) is used.

`\thanks{text}`

The `\thanks` command produces a `\footnote` to the title, usually used for credit acknowledgements.

`\title{text}`

The `\title` command declares *text* to be the title of the document. Use `\\` to force a line break, as usual.

19.2 `\pagenumbering`

Synopsis:

`\pagenumbering{style}`

Specifies the style of page numbers, according to *style*:

<code>arabic</code>	arabic numerals
<code>roman</code>	lowercase Roman numerals
<code>Roman</code>	uppercase Roman numerals
<code>alph</code>	lowercase letters
<code>Alph</code>	uppercase letters

19.3 `\pagestyle`

Synopsis:

`\pagestyle{style}`

The `\pagestyle` command specifies how the headers and footers are typeset from the current page onwards. Values for *style*:

<code>plain</code>	Just a plain page number.
--------------------	---------------------------

- empty** Empty headers and footers, e.g., no page numbers.
- headings** Put running headers on each page. The document style specifies what goes in the headers.
- myheadings** Custom headers, specified via the `\markboth` or the `\markright` commands.

Here are the descriptions of `\markboth` and `\markright`:

`\markboth{left}{right}`

Sets both the left and the right heading. A “left-hand heading” (*left*) is generated by the last `\markboth` command before the end of the page, while a “right-hand heading” (*right*) is generated by the first `\markboth` or `\markright` that comes on the page if there is one, otherwise by the last one before the page.

`\markright{right}`

Sets the right heading, leaving the left heading unchanged.

19.4 `\thispagestyle{style}`

The `\thispagestyle` command works in the same manner as the `\pagestyle` command (see previous section) except that it changes to *style* for the current page only.

20 Spaces

L^AT_EX has many ways to produce white (or filled) space.

Another space-producing command is `\`, to produce a “thin” space (usually 1/6 quad). It can be used in text mode, but is more often useful in math mode (see [Section 17.5 \[Spacing in math mode\]](#), page 59).

20.1 `\hspace`

Synopsis:

```
\hspace[*]{length}
```

The `\hspace` command adds horizontal space. The *length* argument can be expressed in any terms that L^AT_EX understands: points, inches, etc. It is a rubber length. You can add both negative and positive space with an `\hspace` command; adding negative space is like backspacing.

L^AT_EX normally removes horizontal space that comes at the beginning or end of a line. To preserve this space, use the optional `*` form.

20.2 `\hfill`

The `\hfill` fill command produces a “rubber length” which has no natural space but can stretch or shrink horizontally as far as needed.

The `\fill` parameter is the rubber length itself (technically, the glue value ‘`Opt plus1fill`’); thus, `\hspace\fill` is equivalent to `\hfill`.

20.3 `\SPACE`

The `\ (space)` command produces a normal interword space. It’s useful after punctuation which shouldn’t end a sentence. For example `Knuth’s article in Proc.\ Amer.\ Math.\ Soc.\ is fundamental`. It is also often used after control sequences, as in `\TeX\ is a nice system`.

In normal circumstances, `\tab` and `\newline` are equivalent to `\ .`

20.4 `\@`

The `\@` command makes the following punctuation character end a sentence even if it normally would not. This is typically used after a capital letter. Here are side-by-side examples with and without `\@`:

```
... in C\@. Pascal, though ...
... in C. Pascal, though ...
```

produces

```
... in C. Pascal, though ... ... in C. Pascal, though ...
```

20.5 `\thinspace`

`\thinspace` produces an unbreakable and unstretchable space that is 1/6 of an em. This is the proper space to use in nested quotes, as in ‘ ’’.

20.6 `\/`

The `\/` command produces an *italic correction*. This is a small space defined by the font designer for a given character, to avoid the character colliding with whatever follows. The italic *f* character typically has a large italic correction value.

If the following character is a period or comma, it's not necessary to insert an italic correction, since those punctuation symbols have a very small height. However, with semicolons or colons, as well as normal letters, it can help. Compare *f: f;* with *f: f.*

Despite the name, roman characters can also have an italic correction. Compare pdf \TeX with pdf \TeX .

20.7 `\hrulefill`

The `\hrulefill` fill command produces a “rubber length” which can stretch or shrink horizontally. It will be filled with a horizontal rule.

20.8 `\dotfill`

The `\dotfill` command produces a “rubber length” that fills with dots instead of just white space.

20.9 `\addvspace`

`\addvspace{length}`

The `\addvspace` command normally adds a vertical space of height `length`. However, if vertical space has already been added to the same point in the output by a previous `\addvspace` command, then this command will not add more space than needed to make the natural length of the total vertical space equal to `length`.

20.10 `\bigskip` `\medskip` `\smallskip`

These commands produce a given amount of space.

`\bigskip` The same as `\vspace{bigskipamount}`, ordinarily about one line space (with stretch and shrink).

`\medskip` The same as `\vspace{medskipamount}`, ordinarily about half of a line space (with stretch and shrink).

`\smallskip`

The same as `\vspace{smallskipamount}`, ordinarily about a quarter of a line space (with stretch and shrink).

The `\...amount` parameters are determined by the document class.

20.11 `\vfill`

The `\vfill` fill command produces a rubber length (glue) which can stretch or shrink vertically as far as needed. It's equivalent to `\vspace{\fill}` (see [Section 20.2](#) [`\hfill`], [page 64](#)).

20.12 `\vspace[*]{length}`

Synopsis:

```
\vspace[*]{length}
```

The `\vspace` command adds the vertical space *length*, i.e., a rubber length. *length* can be negative or positive.

Ordinarily, \LaTeX removes vertical space added by `\vspace` at the top or bottom of a page. With the optional `*` argument, the space is not removed.

21 Boxes

All the predefined length parameters (see [Section 15.6 \[Predefined lengths\], page 46](#)) can be used in the arguments of the box-making commands.

21.1 `\mbox{text}`

The `\mbox` command creates a box just wide enough to hold the text created by its argument. The *text* is not broken into lines, so it can be used to prevent hyphenation.

21.2 `\fbox` and `\framebox`

Synopses:

```
\fbox{text}
\framebox[width][position]{text}
```

The `\fbox` and `\framebox` commands are like `\mbox`, except that they put a frame around the outside of the box being created.

In addition, the `\framebox` command allows for explicit specification of the box width with the optional *width* argument (a dimension), and positioning with the optional *position* argument.

Both commands produce a rule of thickness `\fboxrule` (default ‘.4pt’), and leave a space of `\fboxsep` (default ‘3pt’) between the rule and the contents of the box.

See [Section 9.18.3 \[`\framebox` \(picture\)\], page 26](#), for the `\framebox` command in the `picture` environment.

21.3 `lrbox`

```
\begin{lrbox}{cmd} text \end{lrbox}
```

This is the environment form of `\sbox`.

The text inside the environment is saved in the box `cmd`, which must have been declared with `\newsavebox`.

21.4 `\makebox`

Synopsis:

```
\makebox[width][position]{text}
```

The `\makebox` command creates a box just wide enough to contain the *text* specified. The width of the box is specified by the optional *width* argument. The position of the text within the box is determined by the optional *position* argument, which may take the following values:

- | | |
|---|---|
| c | Centered (default). |
| l | Flush left. |
| r | Flush right. |
| s | Stretch (justify) across entire <i>width</i> ; <i>text</i> must contain stretchable space for this to work. |

`\makebox` is also used within the picture environment see [Section 9.18.2 \[`\makebox \(picture\)`\]](#), page 26.

21.5 `\parbox`

Synopsis:

```
\parbox[position][height][inner-pos]{width}{text}
```

The `\parbox` command produces a box whose contents are created in `paragraph` mode. It should be used to make a box small pieces of text, with nothing fancy inside. In particular, you shouldn't use any paragraph-making environments inside a `\parbox` argument. For larger pieces of text, including ones containing a paragraph-making environment, you should use a `minipage` environment (see [Section 9.17 \[`minipage`\]](#), page 24).

`\parbox` has two mandatory arguments:

width the width of the parbox;
text the text that goes inside the parbox.

The optional *position* argument allows you to align either the top or bottom line in the parbox with the baseline of the surrounding text (default is top).

The optional *height* argument overrides the natural height of the box.

The *inner-pos* argument controls the placement of the text inside the box, as follows; if it is not specified, *position* is used.

t text is placed at the top of the box.
c text is centered in the box.
b text is placed at the bottom of the box.
s stretch vertically; the text must contain vertically stretchable space for this to work.

21.6 `\raisebox`

Synopsis:

```
\raisebox{distance}[height][depth]{text}
```

The `\raisebox` command raises or lowers *text*. The first mandatory argument specifies how high *text* is to be raised (or lowered if it is a negative amount). *text* itself is processed in LR mode.

The optional arguments *height* and *depth* are dimensions. If they are specified, \LaTeX treats *text* as extending a certain distance above the baseline (*height*) or below (*depth*), ignoring its natural height and depth.

21.7 `\savebox`

Synopsis:

```
\savebox{\boxcmd}[width][pos]{text}
```

This command typeset *text* in a box just as with `\makebox` (see [Section 21.4 \[`\makebox`\]](#), page 67), except that instead of printing the resulting box, it saves it in the box labeled `\boxcmd`, which must have been declared with `\newsavebox` (see [Section 13.4 \[`\newsavebox`\]](#), page 42).

21.8 `\sbox{\boxcmd}{text}`

Synopsis:

```
\sbox{\boxcmd}{text}
```

`\sbox` types *text* in a box just as with `\mbox` (see [Section 21.1 \[`\mbox`\]](#), page 67) except that instead of the resulting box being included in the normal output, it is saved in the box labeled `\boxcmd`. `\boxcmd` must have been previously declared with `\newsavebox` (see [Section 13.4 \[`\newsavebox`\]](#), page 42).

21.9 `\usebox{\boxcmd}`

Synopsis:

```
\usebox{\boxcmd}
```

`\usebox` produces the box most recently saved in the bin `\boxcmd` by a `\savebox` command (see [Section 21.7 \[`\savebox`\]](#), page 68).

22 Special insertions

L^AT_EX provides commands for inserting characters that have a special meaning do not correspond to simple characters you can type.

22.1 Reserved characters

The following characters play a special role in L^AT_EX and are called “reserved characters” or “special characters”.

\$ % & ~ _ ^ \ { }

Whenever you write one of these characters into your file, L^AT_EX will do something special. If you simply want the character to be printed as itself, include a \ in front of the character. For example, \\$ will produce \$ in your output.

One exception to this rule is \ itself, because \\ has its own special (context-dependent) meaning. A roman \ is produced by typing `\backslash` in your file, and a typewriter \ is produced by using ‘\’ in a verbatim command (see [Section 9.27 \[verbatim\], page 35](#)).

Also, \~ and \^ place tilde and circumflex accents over the following letter, as in ã and ô (see [Section 22.3 \[Accents\], page 73](#)); to get a standalone ~ or ^, you can again use a verbatim command.

Finally, you can access any character of the current font once you know its number by using the `\symbol` command. For example, the visible space character used in the `\verb*` command has the code decimal 32, so it can be typed as `\symbol{32}`.

You can also specify octal numbers with ‘’ or hexadecimal numbers with “”, so the previous example could also be written as `\symbol{'40}` or `\symbol{"20}`.

22.2 Text symbols

L^AT_EX provides commands to generate a number of non-letter symbols in running text. Some of these, especially the more obscure ones, are not available in OT1; you may need to load the `textcomp` package.

`\copyright`

`\textcopyright`

The copyright symbol, ©.

`\dag`

The dagger symbol (in text).

`\ddag`

The double dagger symbol (in text).

`\LaTeX`

The L^AT_EX logo.

`\guillemotleft` («)

`\guillemotright` (»)

`\guilsinglleft` (<)

`\guilsinglright` (>)

Double and single angle quotation marks, commonly used in French: «, », <, >.

`\ldots`
`\dots`
`\textellipsis`
 An ellipsis (three dots at the baseline): ‘...’. `\ldots` and `\dots` also work in math mode.

`\lq` Left (opening) quote: ‘.

`\P`
`\textparagraph`
 Paragraph sign (pilcrow).

`\pounds`
`\textsterling`
 English pounds sterling: £.

`\quotedblbase (,,)`
`\quotesinglbase (,)`
 Double and single quotation marks on the baseline: ,, and ,.

`\rq` Right (closing) quote: ’.

`\S` Section symbol.

`\TeX` The T_EX logo.

`\textasciicircum`
 ASCII circumflex: ^.

`\textasciitilde`
 ASCII tilde: ~.

`\textasteriskcentered`
 Centered asterisk: *.

`\textbackslash`
 Backslash: \.

`\textbar` Vertical bar: |.

`\textbardbl`
 Double vertical bar.

`\textbigcircle`
 Big circle symbol.

`\textbraceleft`
 Left brace: {.

`\textbraceright`
 Right brace: }.

`\textbullet`
 Bullet: •.

`\textcircled{letter}`
letter in a circle, as in ®.

`\textcompwordmark`
`\textcapitalwordmark`
`\textascenderwordmark`
Composite word mark (invisible). The `\textcapital...` form has the cap height of the font, while the `\textascender...` form has the ascender height.

`\textdagger`
Dagger: †.

`\textdaggerdbl`
Double dagger: ‡.

`\textdollar` (or `$`)
Dollar sign: \$.

`\textemdash` (or `---`)
Em-dash: — (for punctuation).

`\textendash` (or `--`)
En-dash: — (for ranges).

`\texteuro`
The Euro symbol: €.

`\textexclamdown` (or `!'`)
Upside down exclamation point: ¡.

`\textgreater`
Greater than: >.

`\textless`
Less than: <.

`\textleftarrow`
Left arrow.

`\textordfeminine`
`\textordmasculine`
Feminine and masculine ordinal symbols: ^a, ^o.

`\textperiodcentered`
Centered period: ·.

`\textquestiondown` (or `?'`)
Upside down questionation point: ¿.

`\textquotedblleft` (or `''`)
Double left quote: “.

`\textquotedblright` (or `'`)
Double right quote: ”.

`\textquoteleft` (or `'`)
Single left quote: ‘.

`\textquoteright` (or `'`)
Single right quote: ’.

`\textquotestraightbase`
`\textquotestraightdblbase`
 Single and double straight quotes on the baseline.

`\textregistered`
 Registered symbol: ®.

`\textrightarrow`
 Right arrow.

`\textthreequartersemdash`
 “Three-quarters” em-dash, between en-dash and em-dash.

`\texttrademark`
 Trademark symbol: ™.

`\texttwelveudash`
 “Two-thirds” em-dash, between en-dash and em-dash.

`\textunderscore`
 Underscore: _.

`\textvisiblespace`
 Visible space symbol.

22.3 Accents

L^AT_EX has wide support for many of the world’s scripts and languages, through the `babel` package and related support. This section does not attempt to cover all that support. It merely lists the core L^AT_EX commands for creating accented characters.

The `\capital...` commands produce alternative forms for use with capital letters. These are not available with OT1.

`\"`
`\capitaldieresis`
 Produces an umlaut (dieresis), as in ö.

`\'`
`\capitalacute`
 Produces an acute accent, as in ó. In the `tabbing` environment, pushes current column to the right of the previous column (see [Section 9.21 \[tabbing\]](#), page 28).

`\.`
 Produces a dot accent over the following, as in ô.

`\=`
`\capitalmacron`
 Produces a macron (overbar) accent over the following, as in ō.

`\^`
`\capitalcircumflex`
 Produces a circumflex (hat) accent over the following, as in ô.

`\``
`\capitalgrave`
 Produces a grave accent over the following, as in ò. In the `tabbing` environment, move following text to the right margin (see [Section 9.21 \[tabbing\]](#), page 28).

<code>\~</code>	
<code>\capitaltilde</code>	Produces a tilde accent over the following, as in ñ.
<code>\b</code>	Produces a bar accent under the following, as in ɔ̄.
<code>\c</code>	
<code>\capitalcedilla</code>	Produces a cedilla accent under the following, as in ç.
<code>\d</code>	
<code>\capitaldotaccent</code>	Produces a dot accent under the following, as in ɔ̇.
<code>\H</code>	
<code>\capitalhungarumlaut</code>	Produces a long Hungarian umlaut accent over the following, as in ő.
<code>\i</code>	Produces a dotless i, as in ‘ı’.
<code>\j</code>	Produces a dotless j, as in ‘j’.
<code>\k</code>	
<code>\capitalogonek</code>	Produces a letter with ogonek, as in ‘ǫ’. Not available in the OT1 encoding.
<code>\r</code>	
<code>\capitalring</code>	Produces a ring accent, as in ‘ö’.
<code>\t</code>	
<code>\capitaltie</code>	
<code>\newtie</code>	
<code>\capitalnewtie</code>	Produces a tie-after accent, as in ‘öö’. The <code>\newtie</code> form is centered in its box.
<code>\u</code>	
<code>\capitalbreve</code>	Produces a breve accent, as in ‘ö̆’.
<code>\underbar</code>	Not exactly an accent, this produces a bar under the argument text. The argument is always processed in horizontal mode. The bar is always a fixed position under the baseline, thus crossing through descenders. See also <code>\underline</code> in Section 17.6 [Math miscellany] , page 59.
<code>\v</code>	
<code>\capitalcaron</code>	Produces a háček (check, caron) accent, as in ‘ř’.

22.4 Non-English characters

Here are the basic L^AT_EX commands for inserting characters commonly used in languages other than English.

<code>\aa</code>	
<code>\AA</code>	å and Å.
<code>\ae</code>	
<code>\AE</code>	æ and Æ.
<code>\dh</code>	
<code>\DH</code>	Icelandic letter eth: ð and Ð.
<code>\dj</code>	
<code>\DJ</code>	xxxx
<code>\ij</code>	
<code>\IJ</code>	ij and IJ (except somewhat closer together than appears here).
<code>\l</code>	
<code>\L</code>	ł and Ł.
<code>\ng</code>	
<code>\NG</code>	xxxx
<code>\o</code>	
<code>\O</code>	ø and Ø.
<code>\oe</code>	
<code>\OE</code>	œ and Œ.
<code>\ss</code>	
<code>\SS</code>	ß and SS.
<code>\th</code>	
<code>\TH</code>	Icelandic letter thorn: þ and Þ.

22.5 `\rule`

Synopsis:

```
\rule[raise]{width}{thickness}
```

The `\rule` command produces *rules*, that is, lines or rectangles. The arguments are:

- raise* How high to raise the rule (optional).
- width* The length of the rule (mandatory).
- thickness* The thickness of the rule (mandatory).

22.6 `\today`

The `\today` command produces today's date, in the format '*month dd, yyyy*'; for example, 'July 4, 1976'. It uses the predefined counters `\day`, `\month`, and `\year` (see [Section 14.8](#) [`\day \month \year`], page 45) to do this. It is not updated as the program runs.

The `datetime` package, among others, can produce a wide variety of other date formats.

23 Splitting the input

A large document requires a lot of input. Rather than putting the whole input in a single large file, it's more efficient to split it into several smaller ones. Regardless of how many separate files you use, there is one that is the root file; it is the one whose name you type when you run \LaTeX .

23.1 $\backslash\text{include}$

Synopsis:

```
 $\backslash\text{include}\{file\}$ 
```

If no $\backslash\text{includeonly}$ command is present, the $\backslash\text{include}$ command executes $\backslash\text{clearpage}$ to start a new page (see [Section 11.2 \[\$\backslash\text{clearpage}\$ \], page 38](#)), then reads *file*, then does another $\backslash\text{clearpage}$.

Given an $\backslash\text{includeonly}$ command, the $\backslash\text{include}$ actions are only run if *file* is listed as an argument to $\backslash\text{includeonly}$. See the next section.

The $\backslash\text{include}$ command may not appear in the preamble or in a file read by another $\backslash\text{include}$ command.

23.2 $\backslash\text{includeonly}$

Synopsis:

```
 $\backslash\text{includeonly}\{file1,file2,\dots\}$ 
```

The $\backslash\text{includeonly}$ command controls which files will be read by subsequent $\backslash\text{include}$ commands. The list of filenames is comma-separated. Each *file* must exactly match a filename specified in a $\backslash\text{include}$ command for the selection to be effective.

This command can only appear in the preamble.

23.3 $\backslash\text{input}$

Synopsis:

```
 $\backslash\text{input}\{file\}$ 
```

The $\backslash\text{input}$ command causes the specified *file* to be read and processed, as if its contents had been inserted in the current file at that point.

If *file* does not end in `.tex` (e.g., `foo` or `foo.bar`), it is first tried with that extension (`foo.tex` or `foo.bar.tex`). If that is not found, the original *file* is tried (`foo` or `foo.bar`).

24 Front/back matter

24.1 Tables of contents

A table of contents is produced with the `\tableofcontents` command. You put the command right where you want the table of contents to go; \LaTeX does the rest for you. A previous run must have generated a `.toc` file.

The `\tableofcontents` command produces a heading, but it does not automatically start a new page. If you want a new page after the table of contents, write a `\newpage` command after the `\tableofcontents` command.

The analogous commands `\listoffigures` and `\listoftables` produce a list of figures and a list of tables, respectively. Everything works exactly the same as for the table of contents.

The command `\nofiles` overrides these commands, and *prevents* any of these lists from being generated.

24.1.1 `\addcontentsline`

The `\addcontentsline{ext}{unit}{text}` command adds an entry to the specified list or table where:

<i>ext</i>	The extension of the file on which information is to be written, typically one of: <code>toc</code> (table of contents), <code>lof</code> (list of figures), or <code>lot</code> (list of tables).
<i>unit</i>	The name of the sectional unit being added, typically one of the following, matching the value of the <i>ext</i> argument:
<code>toc</code>	The name of the sectional unit: <code>part</code> , <code>chapter</code> , <code>section</code> , <code>subsection</code> , <code>subsubsection</code> .
<code>lof</code>	For the list of figures.
<code>lot</code>	For the list of tables.
<i>entry</i>	The actual text of the entry.

What is written to the `.ext` file is the command `\contentsline{unit}{name}`.

24.1.2 `\addtocontents`

The `\addtocontents{ext}{text}` command adds text (or formatting commands) directly to the `.ext` file that generates the table of contents or lists of figures or tables.

<i>ext</i>	The extension of the file on which information is to be written: <code>'toc'</code> (table of contents), <code>'lof'</code> (list of figures), or <code>'lot'</code> (list of tables).
<i>text</i>	The text to be written.

24.2 Glossaries

The command `\makeglossary` enables creating glossaries.

The command `\glossary{text}` writes a glossary entry for *text* to an auxiliary file with the `.glo` extension.

Specifically, what gets written is the command `\glossaryentry{text}{pageno}`, where *pageno* is the current `\thepage` value.

The `glossary` package on CTAN provides support for fancier glossaries.

24.3 Indexes

The command `\makeindex` enables creating indexes. Put this in the preamble.

The command `\index{text}` writes an index entry for *text* to an auxiliary file with the `.idx` extension.

Specifically, what gets written is the command `\indexentry{text}{pageno}`, where *pageno* is the current `\thepage` value.

To generate a index entry for ‘bar’ that says ‘See foo’, use a vertical bar: `\index{bar|see{foo}}`. Use `seealso` instead of `see` to make a ‘See also’ entry.

The text ‘See’ is defined by the macro `\seename`, and ‘See also’ by the macro `\alsoname`. These can be redefined for other languages.

The generated `.idx` file is then sorted with an external command, usually either `makeindex` (<http://mirror.ctan.org/indexing/makeindex>) or (the multi-lingual) `xindy` (<http://xindy.sourceforge.net>). This results in a `.ind` file, which can then be read to typeset the index.

The index is usually generated with the `\printindex` command. This is defined in the `makeidx` package, so `\usepackage{makeidx}` needs to be in the preamble.

The rubber length `\indexspace` is inserted before each new letter in the printed index; its default value is `‘10pt plus5pt minus3pt’`.

The `showidx` package causes each index entries to be shown in the margin on the page where the entry appears. This can help in preparing the index.

The `multind` package supports multiple indexes. See also the T_EX FAQ entry on this topic, <http://www.tex.ac.uk/cgi-bin/texfaq2html?label=multind>.

25 Letters

You can use L^AT_EX to typeset letters, both personal and business. The `letter` document class is designed to make a number of letters at once, although you can make just one if you so desire.

Your `.tex` source file has the same minimum commands as the other document classes, i.e., you must have the following commands as a minimum:

```
\documentclass{letter}
\begin{document}
... letters ...
\end{document}
```

Each letter is a `letter` environment, whose argument is the name and address of the recipient. For example, you might have:

```
\begin{letter}{Mr. Joe Smith\\ 2345 Princess St.
\\ Edinburgh, EH1 1AA}
...
\end{letter}
```

The letter itself begins with the `\opening` command. The text of the letter follows. It is typed as ordinary L^AT_EX input. Commands that make no sense in a letter, like `\chapter`, do not work. The letter closes with a `\closing` command.

After the `\closing`, you can have additional material. The `\cc` command produces the usual “cc: ...”. There’s also a similar `\encl` command for a list of enclosures. With both these commands, use `\\` to separate the items.

These commands are used with the `letter` class.

25.1 `\address{return-address}`

The `\address` specifies the return address of a letter, as it should appear on the letter and the envelope. Separate lines of the address should be separated by `\\` commands.

If you do not make an `\address` declaration, then the letter will be formatted for copying onto your organisation’s standard letterhead. (See [Chapter 2 \[Overview\]](#), page 3, for details on your local implementation). If you give an `\address` declaration, then the letter will be formatted as a personal letter.

25.2 `\cc`

Synopsis:

```
\cc{name1\\name2}
```

Produce a list of *names* the letter was copied to. Each name is printed on a separate line.

25.3 `\closing`

Synopsis:

```
\closing{text}
```

A letter closes with a `\closing` command, for example,

```
\closing{Best Regards,}
```

25.4 `\encl`

Synopsis:

```
\encl{line1\\line2}
```

Declare a list of one more enclosures.

25.5 `\location`

```
\location{address}
```

This modifies your organisation's standard address. This only appears if the `firstpage` pagestyle is selected.

25.6 `\makelabels`

```
\makelabels{number}
```

If you issue this command in the preamble, L^AT_EX will create a sheet of address labels. This sheet will be output before the letters.

25.7 `\name`

```
\name{June Davenport}
```

Your name, used for printing on the envelope together with the return address.

25.8 `\opening{text}`

Synopsis:

```
\opening{text}
```

A letter begins with the `\opening` command. The mandatory argument, *text*, is whatever text you wish to start your letter. For instance:

```
\opening{Dear Joe,}
```

25.9 `\ps`

Use the `\ps` command to start a postscript in a letter, after `\closing`.

25.10 `\signature{text}`

Your name, as it should appear at the end of the letter underneath the space for your signature. `\\` starts a new line within *text* as usual.

25.11 `\startbreaks`

```
\startbreaks
```

Used after a `\stopbreaks` command to allow page breaks again.

25.12 `\stopbreaks`

```
\stopbreaks
```

Inhibit page breaks until a `\startbreaks` command occurs.

25.13 `\telephone`

`\telephone{number}`

This is your telephone number. This only appears if the `firstpage` pagestyle is selected.

26 Terminal input/output

26.1 `\typein[cmd]{msg}`

Synopsis:

```
\typein[\icmd]{\imsg}
```

`\typein` prints *msg* on the terminal and causes L^AT_EX to stop and wait for you to type a line of input, ending with return. If the optional *cmd* argument is omitted, the typed input is processed as if it had been included in the input file in place of the `\typein` command. If the *cmd* argument is present, it must be a command name. This command name is then defined or redefined to be the typed input.

26.2 `\typeout{msg}`

Synopsis:

```
\typeout{\imsg}
```

Prints *msg* on the terminal and in the log file. Commands in *msg* that are defined with `\newcommand` or `\renewcommand` (among others) are replaced by their definitions before being printed.

L^AT_EX's usual rules for treating multiple spaces as a single space and ignoring spaces after a command name apply to *msg*. A `\space` command in *msg* causes a single space to be printed, independent of surrounding spaces. A `^^J` in *msg* prints a newline.

27 Command line

The input file specification indicates the file to be formatted; $\text{T}_{\text{E}}\text{X}$ uses `.tex` as a default file extension. If you omit the input file entirely, $\text{T}_{\text{E}}\text{X}$ accepts input from the terminal. You specify command options by supplying a string as a parameter to the command; e.g.

```
latex '\nonstopmode\input foo.tex'
```

will process `foo.tex` without pausing after every error.

If $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ stops in the middle of the document and gives you a `*` prompt, it is waiting for input. You can type `\stop` (and return) and it will prematurely end the document.

Appendix A Document templates

Although not reference material, perhaps these document templates will be useful. Additional template resources are listed <http://tug.org/interest.html#latextemplates>.

A.1 book template

```
\documentclass{book}
\title{Book Class Template}
\author{Alex Author}

\begin{document}
\maketitle

\chapter{First}
Some text.

\chapter{Second}
Some other text.

\section{A subtopic}
The end.
\end{document}
```

A.2 beamer template

The beamer class creates slides presentations.

```
\documentclass{beamer}

\title{Beamer Class template}
\author{Alex Author}
\date{July 31, 2007}

\begin{document}

\maketitle

% without [fragile], any {verbatim} code gets mysterious errors.
\begin{frame}[fragile]
\frametitle{First Slide}

\begin{verbatim}
This is \verbatim!
\end{verbatim}

\end{frame}
```

```
\end{document}
```

A.3 tugboat template

TUGboat is the journal of the T_EX Users Group, <http://tug.org/TUGboat>.

```
\documentclass{ltugboat}
\usepackage{graphicx}
\usepackage{ifpdf}
\ifpdf
\usepackage[breaklinks,colorlinks,linkcolor=black,citecolor=black,
            urlcolor=black]{hyperref}
\else
\usepackage{url}
\fi

\title{Example \TUB\ article}

% repeat info for each author.
\author{First Last}
\address{Street Address \\ Town, Postal \\ Country}
\netaddress{user (at) example dot org}
\personalURL{http://example.org/~user/}

\begin{document}

\maketitle

\begin{abstract}
This is an example article for \TUB{}.
\end{abstract}

\section{Introduction}

This is an example article for \TUB, from
\url{http://tug.org/TUGboat/location.html}.

We recommend the graphicx package for image inclusions, and the
hyperref package for active url's (in the \acro{PDF} output).
Nowadays \TUB\ is produced using \acro{PDF} files exclusively.

The \texttt{ltugboat} class provides these abbreviations and many more:

% verbatim blocks are often better in \small
\begin{verbatim}[\small]
\AllTeX \AMS \AmS \AmSLaTeX \AmSTeX \aw \AW
\BibTeX \CTAN \DTD \HTML
```

```

\ISBN \ISSN \LaTeXe
\Mc \mf \MFB \mtex \PCTeX \pcTeX
\PiC \PiCTeX \plain \POBox \PS
\SC \SGML \SliTeX \TANGLE \TB \TP
\TUB \TUG \tug
\UG \UNIX \VAX \XeT \WEB \WEAVE

\Dash \dash \vellipsis \bull \cents \Dag
\careof \thinspace

\acro{FRED} -> {\small[er] fred} % please use!
\cs{fred}   -> \fred
\env{fred}  -> \begin{fred}
\meta{fred} -> <fred>
\nth{n}    -> 1st, 2nd, ...
\sfrac{3/4} -> 3/4
\booktitle{Book of Fred}
\end{verbatim}

```

For more information, see the ltubguid document at:
[\url{http://mirror.ctan.org/macros/latex/contrib/tugboat}](http://mirror.ctan.org/macros/latex/contrib/tugboat)
 (we recommend using `\verb|mirror.ctan.org|` for `\CTAN\` references).

Email `\verb|tugboat@tug.org|` if problems or questions.

```

\bibliographystyle{plain} % we recommend the plain bibliography style
\nocite{book-minimal}    % just making the bibliography non-empty
\bibliography{xampl}      % xampl.bib comes with BibTeX

\makesignature
\end{document}

```

Concept Index

*

'*' prompt	83
*-form of sectioning commands	14

.

'glo' file	78
'idx' file	78
'ind' file	78

'

'see' and 'see also' index entries	78
--	----

A

abstracts	16
accents	73
accents, mathematical	58
accessing any character of a font	70
acute accent	73
acute accent, math	58
ae ligature	75
align environment, from <code>amsmath</code>	19
aligning equations	19
alignment via tabbing	28
<code>amsmath</code> package, replacing <code>eqnarray</code>	19
appendix, creating	14
aring	75
arrays, math	16
arrow, left, in text	72
arrow, right, in text	73
ascender height	72
ASCII circumflex, in text	71
ASCII tilde, in text	71
asterisk, centered, in text	71
author, for titlepage	62
auxiliary file	3

B

backslash, in text	71
bar, double vertical, in text	71
bar, vertical, in text	71
bar-over accent	73
bar-over accent, math	58
bar-under accent	74
basics of \LaTeX	3
bibliography, creating (automatically)	34
bibliography, creating (manually)	33
<code>bibtex</code> , using	34
big circle symbols, in text	71
black boxes, omitting	5
bold font	8

bold typewriter, avoiding	17
boxes	67
brace, left, in text	71
brace, right, in text	71
breaking lines	36
breaking pages	38
breve accent	74
breve accent, math	58
bug reporting	2
bullet symbol	50
bullet, in text	71
bulleted lists	22

C

calligraphic letters for math	8
cap height	72
caron accent	74
case sensitivity of \LaTeX	3
cc list, in letters	79
cedilla accent	74
centered asterisk, in text	71
centered period, in text	72
centering text, declaration for	17
centering text, environment for	17
characters, accented	73
characters, non-English	74
characters, reserved	70
check accent	74
check accent, math	58
circle symbol, big, in text	71
circled letter, in text	71
circumflex accent	73
circumflex accent, math	58
circumflex, ASCII, in text	71
class options	5
classes of documents	5
closing letters	79
closing quote	71
code, typesetting	35
command line	83
commands, defining new ones	41
composite word mark, in text	72
computer programs, typesetting	35
copyright symbol	70
counters, a list of	44
counters, defining new	41
counters, getting value of	44
counters, setting	45
creating letters	79
creating pictures	24
creating tables	30
credit footnote	62
cross references	15

cross referencing with page number	15
cross referencing, symbolic	15
currency, dollar	72
currency, euro	72

D

dagger, double, in text	72
dagger, in text	70, 72
date, for titlepage	62
<code>datetime</code> package	75
defining a new command	41
defining new environments	42
defining new fonts	43
defining new theorems	42
definitions	41
description lists, creating	17
dieresis accent	73
discretionary multiplication	59
displaying quoted text with paragraph indentation	28
displaying quoted text without paragraph indentation	28
document class options	5
document classes	5
document templates	84
dollar sign	72
dot accent	73
dot over accent, math	58
dot-over accent	73
dot-under accent	74
dotless i	74
dotless i, math	58
dotless j	74
dotless j, math	58
double angle quotation marks	70
double dagger, in text	70, 72
double dot accent, math	58
double guillemets	70
double left quote	72
double low-9 quotation mark	71
double quote, straight base	73
double right quote	72
double spacing	9
double vertical bar, in text	71

E

e-dash	72
ellipsis	71
em-dash	72
em-dash, three-quarters	73
em-dash, two-thirds	73
emphasis	7, 8
enclosure list	80
ending & starting	4
enlarge current page	38
environments	16

environments, defining	42
equation number, cross referencing	15
equation numbers, omitting	19
equations, aligning	19
equations, environment for	19
es-zet German letter	75
eth, Icelandic letter	75
euro symbol	72
exclamation point, upside-down	72
exponent	49

F

feminine ordinal symbol	72
figure number, cross referencing	15
figures, footnotes in	24
figures, inserting	19
fixed-width font	8
<code>float</code> package	20
flushing floats and starting a page	38
font commands, low-level	9
font sizes	8
font styles	7
fonts	7
fonts, new commands for	43
footer style	62
footer, parameters for	12
footnote number, cross referencing	15
footnote parameters	40
footnotes in figures	24
footnotes, creating	39
footnotes, symbolic instead of numbered	39
formulas, environment for	19
formulas, math	49
fragile commands	43
French quotation marks	70
functions, math	57

G

global options	5, 6
glossaries	78
grave accent	73
grave accent, math	58
greater than symbol, in text	72
greek letters	49

H

hacek accent	74
háček accent, math	58
hat accent	73
hat accent, math	58
header style	62
header, parameters for	12
here, putting floats	20
hungarian umlaut accent	74
hyphenation, defining	37

hyphenation, forcing 36
 hyphenation, preventing 67

I

Icelandic eth 75
 Icelandic thorn 75
 ij letter, Dutch 75
 in-line formulas 24
 indent, forcing 47
 indent, suppressing 47
 indentation of paragraphs, in minipage 24
 indexes 78
 input file 76
 input/output 82
 inserting figures 19
 italic font 8

J

justification, ragged left 22
 justification, ragged right 21

K

Knuth, Donald E. 2

L

labelled lists, creating 17
 Lamport, Leslie 2
 L^AT_EX logo 70
 L^AT_EX overview 3
 L^AT_EX Project team 2
 layout commands 11
 layout, page parameters for 12
 left angle quotation marks 70
 left arrow, in text 72
 left brace, in text 71
 left quote 71
 left quote, double 72
 left quote, single 72
 left-justifying text 21
 left-justifying text, environment for 21
 left-to-right mode 61
 lengths, adding to 46
 lengths, defining and using 46
 lengths, defining new 41
 lengths, predefined 46
 lengths, setting 46
 less than symbol, in text 72
 letters 79
 letters, accented 73
 letters, ending 79
 letters, non-English 74
 letters, starting 80
 line break, forcing 36
 line breaking 36

line breaks, forcing 37
 line breaks, preventing 37
 lines in tables 30
 lining text up in tables 30
 lining text up using tab stops 28
 list items, specifying counter 44
 lists of items 22
 lists of items, generic 23
 lists of items, numbered 18
 loading additional packages 6
 log file 3
 logo, L^AT_EX 70
 logo, T_EX 71
 low-9 quotation marks, single and double 71
 low-level font commands 9
 LR mode 61
 LuaT_EX 3

M

macron accent 73
 macron accent, math 58
 Madsen, Lars 19
makeidx package 78
makeindex program 78
 making a title page 34
 making paragraphs 47
 marginal notes 47
 masculine ordinal symbol 72
 math accents 58
 math formulas 49
 math functions 57
 math miscellany 59
 math mode 61
 math mode, entering 49
 math mode, spacing 59
 math symbols 49
 minipage, creating a 24
 modes 61
 monospace font 8
 moving arguments 43
 multicolumn text 11
multind package 78
 multiplication symbol, discretionary line break
 59

N

nested `\include`, not allowed 76
 new commands, defining 41
 new line, output as input 36
 new line, starting 36
 new line, starting (paragraph mode) 36
 new page, starting 38
 non-English characters 74
 notes in the margin 47
 null delimiter 59
 numbered items, specifying counter 44

O

oblique font	8
oe ligature	75
ogonek	74
one-column output	11
opening quote	71
options, document class	5
options, global	6
ordinals, feminine and masculine	72
oslash	75
overbar accent	73
overdot accent, math	58
overview of L ^A T _E X	3

P

packages, loading	6
page break, forcing	38
page break, preventing	38
page breaking	38
page layout parameters	12
page number, cross referencing	15
page numbering style	62
page styles	62
paragraph indentation, in minipage	24
paragraph indentations in quoted text	28
paragraph indentations in quoted text, omitting	28
paragraph mode	61
paragraph symbol	71
paragraphs	47
parameters, for footnotes	40
parameters, page layout	12
pdf _T E _X	3
period, centered, in text	72
pictures, creating	24
pilcrow	71
placement of floats	19
poetry, an environment for	35
polish l	75
postscript, in letters	80
pounds symbol	71
preamble, defined	4
predefined lengths	46
prompt, ‘*’	83

Q

questionation point, upside-down	72
quotation marks, French	70
quote, straight base	73
quoted text with paragraph indentation, displaying	28
quoted text without paragraph indentation, displaying	28

R

ragged left text	22
ragged left text, environment for	21
ragged right text	21
ragged right text, environment for	21
redefining environments	42
registered symbol	73
remarks in the margin	47
reporting bugs	2
reserved characters	70
right angle quotation marks	70
right arrow, in text	73
right brace, in text	71
right quote	71
right quote, double	72
right quote, single	72
right-justifying text	22
right-justifying text, environment for	21
ring accent	74
ring accent, math	58
robust commands	43
roman font	8
running header and footer	12
running header and footer style	62

S

sans serif font	8
script letters for math	8
section number, cross referencing	15
section numbers, printing	14
section symbol	71
sectioning	14
setspace package	9
setting counters	45
sharp S letters	75
showidx package	78
simulating typed text	35
single angle quotation marks	70
single guillemets	70
single left quote	72
single low-9 quotation mark	71
single right quote	72
sizes of text	8
slanted font	8
small caps font	8
space, inserting vertical	65
spaces	64
spacing within math mode	59
Spanish ordinals, feminine and masculine	72
special characters	74
specifier, float placement	19
splitting the input file	76
starting & ending	4
starting a new page	38
starting a new page and clearing floats	38
starting on a right-hand page	38
sterling symbol	71

straight double quote, base	73
straight quote, base	73
stretch, omitting vertical	12
styles of text	7
styles, page	62
subscript	49
superscript	49
symbols, math	49

T

tab stops, using	28
table of contents entry, manually adding	77
table of contents, creating	77
tables, creating	30
terminal input/output	82
\TeX logo	71
text symbols	70
thanks, for titlepage	62
theorems, defining	42
theorems, typesetting	34
thorn, Icelandic letter	75
three-quarters em-dash	73
tie-after accent	74
tilde accent	74
tilde accent, math	58
tilde, ASCII, in text	71
title pages, creating	34
title, for titlepage	62
titles, making	62
trademark symbol	73
transcript file	3
two-column output	11
two-thirds em-dash	73
typed text, simulating	35
typeface sizes	8

typeface styles	7
typefaces	7
typewriter font	8
typewriter labels in lists	17

U

umlaut accent	73
underbar	74
underscore, in text	73
unordered lists	22
using Bib \TeX	34

V

variables, a list of	44
vector symbol, math	58
verbatim text	35
verbatim text, inline	35
vertical bar, double, in text	71
vertical bar, in text	71
vertical space	65
vertical space before paragraphs	47
visible space	35
visible space symbol, in text	73

W

wide hat accent, math	58
wide tile accent, math	58

X

Xe \TeX	3
xindy program	78

Command Index

\$			
\$	49		
.			
.aux file	3		
.dvi file	3		
.log file	3		
.pdf file	3		
.toc file	77		
@			
@{...}	16		
[
[...] for optional arguments	3		
^			
^	49		
-			
-	49		
\			
\ character starting commands	3		
\" (umlaut accent)	73		
\#	70		
\\$	70		
\%	70		
\&	70		
\' (acute accent)	73		
\' (tabbing)	29		
\(.....	49		
\)	49		
*	59		
\+	29		
\,	59		
\-	29		
\- (hyphenation)	36		
\. (dot-over accent)	73		
\/	65		
\:	59		
\;	59		
\<	29		
\= (macron accent)	73		
\= (tabbing)	29		
\>	29, 59		
\> (tabbing)	29		
\@	64		
\@fnsymbol	39		
\[.....	49		
\]	49		
\^	70		
\^ (circumflex accent)	73		
_	70		
\' (grave accent)	73		
\' (tabbing)	29		
\\ (for \shortstack objects)	28		
\\ (for array)	16		
\\ (for center)	17		
\\ (for eqnarray)	19		
\\ (for flushright)	21		
\\ (tabbing)	29		
\\ for \author	62		
\\ for \title	62		
\\ for flushleft	21		
\\ for letters	79		
\\ for tabular	30		
\\ for verse	35		
\\ force line break	36		
* (for eqnarray)	19		
\ 	49		
\{	70		
\}	70		
\~	70		
\~ (tilde accent)	74		
\a (tabbing)	29		
\a' (acute accent in tabbing)	29		
\a= (macron accent in tabbing)	29		
\a' (grave accent in tabbing)	29		
\aa (å)	75		
\AA (Å)	75		
\acute	58		
\addcontentsline{ext}{unit}{text}	77		
\address	79		
\addtocontents{ext}{text}	77		
\addtocounter	45		
\addtolength	46		
\addvspace	65		
\ae (æ)	75		
\AE (Æ)	75		
\aleph	49		
\alph	44		
\Alph	44		
\Alph example	18		
\alpha	49		
\alsoname	78		
\amalg	49		
\and for \author	62		
\angle	49		
\appendix	14		
\approx	49		
\arabic	44		
\arccos	57		

<code>\arcsin</code>	57	<code>\capitalring</code>	74
<code>\arctan</code>	57	<code>\capitaltie</code>	74
<code>\arg</code>	57	<code>\capitaltilde</code>	74
<code>\arraycolsep</code>	16	<code>\caption</code>	20
<code>\arrayrulewidth</code>	32	<code>\cc</code>	79
<code>\arraystretch</code>	32	<code>\cdot</code>	50
<code>\ast</code>	49	<code>\cdots</code>	59
<code>\asympt</code>	50	<code>\centering</code>	17
<code>\author{name \and name2}</code>	62	<code>\chapter</code>	14
<code>\b</code> (bar-under accent).....	74	<code>\check</code>	58
<code>\backslash</code>	50, 70	<code>\chi</code>	50
<code>\bar</code>	58	<code>\circ</code>	50
<code>\baselineskip</code>	9	<code>\circle</code>	25
<code>\baselinestretch</code>	9	<code>\cite</code>	33
<code>\begin</code>	16	<code>\cleardoublepage</code>	38
<code>\beta</code>	50	<code>\clearpage</code>	38
<code>\bf</code>	8	<code>\cline</code>	32
<code>\bfseries</code>	7	<code>\closing</code>	79
<code>\bibitem</code>	33	<code>\clubsuit</code>	50
<code>\bibliography</code>	34	<code>\columnsep</code>	11
<code>\bibliographystyle</code>	34	<code>\columnseprule</code>	11
<code>\bigcap</code>	50	<code>\columnwidth</code>	11
<code>\bigcirc</code>	50	<code>\cong</code>	50
<code>\bigcup</code>	50	<code>\contentsline</code>	77
<code>\bigodot</code>	50	<code>\coprod</code>	50
<code>\bigoplus</code>	50	<code>\copyright</code>	70
<code>\bigotimes</code>	50	<code>\cos</code>	57
<code>\bigskip</code>	65	<code>\cosh</code>	57
<code>\bigskipamount</code>	65	<code>\cot</code>	57
<code>\bigsqcup</code>	50	<code>\coth</code>	57
<code>\bigtriangledown</code>	50	<code>\csc</code>	57
<code>\bigtriangleup</code>	50	<code>\cup</code>	51
<code>\biguplus</code>	50	<code>\d</code> (dot-under accent).....	74
<code>\bigwedge</code>	50	<code>\dag</code>	70
<code>\bmod</code>	57	<code>\dagger</code>	51
<code>\boldmath</code>	49	<code>\dashbox</code>	26
<code>\bot</code>	50	<code>\dashv</code>	51
<code>\bottomfraction</code>	20	<code>\date{text}</code>	62
<code>\bottomnumber</code>	21	<code>\day</code>	45
<code>\bowtie</code>	50	<code>\dblfloatpagefraction</code>	11
<code>\Box</code>	50	<code>\dblfloatsep</code>	11
<code>\breve</code>	58	<code>\dbltextfloatsep</code>	11
<code>\bullet</code>	50	<code>\dbltopfraction</code>	11
<code>\c</code> (cedilla accent).....	74	<code>\ddag</code>	70
<code>\cal</code>	8	<code>\ddagger</code>	51
<code>\cap</code>	50	<code>\ddot</code>	58
<code>\capitalacute</code>	73	<code>\ddots</code>	59
<code>\capitalbreve</code>	74	<code>\deg</code>	57
<code>\capitalcaron</code>	74	<code>\delta</code>	51
<code>\capitalcedilla</code>	74	<code>\Delta</code>	51
<code>\capitalcircumflex</code>	73	<code>\depth</code>	46
<code>\capitaldieresis</code>	73	<code>\det</code>	57
<code>\capitaldotaccent</code>	74	<code>\dh</code> (æ).....	75
<code>\capitalgrave</code>	73	<code>\DH</code> (Æ).....	75
<code>\capitalhungarumlaut</code>	74	<code>\diamond</code>	51
<code>\capitalmacron</code>	73	<code>\Diamond</code>	51
<code>\capitalnewtie</code>	74	<code>\diamondsuit</code>	51
<code>\capitalogonek</code>	74	<code>\dim</code>	57

<code>\displaystyle</code>	49	<code>\fussy</code>	36
<code>\div</code>	51	<code>\gamma</code>	51
<code>\dj</code>	75	<code>\Gamma</code>	51
<code>\DJ</code>	75	<code>\gcd</code>	57
<code>\documentclass</code>	5	<code>\ge</code>	51
<code>\dot</code>	58	<code>\geq</code>	51
<code>\doteq</code>	51	<code>\gets</code>	51
<code>\dotfill</code>	65	<code>\gg</code>	51
<code>\dots</code>	71	<code>\glossary</code>	78
<code>\doublerulesep</code>	32	<code>\glossaryentry</code>	78
<code>\downarrow</code>	51	<code>\grave</code>	58
<code>\Downarrow</code>	51	<code>\guillemotleft</code> (◀).....	70
<code>\ell</code>	51	<code>\guillemotright</code> (▶).....	70
<code>\em</code>	8	<code>\guilsinglleft</code> (◁).....	70
<code>\emph</code>	7	<code>\guilsinglright</code> (▷).....	70
<code>\emptyset</code>	51	<code>\H</code> (Hungarian umlaut accent).....	74
<code>\encl</code>	80	<code>\hat</code>	58
<code>\end</code>	16	<code>\hbar</code>	51
<code>\enlargethispage</code>	38	<code>\headheight</code>	12
<code>\enumi</code>	18	<code>\headsep</code>	12
<code>\enumii</code>	18	<code>\heartsuit</code>	51
<code>\enumiii</code>	18	<code>\height</code>	46
<code>\enumiv</code>	18	<code>\hfill</code>	64
<code>\epsilon</code>	51	<code>\hline</code>	32
<code>\equiv</code>	51	<code>\hom</code>	57
<code>\eta</code>	51	<code>\hookleftarrow</code>	52
<code>\evensidemargin</code>	5	<code>\hookrightarrow</code>	52
<code>\exists</code>	51	<code>\hrulefill</code>	65
<code>\exp</code>	57	<code>\hspace</code>	13
<code>\extracolsep</code>	31	<code>\hspace</code>	64
<code>\fbox</code>	67	<code>\huge</code>	8
<code>\fboxrule</code>	26, 67	<code>\Huge</code>	8
<code>\fboxsep</code>	26, 67	<code>\hyphenation</code>	37
<code>\fill</code>	64	<code>\i</code> (dotless i).....	74
<code>\flat</code>	51	<code>\iff</code>	52
<code>\floatpagefraction</code>	20	<code>\ij</code> (ij).....	75
<code>\floatsep</code>	20	<code>\IJ</code> (IJ).....	75
<code>\flushbottom</code>	12	<code>\Im</code>	52
<code>\fnsymbol</code>	44	<code>\imath</code>	58
<code>\fnsymbol, and footnotes</code>	39	<code>\in</code>	52
<code>\fontencoding</code>	9	<code>\include</code>	76
<code>\fontfamily</code>	9	<code>\includeonly</code>	76
<code>\fontseries</code>	9	<code>\indent</code>	47
<code>\fontshape</code>	9	<code>\index</code>	78
<code>\fontsize</code>	9	<code>\indexentry</code>	78
<code>\footnote</code>	39	<code>\inf</code>	57
<code>\footnotemark</code>	39	<code>\infty</code>	52
<code>\footnoterule</code>	40	<code>\input</code>	76
<code>\footnotesep</code>	40	<code>\int</code>	52
<code>\footnotesize</code>	8	<code>\intertextsep</code>	20
<code>\footnotetext</code>	39	<code>\iota</code>	52
<code>\footskip</code>	12	<code>\it</code>	8
<code>\forall</code>	51	<code>\item</code>	17, 18, 22
<code>\frac</code>	59	<code>\itemindent</code>	22
<code>\frac{num}{den}</code>	59	<code>\itemsep</code>	23
<code>\frame</code>	26	<code>\itshape</code>	7
<code>\framebox</code>	26, 67	<code>\j</code> (dotless j).....	74
<code>\frown</code>	51	<code>\jmath</code>	58

<code>\Join</code>	52	<code>\linewidth</code>	12
<code>\k (ogonek)</code>	74	<code>\listoffigures</code>	77
<code>\kappa</code>	52	<code>\listoftables</code>	77
<code>\ker</code>	57	<code>\listparindent</code>	23
<code>\kill</code>	29	<code>\ll</code>	53
<code>\l (<u>l</u>)</code>	75	<code>\ln</code>	57
<code>\L (<u>L</u>)</code>	75	<code>\lnot</code>	53
<code>\label</code>	15	<code>\location</code>	80
<code>\labelenumi</code>	18	<code>\log</code>	58
<code>\labelenumii</code>	18	<code>\longleftarrow</code>	53
<code>\labelenumiii</code>	18	<code>\longlefttrightarrow</code>	53
<code>\labelenumiv</code>	18	<code>\longmapsto</code>	53
<code>\labelitemi</code>	22	<code>\longrightarrow</code>	53
<code>\labelitemii</code>	22	<code>\lor</code>	53
<code>\labelitemiii</code>	22	<code>\lq</code>	71
<code>\labelitemiv</code>	22	<code>\makebox</code>	67
<code>\labelsep</code>	22	<code>\makebox (picture)</code>	26
<code>\labelwidth</code>	23	<code>\makeglossary</code>	78
<code>\lambda</code>	52	<code>\makeindex</code>	78
<code>\Lambda</code>	52	<code>\makelabels</code>	80
<code>\land</code>	52	<code>\maketitle</code>	62
<code>\langle</code>	52	<code>\mapsto</code>	53
<code>\large</code>	8	<code>\marginpar</code>	47
<code>\Large</code>	8	<code>\marginparpush</code>	47
<code>\LARGE</code>	8	<code>\marginparsep</code>	48
<code>\LaTeX</code>	70	<code>\marginparwidth</code>	48
<code>\lbrace</code>	52	<code>\markboth{left}{right}</code>	63
<code>\lbrack</code>	52	<code>\markright{right}</code>	63
<code>\lceil</code>	52	<code>\mathbf</code>	7
<code>\ldots</code>	71	<code>\mathcal</code>	8
<code>\le</code>	52	<code>\mathnormal</code>	8
<code>\leadsto</code>	52	<code>\mathring</code>	58
<code>\left delim1 ... \right delim2</code>	59	<code>\mathrm</code>	7
<code>\leftarrow</code>	52	<code>\mathsf</code>	8
<code>\Leftarrow</code>	52	<code>\mathtt</code>	8
<code>\lefteqn</code>	19	<code>\mathversion</code>	8
<code>\leftharpoondown</code>	52	<code>\max</code>	58
<code>\leftharpoonup</code>	52	<code>\mbox</code>	67
<code>\leftmargin</code>	22	<code>\mdseries</code>	7
<code>\leftmargini</code>	22	<code>\medskip</code>	65
<code>\leftmarginii</code>	22	<code>\medskipamount</code>	65
<code>\leftmarginiii</code>	22	<code>\mho</code>	53
<code>\leftmarginiv</code>	22	<code>\mid</code>	53
<code>\leftmarginv</code>	22	<code>\min</code>	58
<code>\leftmarginvi</code>	22	<code>\models</code>	53
<code>\leftrightharrow</code>	52	<code>\month</code>	45
<code>\Leftrightarrow</code>	52	<code>\mp</code>	53
<code>\leq</code>	52	<code>\mu</code>	53
<code>\lfloor</code>	52	<code>\multicolumn</code>	32
<code>\lg</code>	57	<code>\multipt</code>	27
<code>\lhd</code>	53	<code>\nabla</code>	53
<code>\lim</code>	57	<code>\name</code>	80
<code>\liminf</code>	57	<code>\natural</code>	53
<code>\limsup</code>	57	<code>\ne</code>	53
<code>\line</code>	26	<code>\nearrow</code>	53
<code>\linebreak</code>	37	<code>\neg</code>	53
<code>\linespread</code>	10	<code>\neq</code>	53
<code>\linethickness</code>	27	<code>\newcommand</code>	41

<code>\newcounter</code>	41	<code>\part</code>	14
<code>\newenvironment</code>	42	<code>\partial</code>	54
<code>\newfont</code>	43	<code>\partopsep</code>	23
<code>\newlength</code>	41	<code>\perp</code>	54
<code>\newline</code>	36	<code>\phi</code>	54
<code>\NEWLINE</code>	64	<code>\pi</code>	54
<code>\newpage</code>	38	<code>\Pi</code>	54
<code>\newsavebox</code>	42	<code>\pm</code>	54
<code>\newtheorem</code>	42	<code>\pmod</code>	58
<code>\newtie</code>	74	<code>\poptabs</code>	29
<code>\ng</code>	75	<code>\pounds</code>	71
<code>\NG</code>	75	<code>\Pr</code>	58
<code>\ni</code>	53	<code>\prec</code>	54
<code>\nocite</code>	33	<code>\preceq</code>	54
<code>\nofiles</code>	77	<code>\prime</code>	54
<code>\noindent</code>	47	<code>\prod</code>	54
<code>\nolinebreak</code>	37	<code>\propto</code>	54
<code>\nonumber</code>	19	<code>\protect</code>	43
<code>\nopagebreak</code>	38	<code>\ps</code>	80
<code>\normalfont</code>	7	<code>\psi</code>	54
<code>\normalmarginpar</code>	47	<code>\Psi</code>	54
<code>\normalsize</code>	8	<code>\pushtabs</code>	29
<code>\not</code>	53	<code>\put</code>	27
<code>\notin</code>	53	<code>\quotedblbase (,,)</code>	71
<code>\nu</code>	53	<code>\quotesinglbase (,)</code>	71
<code>\narrow</code>	53	<code>\r (ring accent)</code>	74
<code>\o (\varnothing)</code>	75	<code>\raggedbottom</code>	12
<code>\O (\emptyset)</code>	75	<code>\raggedleft</code>	22
<code>\obeycr</code>	36	<code>\raggedright</code>	21
<code>\oddsidemargin</code>	5	<code>\raisebox</code>	68
<code>\odot</code>	53	<code>\rangle</code>	54
<code>\oe (\o)</code>	75	<code>\rbrace</code>	54
<code>\OE (\O)</code>	75	<code>\rbrack</code>	54
<code>\oint</code>	53	<code>\rceil</code>	54
<code>\omega</code>	53	<code>\Re</code>	54
<code>\Omega</code>	53	<code>\ref</code>	15
<code>\ominus</code>	53	<code>\refstepcounter</code>	45
<code>\onecolumn</code>	11	<code>\renewenvironment</code>	42
<code>\opening</code>	80	<code>\restorecr</code>	36
<code>\oplus</code>	54	<code>\reversemarginpar</code>	47
<code>\oslash</code>	54	<code>\rfloor</code>	54
<code>\otimes</code>	54	<code>\rhd</code>	54
<code>\oval</code>	27	<code>\rho</code>	54
<code>\overbrace{text}</code>	59	<code>\right</code>	59
<code>\overline{text}</code>	59	<code>\rightarrow</code>	54
<code>\owns</code>	54	<code>\Rightarrow</code>	54
<code>\P</code>	71	<code>\rightharpoondown</code>	54
<code>\pagebreak</code>	38	<code>\rightharpoonup</code>	54
<code>\pagenumbering</code>	62	<code>\rightleftharpoons</code>	55
<code>\pageref</code>	15	<code>\rightmargin</code>	23
<code>\pagestyle</code>	62	<code>\rm</code>	8
<code>\paragraph</code>	14	<code>\rmfamily</code>	7
<code>\parallel</code>	54	<code>\roman</code>	44
<code>\parbox</code>	68	<code>\rq</code>	71
<code>\parindent</code>	24, 47	<code>\rule</code>	75
<code>\parsep</code>	23	<code>\S</code>	71
<code>\parskip</code>	47	<code>\savebox</code>	68
<code>\parskip example</code>	23	<code>\sbox</code>	69

<code>\sc</code>	8	<code>\supset</code>	55
<code>\scriptsize</code>	8	<code>\supseteq</code>	55
<code>\scshape</code>	7	<code>\surd</code>	55
<code>\searrow</code>	55	<code>\swarrow</code>	56
<code>\sec</code>	58	<code>\symbol</code>	70
<code>\section</code>	14	<code>\t</code> (tie-after accent).....	74
<code>\seename</code>	78	<code>\TAB</code>	64
<code>\selectfont</code>	10	<code>\tabbingsep</code>	30
<code>\setcounter</code>	45	<code>\tabcolsep</code>	32
<code>\setlength</code>	46	<code>\tableofcontents</code>	77
<code>\setminus</code>	55	<code>\tan</code>	58
<code>\settodepth</code>	46	<code>\tanh</code>	58
<code>\settoheight</code>	46	<code>\tau</code>	56
<code>\settowidth</code>	46	<code>\telephone</code>	81
<code>\sf</code>	8	<code>\TeX</code>	71
<code>\sffamily</code>	7	<code>\textascenderwordmark</code>	72
<code>\sharp</code>	55	<code>\textasciicircum</code>	71
<code>\shortstack</code>	28	<code>\textasciitilde</code>	71
<code>\sigma</code>	55	<code>\textasteriskcentered</code>	71
<code>\Sigma</code>	55	<code>\textbackslash</code>	71
<code>\signature</code>	80	<code>\textbar</code>	71
<code>\sim</code>	55	<code>\textbardbl</code>	71
<code>\simeq</code>	55	<code>\textbf</code>	7
<code>\sin</code>	58	<code>\textbigcircle</code>	71
<code>\sinh</code>	58	<code>\textbraceleft</code>	71
<code>\sl</code>	8	<code>\textbraceright</code>	71
<code>\slshape</code>	7	<code>\textbullet</code>	71
<code>\small</code>	8	<code>\textcapitalwordmark</code>	72
<code>\smallint</code>	55	<code>\textcircled{letter}</code>	71
<code>\smallskip</code>	65	<code>\textcompwordmark</code>	72
<code>\smallskipamount</code>	65	<code>\textcopyright</code>	70
<code>\smile</code>	55	<code>\textdagger</code>	72
<code>\SPACE</code>	64	<code>\textdaggerdbl</code>	72
<code>\spadesuit</code>	55	<code>\textdollar</code> (or \$).....	72
<code>\sqcap</code>	55	<code>\textellipsis</code>	71
<code>\sqcup</code>	55	<code>\textemdash</code> (or ---).....	72
<code>\sqrt[root]{arg}</code>	59	<code>\textendash</code> (or --).....	72
<code>\sqsubset</code>	55	<code>\texteuro</code>	72
<code>\sqsubseteq</code>	55	<code>\textexclamdown</code> (or !‘).....	72
<code>\sqsupset</code>	55	<code>\textfloatsep</code>	21
<code>\sqsupseteq</code>	55	<code>\textfraction</code>	20
<code>\SS</code> (SS).....	75	<code>\textgreater</code>	72
<code>\ss</code> (ß).....	75	<code>\textheight</code>	12
<code>\stackrel{text}{relation}</code>	59	<code>\textit</code>	7
<code>\star</code>	55	<code>\textleftarrow</code>	72
<code>\startbreaks</code>	80	<code>\textless</code>	72
<code>\stepcounter</code>	45	<code>\textmd</code>	7
<code>\stop</code>	83	<code>\textnormal</code>	7
<code>\stopbreaks</code>	80	<code>\textordfeminine</code>	72
<code>\subparagraph</code>	14	<code>\textordmasculine</code>	72
<code>\subsection</code>	14	<code>\textparagraph</code>	71
<code>\subset</code>	55	<code>\textperiodcentered</code>	72
<code>\subseteq</code>	55	<code>\textquestiondown</code> (or ?‘).....	72
<code>\subsubsection</code>	14	<code>\textquotedblleft</code> (or ‘‘).....	72
<code>\succ</code>	55	<code>\textquotedblright</code> (or ’).....	72
<code>\succeq</code>	55	<code>\textquoteleft</code> (or ‘).....	72
<code>\sum</code>	55	<code>\textquoteright</code> (or ’).....	72
<code>\sup</code>	58	<code>\textquotestraightbase</code>	73

<code>\textquotestraightdblbase</code>	73	<code>\uplus</code>	56
<code>\textregistered</code>	73	<code>\upshape</code>	7
<code>\textrightarrow</code>	73	<code>\upsilon</code>	56
<code>\textrm</code>	7	<code>\Upsilon</code>	56
<code>\textsc</code>	7	<code>\usebox</code>	69
<code>\textsf</code>	7	<code>\usecounter</code>	44
<code>\textsl</code>	7	<code>\usefont</code>	10
<code>\textsterling</code>	71	<code>\usepackage</code>	6
<code>\textthreequartersemdash</code>	73	<code>\v</code> (breve accent)	74
<code>\texttrademark</code>	73	<code>\value</code>	44
<code>\texttt</code>	7	<code>\varepsilon</code>	56
<code>\texttwelveudash</code>	73	<code>\varphi</code>	56
<code>\textunderscore</code>	73	<code>\varpi</code>	56
<code>\textup</code>	7	<code>\varrho</code>	56
<code>\textvisiblespace</code>	73	<code>\varsigma</code>	56
<code>\textwidth</code>	12	<code>\vartheta</code>	56
<code>\th (b)</code>	75	<code>\vdash</code>	56
<code>\TH (b)</code>	75	<code>\vdots</code>	60
<code>\thanks{text}</code>	62	<code>\vec</code>	58
<code>\theta</code>	56	<code>\vector</code>	28
<code>\thicklines</code>	27	<code>\vee</code>	56
<code>\thinlines</code>	27	<code>\verb</code>	35
<code>\thinspace</code>	64	<code>\vert</code>	57
<code>\thispagestyle</code>	63	<code>\Vert</code>	56
<code>\tilde</code>	58	<code>\vfill</code>	65
<code>\times</code>	56	<code>\vline</code>	33
<code>\tiny</code>	8	<code>\vspace</code>	66
<code>\title{text}</code>	62	<code>\wedge</code>	57
<code>\to</code>	56	<code>\widehat</code>	58
<code>\today</code>	75	<code>\width</code>	46
<code>\top</code>	56	<code>\wp</code>	57
<code>\topfraction</code>	20	<code>\wr</code>	57
<code>\topmargin</code>	13	<code>\xi</code>	57
<code>\topnumber</code>	21	<code>\Xi</code>	57
<code>\topsep</code>	23	<code>\year</code>	45
<code>\topskip</code>	13	<code>\zeta</code>	57
<code>\totalheight</code>	46		
<code>\totalnumber</code>	21		
<code>\triangle</code>	56	{...} for required arguments	3
<code>\triangleleft</code>	56		
<code>\triangleright</code>	56		
<code>\tt</code>	8		
<code>\ttfamily</code>	7	1	
<code>\twocolumn</code>	11	10pt option	5
<code>\typein</code>	82	11pt option	5
<code>\typeout</code>	82	12pt option	5
<code>\u</code> (breve accent)	74		
<code>\unboldmath</code>	49	A	
<code>\underbar</code>	74	a4paper option	5
<code>\underbrace{math}</code>	59	a5paper option	5
<code>\underline{text}</code>	59	abstract environment	16
<code>\unitlength</code>	24	array environment	16
<code>\unlhd</code>	56	article class	5
<code>\unrhd</code>	56		
<code>\uparrow</code>	56	B	
<code>\Uparrow</code>	56	b5paper option	5
<code>\updownarrow</code>	56		
<code>\Updownarrow</code>	56		

book class 5

C

center environment 17

D

description environment 17

displaymath environment 17, 49

document environment 18

draft option 5

E

enumerate environment 18

eqnarray environment 19

equation environment 19, 49

executivepaper option 5

F

figure 19

final option 5

fleqn option 5

flushleft environment 21

flushright environment 21

I

indexspace 78

itemize environment 22

L

landscape option 5

latex command 3

latexrefman-discuss@gna.org email address ... 2

legalpaper option 5

leqno option 5

letter 23

letter class 5

letterpaper option 5

list 23

LR box 25

lrbox 67

lualatex command 3

M

math environment 24, 49

minipage environment 24

N

notitlepage option 5

O

onecolumn option 5

oneside option 5

openany option 5

openbib option 5

openright option 5

P

pdflatex command 3

picture 24

printindex 78

Q

quotation 28

quote 28

R

report class 5

S

secnumdepth counter 14

slides class 5

T

tabbing environment 28

table 30

tabular environment 30

textcomp package 70

thebibliography 33

theorem environment 34

titlepage environment 34

titlepage option 5

twocolumn option 5

twoside option 5

V

verbatim environment 35

verse environment 35

X

xelatex command 3